PolyOne

MATERIAL SAFETY DATA SHEET **DB4630 RED**

Version Number 1.1 Revision Date 03/21/2014 Page 1 of 6 Print Date 3/25/2014

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	DB4630 RED		
Product code	:	FO20025878		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **DB4630 RED**

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **DB4630 RED**

sion Date 03/21/2014			Print	Page 3 Date 3/25/2	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage	: Keep containers dry and tightly closed to avoid moisture absor and contamination. Store in a cool dry place.			e absorption	
8.]	EXPOSURE	CONTROLS/PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: Safety glasses with side-shields				
Hand protection	: P	: Protective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures Exposure limit(s)		leat only in areas with appropr ppropriate exhaust ventilation			
Components	Value	Exposure time	Exposure type		
	5 mg/m3	-		List:	
Calcium carbonate	J mg/mJ	PEL:	Respirable fraction.		
Calcium carbonate	15 mg/m3	PEL: PEL:	Total dust.	OSHA Z1	
	-		<u>.</u>	OSHA Z1 OSHA Z1	
	15 mg/m3	PEL: Time Weighted Average	<u>.</u>	OSHA ZI OSHA ZI MX OEL	
	15 mg/m3 10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Total dust.	OSHA Z1 OSHA Z1 MX OEL	
	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust.	OSHA Z1 OSHA Z1 MX OEL MX OEL	
Form	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquio	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo	Total dust. DPERTIES uration rate : No	OSHA ZI OSHA ZI MX OEL	
Form	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquio	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo bus, liquid Specif	Total dust. DPERTIES uration rate : No ic Gravity : No	OSHA ZI OSHA ZI MX OEL MX OEL	
Form Appearance	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : visco	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo bus, liquid Specif Bulk d	Total dust. Total dust. DPERTIES uration rate : No ic Gravity : No ensity : No	OSHA ZI OSHA ZI MX OEL MX OEL	
Form Appearance Colour Odour Melting point/range	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : visco : RED : very : not a	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo pus, liquid Specif Bulk d faint Vapou pplicable Vapou	Total dust. Total dust. DPERTIES uration rate : No ic Gravity : No ensity : No r pressure : No r density : No	OSHA ZI OSHA ZI MX OEL MX OEL MX OEL	
Form Appearance Colour Odour Melting point/range Boiling Point:	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : visco : RED : very : not a : not a	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo pus, liquid Specif faint Vapou pplicable Vapou pplicable pH	Total dust. Total dust. DPERTIES uration rate : No ic Gravity : No ensity : No r pressure : No r density : No	OSHA ZI OSHA ZI MX OEL MX OEL	
Form Appearance Colour Odour Melting point/range	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : visco : RED : very : not a	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo pus, liquid Specif faint Vapou pplicable Vapou pplicable pH	Total dust. Total dust. DPERTIES uration rate : No ic Gravity : No ensity : No r pressure : No r density : No	OSHA ZI OSHA ZI MX OEL MX OEL MX OEL	
Form Appearance Colour Odour Melting point/range Boiling Point:	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : visco : RED : very : not a : imm	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo pus, liquid Specif faint Vapou pplicable Vapou pplicable pH	Total dust. Total dust. DPERTIES uration rate : No ic Gravity : No ensity : No r pressure : No r density : No : No	OSHA Z1 OSHA Z1 MX OEL MX OEL t established t determined t determined t determined t determined	



MATERIAL SAFETY DATA SHEET **DB4630 RED**

Version Number 1.1 Revision Date 03/21/2014 Page 4 of 6 Print Date 3/25/2014

Stability	: The product is stable if stored and handled as prescribed.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.	
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). 	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification,

Version Number 1.1



Page 5 of 6

MATERIAL SAFETY DATA SHEET **DB4630 RED**

sion Date 03/21/2014	Print Date 3/25/20
	transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
65	
65 SARA Title III Section 302	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance
65 SARA Title III Section 302	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance
65 SARA Title III Section 302	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulation
65 SARA Title III Section 302 Unless specific chemicals and SARA Title III Section 313	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulat Toxic Chemicals:
65 SARA Title III Section 302 Unless specific chemicals and SARA Title III Section 313	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulat Toxic Chemicals:
65 SARA Title III Section 302 Unless specific chemicals are SARA Title III Section 313 Unless specific chemicals are Canadian Regulations:	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulati Toxic Chemicals:
65 SARA Title III Section 302 Unless specific chemicals are SARA Title III Section 313 Unless specific chemicals are Canadian Regulations:	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulati Toxic Chemicals: e identified under this section, this product is Not Applicable under this regulati
65 SARA Title III Section 302 Unless specific chemicals are SARA Title III Section 313 Unless specific chemicals are Canadian Regulations: National Pollutant Re	California to cause birth defects or other reproductive harm. Extremely Hazardous Substance e identified under this section, this product is Not Applicable under this regulati Toxic Chemicals: e identified under this section, this product is Not Applicable under this regulati

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET **DB4630 RED**

Version Number 1.1 Revision Date 03/21/2014 Page 6 of 6 Print Date 3/25/2014

		Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.