PolvOne

MATERIAL SAFETY DATA SHEET **VBX3471B DX9 BLACK**

Version Number 1.1 Revision Date 03/29/2014

Page 1 of 6 Print Date 4/5/2014

1. PRODUCT AND COMPANY IDENTIFICATION				
POLYONE CORPORATI 8155 Cobb Center Drive,		aw, GA 30152		
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	VBX3471B DX9 BLACK		
Product code	:	FO20026820		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium hydroxide	1305-62-0	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Particulates, like other inert materials can be mechanically irritating.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	

PolyOne.

MATERIAL SAFETY DATA SHEET **VBX3471B DX9 BLACK**

Version Number 1.1 Revision Date 03/29/2014 Page 2 of 6 Print Date 4/5/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **VBX3471B DX9 BLACK**

sion Number 1.1 vision Date 03/29/2014		Page 3 of Print Date 4/5/201
		only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium hydroxide	5 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	Recommended exposure limit (REL):		NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range
- solid
 powder, granular
 BLACK
 very faint
 Not determined
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicable
 Not determined
 Not determined
 not applicable
 not applicable

PolvOne

MATERIAL SAFETY DATA SHEET **VBX3471B DX9 BLACK**

Version Number 1.1 Revision Date 03/29/2014

_

Page 4 of 6 Print Date 4/5/2014

Boiling Point: Water solubility	: not applicable pH : not applicable : insoluble
	10. STABILITY AND REACTIVITY
Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1305-62-0	Calcium hydroxide	Irritant	Eyes, Skin, Respiratory
			system.
		Systemic effects	Eyes, Skin, Respiratory
			system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1305-62-0	Calcium hydroxide	Oral LD50	7,340 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name	OSHA	IARC	NTP
-----------------------	------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

PolyOne.

MATERIAL SAFETY DATA SHEET **VBX3471B DX9 BLACK**

Version Number 1.1 Revision Date 03/29/2014 Page 5 of 6 Print Date 4/5/2014

NTP Carcinogen Classification 1 - The component is known to 2 - The component is reasonable	be a	human carcinogen. ticipated to be a human carcinogen.
	12	2. ECOLOGICAL INFORMATION
Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available
Additional advice	:	no data available
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO/IMDG (maritime)	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)

blvUn<u>e</u>

MATERIAL SAFETY DATA SHEET VBX3471B DX9 BLACK

Version Number 1.1 Revision Date 03/29/2014 Page 6 of 6 Print Date 4/5/2014

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification	:	Not controlled.
DSL	:	DSL status has not been determined. Quantity use in Canada may be

restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.