PolvOne

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 1 of 7 Print Date 4/8/2014

1. PRODUCT AND COMPANY IDENTIFICATION					
POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152					
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE			
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	LX-P-1000 PINK MASKING LATEX			
Product code	:	FO20027238			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. Information provided on the health effects of this product is based on individual components. In addition, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact, Inhalation, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye and skin irritation.	
Skin	:	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	

PolyOne.

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 2 of 7 Print Date 4/8/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Never give anything by mouth to an unconscious person. Seek medical attention if necessary. Do not induce vomiting without medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 no data available no data available no data available Carbon dioxide (CO2), Water, Foam, Dry chemical. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Burning dry latex produces dense black smoke with the possibility of
Unusual Fire/Explosion Hazards	burning dry latex produces dense black shoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid

PolyOne.

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 3 of 7 Print Date 4/8/2014

		7. HANDLING AND STORAGE
Handling	:	Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.
Storage	:	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. Airborne contaminant levels should be maintained below the occupational exposure guidelines.
Eye/Face Protection	:	Safety glasses with side-shields Wear goggles or face shield during operations that present a splash potential.
Hand protection	:	Impervious gloves such as rubber or PVC
Skin and body protection	:	Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.
Engineering measures	:	Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)		

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 4 of 7 Print Date 4/8/2014

: Slower than Butyl Acetate

: Not determined

: Not applicable

: Not established

: Heavier than air.

: Not determined

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Evapouration rate

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

: liquid

: liquid

: PINK

: slight

: not applicable

: Not established

Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

Form

: completely miscible

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Extremes of temperature and direct sunlight. Keep from freezing.
Incompatible Materials	:	Acids, metal salts, and solvents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 5 of 7 Print Date 4/8/2014

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Fitanium dioxide	no	2B	no
2B - The component is poNTP Carcinogen Classifi1 - The component is known	cinogenic to humans. robably carcinogenic to huma ossibly carcinogenic to huma	ns. n.		
	12. ECOLOGICAI	L INFORMATION		
Persistence and degradab	ility : no data available			
Environmental Toxicity	: no data available			
Bioaccumulation Potentia	al : no data available			
Additional advice	: no data available	:		
	13. DISPOSAL CO	DNSIDERATIONS		
Product	generator of was classification, tra	recycling is preferred te material has the re ansportation and disp al, state/provincial an	sponsibility for pr osal in accordance	oper waste with
Contaminated packaging	material has the transportation an	ferred when possible responsibility for pro d disposal in accorda and local regulations.	oper waste classific ance with applicab	cation,
	14. TRANSPORT	INFORMATION		
U.S. DOT Classification	: Refer to specific	regulation.		
ICAO/IATA	: Refer to specific	regulation.		
IMO/IMDG (maritime)	: Refer to specific	regulation.		
	15. REGULATORY	Y INFORMATION		
US Regulations:				
OSHA Status	: Classified as haz	ardous based on con	ponents.	

PolyOne

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 6 of 7 Print Date 4/8/2014

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification	:	D2A
DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET LX-P-1000 PINK MASKING LATEX

Version Number 1.1 Revision Date 03/30/2014 Page 7 of 7 Print Date <u>4/8/2014</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.