PolvOne

MATERIAL SAFETY DATA SHEET

Geon[™] DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 1 of 8 Print Date 3/28/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Geon [™] DB4125 Red
Product code	:	FO20028124
Chemical Name	:	Mixture
CAS-No.	:	Mixture

CAS-No.:MixtureProduct Use:Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Bisphenol A - Epichlorohydrin polymer	25068-38-6	1 - 5
Antimony trioxide	1309-64-4	1 - 5
Barium sulfate	7727-43-7	1 - 5
Miscellaneous Organotin Compounds	0-03-3	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: Inl	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation : Inh trac	alation of airborne droplets may cause irritation of the respiratory t.			
6	y be harmful if swallowed. y cause eye and skin irritation.			
	berience shows no unusual dermatitis hazard from routine handling.			

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 8 Print Date 3/28/2014

Medical Conditions: None known.Aggravated by Exposure:					
		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
		5. FIREFIGHTING MEASURES			
Flash point	:	no data available			
Flammable Limits					
Upper explosion limit	:	no data available			
Lower explosion limit	:	no data available			
Auto-ignition temperature	:	Not applicable			
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.			
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	:	May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. A(CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.			
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.			

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 8 Print Date 3/28/2014

Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.	
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 8 Print Date 3/28/2014

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
Miscellaneous Organotin Compounds	0.1 mg/m3	Time Weighted Average (TWA):	Total as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	Total as Sn	ACGIH
	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	MX OEL
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility liquid
viscous, liquid
RED
very faint
not applicable
not applicable
immiscible

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY

Stability

: The product is stable if stored and handled as prescribed.

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 5 of 8 Print Date 3/28/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25068-38-6	Bisphenol A -	Irritant	Skin.
	Epichlorohydrin polymer		
		sensitizer	Skin.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
0-03-3	Miscellaneous Organotin	Systemic effects	Eyes, Skin, Liver, central
	Compounds		nervous system (CNS), heart
			or circulatory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
25068-38-6	Bisphenol A -	Oral LD50	11,400 mg/kg	rat
	Epichlorohydrin polymer	Dermal LD50	> 6,000 mg/kg	rabbit
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

PolyOne

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014

Page 6 of 8 Print Date 3/28/2014

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

 $2\mathbf{B}$ - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.			
Bioaccumulation Potential	: no data available			
Additional advice	: no data available			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Refer to specific regulation.			
ICAO/IATA	: Refer to specific regulation.			
IMO/IMDG (maritime)	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

ersion Number 1.1 evision Date 03/13/2014				Pr	Page 7 of ٤ int Date 3/28/2014	
OSHA Status :	Classified as hazardous based on components.					
TSCA Status :	A Status : All components of this product are listed on or exempt from the TSCA Inventory.					
US. EPA CERCLA Hazardous Subs	stances (40 CFR 3	02)				
not applicable						
California Proposition : 65	WARNING! Th California to cau		ontains a chem	iical know	wn to the State of	
SARA Title III Section 302 Extreme	ely Hazardous Sul	ostance				
Unless specific chemicals are identi	fied under this sec	tion, this pro	oduct is Not A	pplicable	under this regulatior	
SARA Title III Section 313 Toxic C	hemicals:					
Unlass specific chemicals are identi	fied under this say	tion this nr	duct is Not A	nnliachla	under this regulation	
Unless specific chemicals are identi Chemical Name	fied under uns sec		AS-No.		percent	
ANTIMONY COMPOUNDS)9-64-4	1.00 - :		
		15	JJ 01 1	1.00	5.00	
Canadian Regulations:						
National Pollutant Release Ir	wentory (NPRI)					
Chemical Name	iveniory (IVFKI)	CAS-No.	Weig	nt	NPRI ID#	
			percer			
Antimony trioxide		1309-64-4	1.00 -			
	DOA					
WHMIS Classification :	D2A					
WHMIS Ingredient Disclosu	re List					
CAS-No. 1309-64-4 0-03-3						
DSL :	All components Substances List (Canadian	Domestic	
National Inventories:						

PolyOne

MATERIAL SAFETY DATA SHEET Geon™ DB4125 Red

Version Number 1.1 Revision Date 03/13/2014 Page 8 of 8 Print Date 3/28/2014

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.