MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013

Page 1 of 7 Print Date 4/8/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Geon [™] Sensation DB4962 White
Product code	:	FO20031149
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	0.1 - 1
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013 Page 2 of 7 Print Date 4/8/2013

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013		Page 3 of 7 Print Date 4/8/2013
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPO)SU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components Value Exposure time Exposure type List: OSHA Z1 Calcium carbonate 5 mg/m3 PEL: Respirable fraction. PEL: Total dust. OSHA Z1 15 mg/m3 10 mg/m3 Time Weighted Average MX OEL (TWA): 20 mg/m3 Short Term Exposure Limit MX OEL (STEL): Titanium dioxide 10 mg/m3 Time Weighted Average ACGIH (TWA): 15 mg/m3 PEL: Total dust. OSHA Z1 10 mg/m3 Time Weighted Average Total dust. OSHA Z1A (TWA): Time Weighted Average 10 mg/m3 as Ti MX OEL (TWA): Short Term Exposure Limit 20 mg/m3 as Ti MX OEL (STEL):

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: liquid

Evaporation rate

: Not established

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013 Page 4 of 7 Print Date 4/8/2013

Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 viscous, liquid WHITE very faint not applicable not applicable immiscible 	Specific Gravity Bulk density Vapour pressure Vapour density pH		
	10. STABILITY A	ND REACTIVITY		T
Stability	: The product is sta	able if stored and handled as	prescribed.	
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Keep away from decomposition, d	oxidizing agents and open fl lo not overheat.	ame. To avoid thermal	
Incompatible Materials		h strong acids and oxidizing polymers and acetal copolyr		
Hazardous decomposition products	(NOx), hydrogen smoke are all pos degradation. As after one hour at	CO2), carbon monoxide (CO a chloride (HCl), other hazard ssible. Prolonged heating ma a general rule of thumb, deg 177 °C (350 °F), after 10 mi minutes at 232 °C (450 °F).	dous materials, and ay result in product radation begins to occur nutes at 204 °C (400	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013 Page 5 of 7 Print Date 4/8/2013

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013 Page 6 of 7 Print Date 4/8/2013

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Miscellaneous Zinc Compou			CAS-No.	Weight percent	NPRI ID#
	Miscellaneous Zinc Compounds			0.10 - 1.00	241
WHMIS Classification	:	D2A			
DSL	:	DSL status has restricted by re		ined. Quantity use	e in Canada may
ational Inventories:					
Australia AICS	:	Not determined	1		
China IECS	:	Not determined	1		
Europe EINECS	:	Not determined	1		
Japan ENCS	:	Not determined	1		
Korea KECI	:	Not determined	1		
Philippines PICCS	:	Not determined	1		

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET Geon™ Sensation DB4962 White

Version Number 1.0 Revision Date 04/08/2013 Page 7 of 7 Print Date 4/8/2013

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.