MATERIAL SAFETY DATA SHEET WB-1021-B REDWOOD COATING

Version Number 1.0 Revision Date 05/09/2013 Page 1 of 6 Print Date 5/10/2013

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	WB-1021-B REDWOOD COATING		
Product code	:	FO20031291		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use		Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Iron oxide	1309-37-1	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. Information provided on the health effects of this product is based on individual components. In addition, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact, Inhalation, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	:
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne

MATERIAL SAFETY DATA SHEET **WB-1021-B REDWOOD COATING**

Version Number 1.0 Revision Date 05/09/2013 Page 2 of 6 Print Date 5/10/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Never give anything by mouth to an unconscious person. Seek medical attention if necessary. Do not induce vomiting without medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit	 no data available no data available
Auto-ignition temperature Suitable extinguishing media	no data availableCarbon dioxide (CO2), Water, Foam, Dry chemical.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
Unusual Fire/Explosion Hazards	 Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid

PolyOne.

MATERIAL SAFETY DATA SHEET **WB-1021-B REDWOOD COATING**

Version Number 1.0 Revision Date 05/09/2013 Page 3 of 6 Print Date 5/10/2013

		7. HANDLING AND STORAGE
Handling	:	Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.
Storage	:	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.
8. EX	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. Airborne contaminant levels should be maintained below the occupational exposure guidelines.
Eye/Face Protection	:	Safety glasses with side-shields Wear goggles or face shield during operations that present a splash potential.
Hand protection	:	Impervious gloves such as rubber or PVC
Skin and body protection	:	Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.
Engineering measures	:	Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET WB-1021-B REDWOOD COATING

Version Number 1.0 Revision Date 05/09/2013 Page 4 of 6 Print Date 5/10/2013

Components	Value	Expos	ure time	Exposure typ			
Iron oxide	10 mg/m3 PEL:			Fume.	OSHA Z		
	5 mg/m3	(TWA):		as Fe	MX OEI		
	10 mg/m3			as Fe	MX OEI		
	5 mg/m3	Time Weig	hted Average WA):	Respirable frac	tion. ACGIH		
	9. PHYSI(CAL AND CH	IEMICAL PRO	PERTIES			
Form	: liqui	d	Evapor	Evapouration rate : Slower than Buty Acetate			
Appearance	: liqui	d	Specifi	c Gravity :	Not determined		
Colour	: RED		Bulk d		Not applicable		
Odour	: sligh			r pressure :	Not established		
Melting point/range		pplicable		r density :	Heavier than air		
Boiling Point:	: Not o	established	pH	•	Not determined		
Water solubility		oletely miscibl					
•	-						
	10. 8	STABILITY A	AND REACTIV	ITY			
Stability	: T	he product is s	table if stored a	nd handled as pres	scribed.		
Hazardous Polymerizatio	n : W	Vill not occur.					
Conditions to avoid	: E	xtremes of ten	perature and dir	ect sunlight. Kee	p from freezing.		
Incompatible Materials	: A	cids, metal sal	ts, and solvents				
Hazardous decomposition products				nonoxide (CO), or ls, and smoke are			
	11. TO	XICOLOGI	CAL INFORMA	ATION			
This mixture has not been health data for the individ					ted are based on ex		
			.1. 111		• • • • •		
<u>Toxicity Overview</u> This product contains the	following co	mponents whi	ch in their pure	form have the follo	owing characterist		
This product contains the		-					
This product contains the CAS-No.	following co Chemica	-	Effect Systemic effect	Ta	arget Organ		

Persistence and degradability

: no data available

: no data available

Environmental Toxicity

PolyOne.

MATERIAL SAFETY DATA SHEET **WB-1021-B REDWOOD COATING**

Version Number 1.0 Revision Date 05/09/2013 Page 5 of 6 Print Date 5/10/2013

Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	stremely Hazardous Substance

PolvOne

MATERIAL SAFETY DATA SHEET WB-1021-B REDWOOD COATING

Version Number 1.0 Revision Date 05/09/2013 Page 6 of 6 Print Date 5/10/2013

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Branched-nonylphenol, ethoxylate	68412-54-4	0.10 - 1.00	186
		0.10 - 1.00	

WHMIS Classification	:	Not controlled.		
DSL	:	DSL status has not been determined. Quantity use in Canada may be restricted by regulations.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.