MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013

Page 1 of 6 Print Date 10/2/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Geon™ DM758C MATTE GREEN 65A
Product code	:	FO20031573
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013 Page 2 of 6 Print Date 10/2/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013		Page 3 of 6 Print Date <i>10/2/2013</i>
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXF	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour
- : liquid : viscous, liquid : GREEN : very faint

Evapouration rate : Not established Specific Gravity : Not determined Bulk density Vapour pressure

: Not applicable : Not determined

MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013

Melting point/range Boiling Point: Water solubility	not applicablenot applicableimmiscible	Vapour density pH	Not determinedNot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: The product is stab	le if stored and handled a	s prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open a not overheat.	flame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi degradation. As a after one hour at 1	O2), carbon monoxide (C hloride (HCl), other hazar ible. Prolonged heating m general rule of thumb, deg 77 °C (350 °F), after 10 m hinutes at 232 °C (450 °F)	rdous materials, and hay result in product gradation begins to occur hinutes at 204 °C (400

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	0	Themical Name	Effect	Target Organ
112926-00-8		amorphous, tated and gel	Irritant	Respiratory system, Eyes.
1317-65-3	Calciu	m carbonate	Irritant	Eyes, Skin.
			Systemic effects	Eyes, Skin, Respiratory system.
			CAL INFORMATION	1
Persistence and deg	radability	: Not readily bi	odegradable.	
Environmental Tox	icity	: Environmenta whole.	l toxicity has not been	established for this mixture as a
Bioaccumulation Po	otential	: no data availa	ble	
Additional advice		: no data availa	ble	
		12 DISDOSAT	CONSIDERATIONS	1



Page 4 of 6 Print Date 10/2/2013



MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013	Page 5 of 6 Print Date <i>10/2/2013</i>
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	

PolyOne

MATERIAL SAFETY DATA SHEET Geon™ DM758C MATTE GREEN 65A

Version Number 1.1 Revision Date 10/02/2013 Page 6 of 6 Print Date 10/2/2013

Chemical Name		CAS-No.	Weight	NPRI ID#	
Phthalocyanine green			1328-53-6	0.10 - 1.00	
Miscellaneous Zinc Compoun	ıds		0-05-5	0.10 - 1.00	241
WHMIS Classification	:	All component	s of this product a (DSL) or are exe	are on the Canadia empt.	n Domestic
ational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.