STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

Page 1 of 19 Print Date 10/30/2015

SAFETY DATA SHEET

STAN-TONE EPX-21345 ORANGE

Section 1. Identification		
		STAN-TONE EPX-21345 ORANGE
GHS product identifier	:	
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20031899
Product type	:	liquid
<u>Relevant identified uses of the subs</u> Product use	stance :	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

GHS label elements



STAN-TONE EPX-21345 ORANGE

Version Numbe	er 1.2
Revision Date	10/29/2015

Page 2 of 19 Print Date 10/30/2015

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Causes skin and eye irritation. May cause an allergic skin reaction. May cause cancer.
Precautionary statements		
General Prevention Response	::	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash
		with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Store in a well-ventilated place.
Disposal	:	Dispose of contents and container in accordance with all local,
		regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20031899

CAS number/other identifiers

Ingredient name	%	CAS number
Bisphenol A - Epichlorohydrin polymer	60 - 100	25068-38-6



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 3 of 19 Print Date 10/30/2015

Lead chromate	10 - 30	7758-97-6
Molybdate orange (Lead chromate pigment)	5 - 10	12656-85-8
Lead sulfate	1 - 5	7446-14-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting

ne

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 4 of 19 Print Date 10/30/2015

unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	:::::::::::::::::::::::::::::::::::::::	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. Irritating to mouth, throat and stomach.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical att	tentio	on and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

<u>vOne</u>

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

Page 5 of 19 Print Date 10/30/2015

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment	nt ar	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate



STAN-TONE EPX-21345 ORANGE

Version Number 1.2	Page 6 of 19
Revision Date 10/29/2015	Print Date 10/30/2015

waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill:Stop leak if without risk. Move containers from spill area. Approach
release from upwind. Prevent entry into sewers, water courses,
basements or confined areas. Wash spillages into an effluent treatment
plant or proceed as follows. Contain and collect spillage with non-
combustible, absorbent material e.g. sand, earth, vermiculite or
diatomaceous earth and place in container for disposal according to
local regulations (see Section 13). Dispose of via a licensed waste
disposal contractor. Contaminated absorbent material may pose the
same hazard as the spilled product. Note: see Section 1 for emergency
contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

<u>olyOne</u>.

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 7 of 19 Print Date 10/30/2015

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Lead chromate	ACGIH TLV (2012-03-05) expressed as Cr
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 0.012 mg/m3
	ACGIH TLV (1994-09-01) measured as Pb
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 0.05 mg/m3
	OSHA PEL (2006-11-27) expressed as Cr
	PEL: Permissible Exposure Level 0.005 mg/m3
	OSHA PEL Z2 (2006-11-27)
	Exposure limit value-ceiling concentration 0.001 mg/m3
	NIOSH REL (2010-09-01) expressed as Cr
	Time Weighted Average (TWA) 0.0002 mg/m3
	OSHA PEL 1989 (1989-03-01) Calculated as CrO3
	Exposure limit value-ceiling concentration 0.1 mg/m3
	OSHA PEL 1989 (1989-03-01) measured as Pb
	PEL: Permissible Exposure Level 0.075 mg/m3
Molybdate orange (Lead chromate	OSHA PEL (1993-06-30) expressed as Mo
pigment)	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	OSHA PEL (2006-11-27) expressed as Cr
	PEL: Permissible Exposure Level 0.005 mg/m3
	OSHA PEL Z2 (2006-11-27)
	Exposure limit value-ceiling concentration 0.001 mg/m3
	NIOSH REL (2010-09-01) expressed as Cr
	Time Weighted Average (TWA) 0.0002 mg/m3
	Time Weighted Average (TWA) 0.5 mg/m3
	OSHA PEL 1989 (1989-03-01) Calculated as CrO3
	Exposure limit value-ceiling concentration 0.1 mg/m3
	OSHA PEL 1989 (1989-03-01) measured as Pb
	PEL: Permissible Exposure Level 0.075 mg/m3
	OSHA PEL 1989 (1989-03-01) expressed as Mo
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL 1989 (1989-03-01) expressed as Cr
	PEL: Permissible Exposure Level 0.5 mg/m3
	ACGIH TLV (1995-05-23) measured as Pb
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 0.05 mg/m3
	ACGIH TLV (2001-02-22) expressed as Mo



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

	TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3 Form: Inhalable fraction TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Respirable fraction
Lead sulfate	NIOSH REL (2005-09-30)
	OSHA PEL 1989 (1989-03-01) measured as Pb PEL: Permissible Exposure Level 0.05 mg/m3 ACGIH TLV (1995-05-23) measured as Pb TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.05 mg/m3
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be
	8/19



STAN-TONE EPX-21345 ORANGE

Version Number 1.2	Page 9 of 19
Revision Date 10/29/2015	Print Date 10/30/2015

		noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures,
		consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [Paste.]
Color		ORANGE
Odor	:	Not available.
Odor threshold		Not available.
0		Not available.
pH Malking angint	:	1 (of a failed of
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
Lower and upper explosive (flammable) limits	:	Lower: Not available. Upper: Not available.
	:	200010101000 a Canadoro
(flammable) limits		Upper: Not available.
(flammable) limits Vapor pressure		Upper: Not available. Not available.
(flammable) limits Vapor pressure Vapor density		Upper: Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density		Upper: Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility		Upper: Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water	:	Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n-	:	Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water		Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature		Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available.

ne

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

Page 10 of 19 Print Date 10/30/2015

Viscosity

Dynamic: Not available. Kinematic: Not available.

Section 10. Stability and reactivity

:

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Bisphenol A - Epichlorohydr	in polymer	· -		· -
	LD50 Oral	Rat	13,600 mg/kg	-
	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	13,600 mg/kg	-
Lead chromate		•	· · ·	·
Molybdate orange (Lead chro	omate pigment)			
Lead sulfate				
Conclusion/Summary	: Mi	ixture.Not fully tested	l.	

Irritation/Corrosion



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 11 of 19 Print Date 10/30/2015

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A -	Eyes - Mild	Rabbit			-
Epichlorohydrin polymer	irritant				
· · · · ·	Eyes - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Skin - Severe	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
Conclusion/Summary		1	1	1	1
Skin	: M	ixture.Not fu	llv tested.		
Eyes		ixture.Not fu			
Respiratory		ixture.Not fu			
y	•				
Sensitization					
Conclusion/Summary					
Skin	: M	ixture.Not fu	llv tested.		
Respiratory		ixture.Not fu			
y	•				
Mutagenicity					
Conclusion/Summary	: M	lixture.Not fu	llv tested.		
Concrusion, Summary	• • • •				
Carcinogenicity					
Conclusion/Summary	: M	ixture.Not fu	lly tested.		
Classification			5		
Product/ingredient	OSHA	IARC	NTP		
name					
Lead chromate	+	1	Known	to be a human card	inogen.Reasonably
				ated to be a human	
	+	1			<u> </u>
Molybdate orange (Lead		1			
Molybdate orange (Lead chromate pigment)					

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

<u>PolyOne</u>

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 12 of 19 Print Date 10/30/2015

Conclusion/Summary	:	Mixture.Not fully tested.
Specific target organ toxicity (single Not available.	e exp	<u>osure)</u>
Specific target organ toxicity (repea Not available.	ated o	exposure)
Aspiration hazard Not available.		
Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	::	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. Irritating to mouth, throat and stomach.
Symptoms related to the physical, cl	hemi	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering
Inhalation Skin contact	:	redness No specific data. Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effects and	also c	chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

Page 13 of 19 Print Date 10/30/2015

Conclusion/Summary	: Mixture.Not fully tested.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of toxicity	

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Lead sulfate			
	Acute LC50 148 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 750 µg/l Marine water	Fish - Fish	96 h
	Acute LC50 60,800 µg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 6,240 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 148,000 µg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 0.392 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute IC50 82 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute IC50 360 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute IC50 400 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 395 µg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 54,500 µg/l Fresh	Aquatic invertebrates.	48 h



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015

Page 14 of 19 Print Date 10/30/2015

	water		Crustacean Order	
Conclusion/Summary	:	Not available.		
<u>Persistence and degradability</u> Conclusion/Summary	:	Not available.		

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A -	2.64 - 3.78	31.00	low
Epichlorohydrin polymer			
Molybdate orange (Lead		3,600.00	high
chromate pigment)			

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

PolyOne.

STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 15 of 19 Print Date 10/30/2015

Section 14. Transport information

U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Consult mode specific transport rules
IMO/IMDG (maritime)	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	: United States - TSCA 12(b) - Chemical export notification: The following components are listed: Lead chromate Molybdate orange (Lead chromate pigment) Lead sulfate
	United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed
	United States - TSCA 5(a)2 - Proposed significant new use rules: Listed Lead chromate Molybdate orange (Lead chromate pigment) Lead sulfate
	United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Listed Lead chromate Molybdate orange (Lead chromate pigment)
	United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 4(a) - Final Test Rules: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Lead chromate Molybdate orange (Lead chromate pigment)



STAN-TONE EPX-21345 ORANGE

Version Numbe	er 1.2
Revision Date	10/29/2015

Page 16 of 19 Print Date 10/30/2015

Lead sulfate

United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor		Not listed
Chemicals)		Not listed
DEA List II Chemicals (Essential Chemicals)	:	not fisted

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Lead sulfate	7446-14-2	
		10 lb(s)
		4.54 kg

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Bisphenol A - Epichlorohydrin polymer	60 - 100	АН
Lead chromate	10 - 30	СН
Molybdate orange (Lead chromate pigment)	5 - 10	СН
Lead sulfate	1 - 5	СН



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 17 of 19 Print Date 10/30/2015

SARA 313

	Product name	CAS number	%
Form R - Reporting	Lead chromate	7758-97-6	10 - 30
requirements			
	Molybdate orange (Lead chromate pigment)	12656-85-8	5 - 10
	Lead sulfate	7446-14-2	1 - 5
Supplier notification	Lead chromate	7758-97-6	10 - 30
	Molybdate orange (Lead chromate pigment)	12656-85-8	5 - 10
	Lead sulfate	7446-14-2	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: The following components are listed:
	Lead chromate
	Lead sulfate
New York	: The following components are listed:
	Lead sulfate
New Jersey	: The following components are listed:
	Lead chromate
	Molybdate orange (Lead chromate pigment)
	Lead sulfate
Pennsylvania	: The following components are listed:
	Lead chromate
	Molybdate orange (Lead chromate pigment)
	Lead sulfate

California Prop. 65

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.

<u>olyOne</u>

STAN-TONE EPX-21345 ORANGE

Version Number 1.2	Page 18 of 19
Revision Date 10/29/2015	Print Date 10/30/2015

International regulations

International lists	:	 Australia inventory (AICS): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted. Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted. Japan inventory: All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. Korea inventory: All components are listed or exempted. New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted.
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention	:	Not listed
List Schedule II Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule III Chemicals		

Section 16. Other information

<u>History</u>		
Date of printing	:	10/30/2015
Date of issue/Date of revision	:	10/29/2015
Date of previous issue	:	06/25/2015
Version	:	1.2
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL $73/78$ = International Convention for the Prevention of Pollution
		From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-



STAN-TONE EPX-21345 ORANGE

Version Number 1.2 Revision Date 10/29/2015 Page 19 of 19 Print Date 10/30/2015

named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.