

Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 1 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

SAFETY DATA SHEET

Geon™ DM5499 FLEX GRAY ELECTRICAL

Section 1. Identification

GHS product identifier : Geon™ DM5499 FLEX GRAY ELECTRICAL

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20044457Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

: CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

GHS label elements



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 2 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

Hazard pictograms :

Signal word : Warning

Hazard statements : Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary statements

General : Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid

breathing vapor. Wash hands thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace.

Response: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash

with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known. **Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20044457

CAS number/other identifiers

Ingredient name	%	CAS number
Proprietary Hazardous Compounds	1 - 2.9	Not available.



Geon™ DM5499 FLEX GRAY ELECTRICAL

 Version Number 1.0
 Page 3 of 20

 Revision Date 02/20/2019
 Print Date 02/21/2019

Titanium dioxide	0.3 - 1	13463-67-7
Bisphenol A - Epichlorohydrin polymer	0.3 - 1	25068-38-6
Antimony trioxide	0.3 - 1	1309-64-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Inhalation	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained
		personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 4 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 5 of 20 Print Date 02/21/2019

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO_2 .

None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-

insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 6 of 20 Print Date 02/21/2019

Large spill

contractor.

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0
Revision Date 02/20/2019

Page 7 of 20 Print Date 02/21/2019

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Proprietary Hazardous Compounds	None.
Antimony trioxide	OSHA PEL (1993-06-30) TWA 0.5 mg/m3 (as antimony) NIOSH REL (1994-06-01) TWA 0.5 mg/m3 (as antimony) OSHA PEL 1989 (1989-03-01) TWA 0.5 mg/m3 (as antimony)
Bisphenol A - Epichlorohydrin polymer	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3

Appropriate engineering controls: If user operations generate dust, fumes, gas, vapor or mist, use process

enclosures, local exhaust ventilation or other engineering controls to

keep worker exposure to airborne contaminants below any

recommended or statutory limits.

Environmental exposure controls: Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

7/20



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019

Page 8 of 20 Print Date 02/21/2019

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Personal protective equipment for the body should be selected based **Body protection**

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Appropriate footwear and any additional skin protection measures Other skin protection should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this

product.

Based on the hazard and potential for exposure, select a respirator that Respiratory protection

> meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid]

Color **GREY**

Odor Not available. **Odor threshold** Not available. Not available. рH **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. Not available. **Burning rate Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available.



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 9 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

(flammable) limits Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials: Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure	
Titanium dioxide	anium dioxide				
Remarks - Oral:	No applicable toxic	city data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
Bisphenol A - Epichlorohydrin	rin polymer				
	LD50 Oral	Rat	11,400 mg/kg	-	

9/20



Geon™ DM5499 FLEX GRAY ELECTRICAL

 Version Number 1.0
 Page 10 of 20

 Revision Date 02/20/2019
 Print Date 02/21/2019

Remarks - Inhalation:	No applicable to	xicity data		
Remarks - Dermal:	No applicable to	No applicable toxicity data		
Antimony trioxide				
	LD50 Oral	Rat	34,000 mg/kg	=
Remarks - Inhalation:	No applicable to	xicity data		
Remarks - Dermal:	No applicable toxicity data			
Proprietary Hazardous Compo	unds			
Remarks - Oral:	No applicable to	xicity data		
Remarks - Inhalation:	No applicable to	xicity data		
Remarks - Dermal:	No applicable to	xicity data		

Conclusion/Summary: Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Bisphenol A -	Eyes - Mild	Rabbit			-
Epichlorohydrin polymer	irritant				
	Eyes - Mild	Rabbit			=
	irritant				
	Skin -	Rabbit		24 hrs	=
	Moderate				
	irritant				
	Skin - Severe	Rabbit		24 hrs	-
	irritant				
	Eyes - Mild	Rabbit			=
	irritant				
Antimony trioxide	Eyes - Mild	Rabbit			=
	irritant				

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 11 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Titanium dioxide		2B	
Antimony trioxide		2B	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 12 of 20 Print Date 02/21/2019

redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	47,869.8 mg/kg
Route	ATE value
Dermal	105,313.5 mg/kg
Route	ATE value
Inhalation (dusts and mists)	143.6 mg/l

Section 12. Ecological information

Toxicity



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 13 of 20 Print Date 02/21/2019

Product/ingredient name	Result	Species	Exposure			
Titanium dioxide	1100000	Species	2			
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h			
	water					
Remarks - Acute - Fish:	Acute		•			
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h			
		Crustaceans				
Remarks - Acute - Aquatic	Acute	•				
invertebrates.:						
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h			
Daniela Arrata Arrata	A costs	Dapinna				
Remarks - Acute - Aquatic invertebrates.:	Acute					
	No applicable torrigitar data					
Remarks - Acute - Aquatic plants:	No applicable toxicity data					
Remarks - Chronic - Fish:	No applicable toxicity data					
Remarks - Chronic -	No applicable toxicity data No applicable toxicity data					
	No applicable toxicity data					
Aquatic invertebrates.: Bisphenol A - Epichlorohydrir	nolymor					
Remarks - Acute - Fish:	No applicable toxicity data					
Remarks - Acute - Aquatic	No applicable toxicity data	No applicable toxicity data				
invertebrates.:	NI11- (1-14 1-4					
Remarks - Acute - Aquatic	No applicable toxicity data					
plants: Remarks - Chronic - Fish:	No applicable torrigitar data					
	No applicable toxicity data					
Remarks - Chronic -	No applicable toxicity data					
Aquatic invertebrates.: Antimony trioxide						
Allumony trioxide	Acute LC50 > 530 Mg/l Fresh	Fish - Fish	96 h			
	water	1 1511 - 1 1511	70 11			
Remarks - Acute - Fish:	Acute		1			
Acinal AS - Acute - Fish;	Acute EC50 560 Mg/l Fresh water	Aquatic invertebrates.	48 h			
	ricate Leso soo wight fresh water	Crustaceans	70 11			
Remarks - Acute - Aquatic	Acute	Crustaccans				
invertebrates.:	1 icute					
mver coraces.	Acute EC50 423.45 Mg/l Fresh	Aquatic invertebrates.	48 h			
	water	Daphnia	10 11			
Remarks - Acute - Aquatic	Acute		1			
invertebrates.:						
	Acute EC50 0.73 Mg/l Fresh water	Aquatic plants - Algae	72 h			
Remarks - Acute - Aquatic	Acute	1 1 1	1			
plants:						
P	Acute EC50 0.74 Mg/l Fresh water	Aquatic plants - Algae	96 h			
Remarks - Acute - Aquatic	Acute	1 1 1				
	12/00					



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 14 of 20 Print Date 02/21/2019

Acute NOEC 0.2 Mg/l Fresh water	Aquatic plants - Algae	96 h
Chronic		
No applicable toxicity data		
No applicable toxicity data		
unds		
No applicable toxicity data		
No applicable toxicity data		
No applicable toxicity data		
No applicable toxicity data	·	_
No applicable toxicity data		
	No applicable toxicity data No applicable toxicity data unds No applicable toxicity data	Chronic No applicable toxicity data No applicable toxicity data unds No applicable toxicity data No applicable toxicity data

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A - Epichlorohydrin	2.64 - 3.78	31.00	low
polymer			

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 15 of 20 Print Date 02/21/2019

products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules:

Listed 4-Nonylphenol, branched

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019

Page 16 of 20 Print Date 02/21/2019

Lead

United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed 4-Nonylphenol, branched

Octocrilene

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Antimony trioxide

2-Ethylhexanoic acid zinc salt

Phenol Lead Arsenic

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Not listed

Not listed

Listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential Chemicals)

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification SKIN IRRITATION - Category 2

16/20



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Revision Date 02/20/2019 Page 17 of 20 Print Date 02/21/2019

EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
Proprietary Hazardous	>= 1 - <= 2.9	Fire hazard - Immediate (acute) health hazard - Delayed
Compounds		(chronic) health hazard
Antimony trioxide	>= 0.3 - < 1	EYE IRRITATION - Category 2B
·		CARCINOGENICITY - Category 2
Bisphenol A -	>= 0.3 - < 1	SKIN IRRITATION - Category 2
Epichlorohydrin polymer		EYE IRRITATION - Category 2B
		SKIN SENSITIZATION - Category 1
Titanium dioxide	>= 0.3 - <= 1	CARCINOGENICITY - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting	Lead	7439-92-1	0 - 0.1
requirements			
	Proprietary Hazardous		1 - 2.9
	Compounds		
	Antimony trioxide	1309-64-4	0.3 - 1
	-		
Supplier notification	Lead	7439-92-1	0 - 0.1
	Antimony trioxide	1309-64-4	0.3 - 1
	Proprietary Hazardous Compounds		1 - 2.9

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

Proprietary Hazardous Compounds

New York : The following components are listed:

Antimony trioxide



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 18 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer Proprietary Hazardous Compounds

Antimony trioxide Titanium dioxide

Pennsylvania : The following components are listed:

Aluminum hydroxide

Proprietary Hazardous Compounds

Antimony trioxide

Titanium dioxide

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Antimony trioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Antimony trioxide	No.	No.
Titanium dioxide	No.	No.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia : Not determined.

Canada : All components are listed or exempted.

Not determined. China Not determined. **Europe inventory** Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined.

United States : All components are listed or exempted.



Geon™ DM5499 FLEX GRAY ELECTRICAL

Version Number 1.0 Page 19 of 20 Revision Date 02/20/2019 Print Date 02/21/2019

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 02/21/2019Date of issue/Date of revision: 02/20/2019Date of previous issue: 00/00/0000

Version : 1.0

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.



Geon™ DM5499 FLEX GRAY ELECTRICAL

 Version Number 1.0
 Page 20 of 20

 Revision Date 02/20/2019
 Print Date 02/21/2019