

CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Page 1 of 18 Revision Date 04/05/2022 Print Date 04/06/2022

SAFETY DATA SHEET

CORETM DB5664 RIGID BLUE UV FR

Section 1. Identification

GHS product identifier : CORE™ DB5664 RIGID BLUE UV FR

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20049049Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation)

elephone number : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

GHS label elements



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 2 of 18 Print Date 04/06/2022

Hazard pictograms

(!)

Signal word : Warning

Hazard statements : Causes serious eye irritation.

Suspected of causing cancer.

Precautionary statements

Not applicable.

Prevention : Obtain special instructions before use. Wear protective gloves. Wear

protective clothing. Wear eye or face protection.

Response : IF exposed or concerned: Get medical advice or attention. IF IN

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements Hazards not otherwise classified None known. None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20049049

CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	>= 10 - <= 25	68515-48-0
C9-rich		
Siloxane and silicones, dimethyl	>= 1 - <= 3	63148-62-9
Antimony trioxide	>= 0.3 - < 1	1309-64-4
Titanium dioxide	> 0 - <= 0.3	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 3 of 18 Print Date 04/06/2022

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eve contact : Causes serious eye irritation.

Inhalation
Skin contact
No known significant effects or critical hazards.
No known significant effects or critical hazards.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 4 of 18 Print Date 04/06/2022

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

: None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

Hazardous thermal decomposition products

: May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity

of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 5 of 18 Print Date 04/06/2022

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8).

Avoid exposure - obtain special instructions before use. Do not handle



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 6 of 18 Print Date 04/06/2022

Advice on general occupational hygiene

mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this

until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	None.
Siloxane and silicones, dimethyl	None.
Antimony trioxide	NIOSH REL (1994-06-01) TWA 0.5 mg/m3 OSHA PEL 1989 (1989-03-01) TWA 0.5 mg/m3 (as antimony) OSHA PEL (1993-06-30) TWA 0.5 mg/m3 (as antimony) ACGIH TLV (2021-01-07) TWA 0.02 mg/m3 Form: Inhalable fraction
Titanium dioxide	OSHA PEL 1989 (1989-03-01)



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 7 of 18 Print Date 04/06/2022

	TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
--	---

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0
Revision Date 04/05/2022

Page 8 of 18 Print Date 04/06/2022

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : liquid [liquid]

Color : BLUE

Odor Not available. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Aerosol product

Heat of combustion : Not available.

Ignition distance : Not available. **Enclosed space ignition - Time** : Not available.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 9 of 18 Print Date 04/06/2022

equivalent

Enclosed space ignition -

Deflagration density

: Not available.

Flame height : Not available. Flame duration : Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure		
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich						
	LD50 Oral	Rat	10,000 mg/kg	-		
Siloxanes and Silicones, di-Me						
	LD50 Oral	Rat	17,000 mg/kg	-		
Antimony oxide	Antimony oxide					
	LD50 Oral	Rat	34,000 mg/kg	-		
Titanium oxide (TiO2)	Titanium oxide (TiO2)					
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	Dusts and mists					
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic acid, di-C8-10-branched	Eyes - Mild irritant	Rabbit	-		-



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 10 of 18 Print Date 04/06/2022

alkyl esters, C9-rich					
Siloxanes and Silicones, di- Me	Eyes - Mild irritant	Rabbit	-	24 hrs	-
	Eyes - Moderate irritant	Rabbit	-	24 hrs	-
	Eyes - Mild irritant	Rabbit	-	1 hrs	-
	Skin - Mild irritant	Rabbit	-	24 hrs	-
Antimony oxide	Eyes - Mild irritant	Rabbit	-		-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Antimony oxide	-	2B	-
Titanium oxide (TiO2)	-	2B	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture. Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 11 of 18 Print Date 04/06/2022

Not available.

Aspiration hazard

Not available.

Information on the likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following: pain or irritation,

watering, redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects: Not available.Potential delayed effects: Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General: No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 12 of 18 Print Date 04/06/2022

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE™ DB5664 RIGID BLUE UV FR	421,514.1 mg/kg	N/A	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10,000 mg/kg	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me	17,000 mg/kg	N/A	N/A	N/A	N/A
Antimony oxide	34,000 mg/kg	N/A	N/A	N/A	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Siloxanes and Silicones, di-Me			
	Acute LC50 44.5 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
Antimony oxide			
	Acute LC50 > 530 Mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water		
	Acute EC50 560 Mg/l Fresh	Crustaceans - Cypris	48 h
	water	subglobosa	
	Acute EC50 3.01 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 13 of 18 Print Date 04/06/2022

Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
	dubia	
Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
water		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 14 of 18 Print Date 04/06/2022

<u>United States - RCRA Toxic hazardous waste "U" List:</u> Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed

Lead

United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Siloxane and silicones, dimethyl

Octocrilene

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022

Page 15 of 18 Print Date 04/06/2022

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Antimony trioxide

Phthalocyanine Blue

2-Ethylhexanoic acid zinc salt

Phenol Arsenic Lead

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Listed

Not listed

Not listed

Not listed

Not listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification EYE IRRITATION - Category 2A

CARCINOGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 10 - <= 25	EYE IRRITATION - Category 2B
Siloxanes and Silicones, di- Me	>= 1 - <= 3	EYE IRRITATION - Category 2A
Antimony oxide	>= 0.3 - < 1	EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 16 of 18 Print Date 04/06/2022

Titanium oxide (TiO2)	> 0 - <= 0.3	CARCINOGENICITY - Category 2

Form R - Reporting requirements

Product name	CAS number	%
Antimony trioxide	1309-64-4	>= 0.3 - < 1
Lead	7439-92-1	> 0 - < 0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: The following components are listed:

Antimony trioxide

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

Antimony trioxide Titanium dioxide

Pennsylvania : The following components are listed:

Antimony trioxide

Titanium dioxide

California Prop. 65

WARNING: This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable	
		dosage level	
1,2-Benzenedicarboxylic acid, di-C8-10-	Yes.	-	
branched alkyl esters, C9-rich			
Antimony trioxide	-	-	
Titanium dioxide	-	-	

United States inventory (TSCA 8b) : All components are active or exempted.



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Page 17 of 18 Revision Date 04/05/2022 Print Date 04/06/2022

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia : Not determined.

Canada : All components are listed or exempted.

China Not determined. Not determined. **Europe inventory** Not determined. Japan New Zealand Not determined. **Philippines** Not determined. Republic of Korea Not determined. **Taiwan** Not determined. **Turkey** Not determined.

United States : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 04/06/2022Date of issue/Date of revision: 04/05/2022Date of previous issue: 00/00/0000

Version : 1.0

Key to abbreviations: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container



CORE™ DB5664 RIGID BLUE UV FR

Version Number 1.0 Revision Date 04/05/2022 Page 18 of 18 Print Date 04/06/2022

 $IMDG = International \ Maritime \ Dangerous \ Goods$

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.