### CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 1 of 18 Print Date 07/18/2023

# SAFETY DATA SHEET

CORE<sup>TM</sup> SK417 White formula #7

Section 1. Identification	on	
GHS product identifier	:	CORE <sup>™</sup> SK417 White formula #7
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20050038
Product type	:	liquid
	stance	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	EYE IRRITATION - Category 2B SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

#### **GHS label elements**

## CORE<sup>™</sup> SK417 White formula #7



Version Number 1.0 Revision Date 06/15/2023

#### Page 2 of 18 Print Date 07/18/2023

Hazard pictograms	:	
Signal word Hazard statements	:	Warning May cause an allergic skin reaction. Causes eye irritation. Suspected of causing cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must
Response	:	not be allowed out of the workplace. IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20050038

#### CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 10 - <= 25	13463-67-7
Solvent naphtha, petroleum, light arom.	>= 10 - <= 25	64742-95-6



## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023 Page 3 of 18 Print Date 07/18/2023

Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	95-63-6
2-Hydroxy-4-n-octoxybenzophenone	>= 1 - <= 3	1843-05-6
Cumene	> 0 - <= 0.3	98-82-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

**Description of necessary first aid measures** 

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 4 of 18 Print Date 07/18/2023

#### Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	::	Causes eye irritation. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.
<b>Over-exposure signs/symptoms</b>		
Eye contact	:	Adverse symptoms may include the following: irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical atte	entio	on and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## **Section 5. Fire-fighting measures**

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide

# **ÄVIENT**

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023 Page 5 of 18 Print Date 07/18/2023

		carbon monoxide phosphorus oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containn	nent ar	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the
		5/18

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 6 of 18 Print Date 07/18/2023

same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits		
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30)		


# **ÀVIENT**

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023 Page 7 of 18 Print Date 07/18/2023

	TWA 15 mg/m3 Form: Total dust <b>ACGIH TLV (2022-01-06)</b> TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles
Solvent naphtha, petroleum, light arom.	None.
Benzene, 1,2,4-trimethyl-	NIOSH REL (1994-06-01) TWA 125 mg/m3 25 ppm OSHA PEL 1989 (1989-03-01) TWA 125 mg/m3 25 ppm ACGIH TLV (1994-09-01) TWA 123 mg/m3 25 ppm
2-Hydroxy-4-n-octoxybenzophenone	None.
Cumene	ACGIH TLV (2021-01-07) TWA 5 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 245 mg/m3 50 ppm
Appropriate engineering controls : Environmental exposure controls :	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## CORE<sup>™</sup> SK417 White formula #7





Page 8 of 18
Print Date 07/18/2023

Eye/face protection	when a risk asse liquid splashes, following protec	complying with an approved standard should be used essment indicates this is necessary to avoid exposure to mists, gases or dusts. If contact is possible, the ction should be worn, unless the assessment indicates a f protection: chemical splash goggles.
Skin protection		
Hand protection	standard should if a risk assessm parameters spec the gloves are st noted that the tin different for diff	ant, impervious gloves complying with an approved be worn at all times when handling chemical products tent indicates this is necessary. Considering the ified by the glove manufacturer, check during use that ill retaining their protective properties. It should be me to breakthrough for any glove material may be ferent glove manufacturers. In the case of mixtures, veral substances, the protection time of the gloves ately estimated.
Body protection	: Personal protect on the task bein	ive equipment for the body should be selected based g performed and the risks involved and should be pecialist before handling this product.
Other skin protection	should be select	twear and any additional skin protection measures ed based on the task being performed and the risks ould be approved by a specialist before handling this
Respiratory protection	meets the appro- used according	zard and potential for exposure, select a respirator that priate standard or certification. Respirators must be to a respiratory protection program to ensure proper and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state	:	liquid [liquid]
Color	:	WHITE
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 9 of 18 Print Date 07/18/2023

(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide (TiO2)				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Solvent naphtha (petroleum),	light arom.			
	LD50 Oral	Rat	8,400 mg/kg	-
Benzene, 1,2,4-trimethyl-				
	LD50 Oral	Rat	5,000 mg/kg	-
	LC50 Inhalation	Rat	18 Mg/l	4 h
	Vapor			
Methanone, [2-hydroxy-4-(oc	tyloxy)phenyl]phenyl	-		



## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023

#### Page 10 of 18 Print Date 07/18/2023

	LD50 Oral	Rat	10,000 mg/kg	-
	LD50 Dermal	Rabbit	10,000 mg/kg	-
Benzene, (1-methylethyl)-				
	LD50 Oral	Rat	1,400 mg/kg	-
	LC50 Inhalation	Rat	39 Mg/l	4 h
1	Vapor			

**Conclusion/Summary** 

: Mixture.Not fully tested.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hrs	-
Benzene, (1-methylethyl)-	Eyes - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Eyes - Mild irritant	Rabbit	-		-

Conclusion/Summary Skin Eyes Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
Sensitization	
Conclusion/Summary Skin Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
<b>Mutagenicity</b>	
Conclusion/Summary	: Mixture.Not fully tested.
<b>Carcinogenicity</b>	
Conclusion/Summary	: Mixture.Not fully tested.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Benzene, (1-methylethyl)-	-	2B	Reasonably anticipated to be a human carcinogen.

#### **Reproductive toxicity**

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 11 of 18 Print Date 07/18/2023

Conclusion/Summary	:	Mixture.Not fully tested.
		2

#### **Teratogenicity**

**Conclusion/Summary** : Mixture.Not fully tested.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Name			Result	
Solvent naphtha (petroleum), light aron	n.		ASPIRATION HAZARD - Category 1	
Information on the likely routes of exposure	:	Not available.		
Potential acute health effects				
Eye contact	:	Causes eye irr	itation.	
Inhalation	:		nificant effects or critical hazards.	
Skin contact	:		allergic skin reaction.	
Ingestion	:	No known sig	nificant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics				
Eye contact	:	Adverse symptoms may include the following: irritation, watering, redness		
Inhalation	:	No specific da	ta.	
Skin contact	:	Adverse symp	toms may include the following: irritation, redness	
Ingestion	:	No specific da	ta.	
Delayed and immediate effects and also chronic effects from short and long term exposure				
Short term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
11/18				

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023

# **ÀVIENT**

Page 12 of 18 Print Date 07/18/2023

#### Potential chronic health effects

on may occur when s.
ncer depends on duration and
hazards.
hazards.

Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE™ SK417 White formula #7	71211.9 mg/kg	N/A	N/A	304.4 Mg/l	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l
Solvent naphtha (petroleum), light arom.	8400 mg/kg	N/A	N/A	N/A	N/A
Benzene, 1,2,4-trimethyl-	5000 mg/kg	N/A	N/A	18 Mg/l	N/A
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	10000 mg/kg	10000 mg/kg	N/A	N/A	N/A
Benzene, (1-methylethyl)-	1400 mg/kg	N/A	N/A	39 Mg/l	N/A

#### **Other information**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## Section 12. Ecological information

:

**Toxicity** 

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023

# AVIENT

#### Page 13 of 18 Print Date 07/18/2023

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)	•		•
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h
Benzene, 1,2,4-trimethyl-	•	•	
	Acute LC50 7.72 Mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute LC50 4.91 Mg/l Marine	Crustaceans - Elasmopus	48 h
	water	pectenicrus	
Benzene, (1-methylethyl)-			
	Acute LC50 0.0027 Mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water		
	Acute EC50 7.4 Mg/l Marine	Crustaceans - Artemia sp.	48 h
	water		
	Acute EC50 10.6 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		

Conclusion/Summary

: Not available.

#### Persistence and degradability

**Conclusion/Summary** 

Not available.

:

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Solvent naphtha (petroleum), light	-	10.00 - 2,500.00	high
arom.			
Benzene, 1,2,4-trimethyl-	3.63	243.00	low
Methanone, [2-hydroxy-4-	6	99.00	low
(octyloxy)phenyl]phenyl-			
Benzene, (1-methylethyl)-	3.55	35.48	low

#### **Mobility in soil**

Soil/water partition coefficient	:	Not available.
(KOC)		

:

Other adverse effects

No known significant effects or critical hazards.

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023

# AVIENT

Page 14 of 18 Print Date 07/18/2023

## Section 13. Disposal considerations

:

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not regulated for transportation.
International Air ICAO/IATA	: Consult mode specific transport rules
International Water IMO/IMDG	: Consult mode specific transport rules

## Section 15. Regulatory information

U.S. Federal regulations	: United States - TSCA 12(b) - Chemical export notification: None
	of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 15 of 18 Print Date 07/18/2023

		listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed 2-Ethylhexanoic acid zinc salt Ethyl benzene Zinc oxide Phenol United States - EPA Clean water act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

#### SARA 311/312

Classification

**Chemicals**)

EYE IRRITATION - Category 2B



## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023 Page 16 of 18 Print Date 07/18/2023

#### SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

#### Composition/information on ingredients

Name	%	Classification
Titanium oxide (TiO2)	>= 10 - <= 25	CARCINOGENICITY - Category 2
Solvent naphtha (petroleum), light arom.	>= 10 - <= 25	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B ASPIRATION HAZARD - Category 1
Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	>= 1 - <= 3	SKIN SENSITIZATION - Category 1
Benzene, (1-methylethyl)-	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2

#### <u>SARA 313</u>

#### Form R - Reporting requirements

Product name	CAS number	%
Benzene, 1,2,4-trimethyl-	95-63-6	>= 3 - < 7
Cumene	98-82-8	>= 0.1 - < 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

: The following components are listed:
Titanium dioxide
Benzene, 1,2,4-trimethyl-
: None of the components are listed.
: The following components are listed:

16/18

## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023



Page 17 of 18 Print Date 07/18/2023

Ethene, chloro-, homopolymer Titanium dioxide Solvent naphtha, petroleum, light arom. Benzene, 1,2,4-trimethylThe following components are listed: Titanium dioxide

Pennsylvania

Benzene, 1,2,4-trimethyl-

#### California Prop. 65

**T 1 1 0 1** 

**WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Cumene	-	-

4 11

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations Inventory list		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

## Section 16. Other information

Hazardous Material Information System (U.S.A.)



## CORE<sup>™</sup> SK417 White formula #7

Version Number 1.0 Revision Date 06/15/2023 Page 18 of 18 Print Date 07/18/2023

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

HISTOLA		
Date of printing	:	07/18/2023
Date of issue/Date of revision	:	06/15/2023
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		$\hat{U}N = United Nations$
References	:	Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.