CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023



Page 1 of 20 Print Date 10/04/2023

SAFETY DATA SHEET

CORE[™] SK431 White "90"

Section 1. Identification	n	
GHS product identifier Chemical name	:	CORE [™] SK431 White "90" Mixture
CAS number Other means of identification	:	Mixture FO20050326
Product type	:	liquid
Relevant identified uses of the substa Product use	nce :	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).


Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

GHS label elements

CORE™ SK431 White "90"



ÀVIENT

Page 2 of 20 Print Date 10/04/2023

Hazard pictograms	:	
Signal word Hazard statements	:	Warning May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor.
Response	:	Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or
		attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20050326

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 25 - <= 50	13463-67-7
Solvent naphtha, petroleum, light arom.	>= 10 - <= 25	64742-95-6



CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023 Page 3 of 20 Print Date 10/04/2023

Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	95-63-6
2-Amino-2-methylpropanol	>= 1 - <= 3	124-68-5
2-Hydroxy-4-n-octoxybenzophenone	>= 1 - <= 3	1843-05-6
Cumene	>= 0.3 - < 1	98-82-8
Ethyl benzene	> 0 - <= 0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

ÀVIENT

Page 4 of 20 Print Date 10/04/2023

kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Inhalation Skin contact Ingestion	No kno May ca	s serious eye irritation. own significant effects or critical hazards. ause an allergic skin reaction. own significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact		6
Inhalation	: No spe	cific data.
Skin contact	-	se symptoms may include the following:
Ingestion		cific data.
Indication of immediate medical a	ention and s	pecial treatment needed, if necessary
Notes to physician	may be	e of inhalation of decomposition products in a fire, symptoms e delayed. The exposed person may need to be kept under al surveillance for 48 hours.
Specific treatments	: No spe	cific treatment.
Protection of first-aiders	suitabl give m	ion shall be taken involving any personal risk or without e training. It may be dangerous to the person providing aid to outh-to-mouth resuscitation. Wash contaminated clothing ghly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

:

Extinguishing media

Suitable extinguishing media

In case of fire, use water spray (fog), foam, dry chemical or CO₂.

CORE[™] SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

ÀVIENT

Page 5 of 20 Print Date 10/04/2023

Unsuitable extinguishing media	:	None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-

contractor.

insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

CORE™ SK431 White "90"

ÄVIENT"

Version Number 1.0	Page 6 of 20
Revision Date 10/03/2023	Print Date 10/04/2023

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

:

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

CORE[™] SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023



Page 7 of 20 Print Date 10/04/2023

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles
Solvent naphtha, petroleum, light arom.	None.
Benzene, 1,2,4-trimethyl-	NIOSH REL (1994-06-01) TWA 125 mg/m3 25 ppm OSHA PEL 1989 (1989-03-01) TWA 125 mg/m3 25 ppm ACGIH TLV (1994-09-01) TWA 123 mg/m3 25 ppm
2-Amino-2-methylpropanol	None.
2-Hydroxy-4-n-octoxybenzophenone	None.
Cumene	ACGIH TLV (2021-01-07) TWA 5 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 245 mg/m3 50 ppm
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm ACGIH TLV (2010-12-06) Ototoxicant TWA 20 ppm

7/20

CORE[™] SK431 White "90"

Ver Re

AVIENT

ersion Number 1.0	Page 8 of 20
evision Date 10/03/2023	Print Date 10/04/2023

Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be
		necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations
Eye/face protection	:	and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be
Other skin protection	:	approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be
		8/20

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

AVIENT

Page 9 of 20 Print Date 10/04/2023

used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [liquid]
Color		WHITE
Odor		Not available.
Odor threshold		Not available.
pH		Not available.
Melting point		Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
-	•	Not available.
Burning time	•	
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
	:	Upper: Not available. Not available.
(flammable) limits	:	
(flammable) limits Vapor pressure	:	Not available.
(flammable) limits Vapor pressure Vapor density	:	Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility	:	Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density	:	Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water	:	Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water	:	Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature	:	Not available. Not available. Not available. Not available. Not available. Not applicable.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water	:	Not available. Not available. Not available. Not available. Not available. Not applicable. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature SADT	:	Not available. Not available. Not available. Not available. Not available. Not applicable. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature		Not available. Not available. Not available. Not available. Not available. Not applicable. Not available. Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials	:	Keep away from extreme heat and oxidizing agents. Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
		during processing.



CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

Page 10 of 20 Print Date 10/04/2023

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

:

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide (TiO2)	·	· · ·		
· · · · ·	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Solvent naphtha (petroleum),	light arom.			
	LD50 Oral	Rat	8,400 mg/kg	-
Benzene, 1,2,4-trimethyl-		•		•
	LD50 Oral	Rat	5,000 mg/kg	-
	LC50 Inhalation	Rat	18 Mg/l	4 h
	Vapor		Ŭ	
1-Propanol, 2-amino-2-methy	/1-	•		
•	LD50 Oral	Rat	2,900 mg/kg	-
Methanone, [2-hydroxy-4-(oc	tyloxy)phenyl]phenyl	-		
- - - - -	LD50 Oral	Rat	10,000 mg/kg	-
	LD50 Dermal	Rabbit	10,000 mg/kg	-
Benzene, (1-methylethyl)-	•	•	· · · · · ·	
	LD50 Oral	Rat	1,400 mg/kg	-
	LC50 Inhalation	Rat	39 Mg/l	4 h
	Vapor		Ũ	
Benzene, ethyl-	-			
÷	LD50 Oral	Rat	3,500 mg/kg	-
	LD50 Dermal	Rabbit	5,000 mg/kg	-

Conclusion/Summary

Mixture.Not fully tested.

:

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hrs	-
1-Propanol, 2-amino-2- methyl-	Eyes - Severe irritant	Rabbit	-		-
Benzene, (1-methylethyl)-	Eyes - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-

CORE™ SK431 White "90"



Version Number 1.0 Revision Date 10/03/2023

Page 11 of 20 Print Date 10/04/2023

	Eyes - Mild irritant	Rabbit	-		_
Benzene, ethyl-	Skin - Mild irritant	Rabbit	-	24 hrs	-
· · ·	Eyes - Severe irritant	Rabbit	-		-
Conclusion/Summary					
Skin	: Mixture.No	t fully tested.			
Eyes	: Mixture.No	t fully tested			
Respiratory	: Mixture.No	ot fully tested			
<u>Sensitization</u>					
Conclusion/Summary					
Skin		ot fully tested.			
Respiratory	: Mixture.No	ot fully tested			
Mutagenicity					
Conclusion/Summary	: Mixture.No	ot fully tested			
Carcinogenicity					
Conclusion/Summary	: Mixture.No	ot fully tested			

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Benzene, (1-methylethyl)-	-	2B	Reasonably anticipated to be a human carcinogen.
Benzene, ethyl-	-	2B	-

Reproductive toxicity

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

Teratogenicity

Conclusion/Summary

: Mixture.Not fully tested.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

CORE[™] SK431 White "90"



Version Number 1.0 Revision Date 10/03/2023

Page 12 of 20 Print Date 10/04/2023

Name		Result	
Solvent naphtha (petroleum), light aron	1.	ASPIRATION HAZARD - Category 1	
Benzene, ethyl-	e, ethyl- ASPIRATION HAZARD - Category 1		
Information on the likely routes of exposure	: Not avail	able.	
Potential acute health effects			
Eye contact Inhalation Skin contact Ingestion	No knowMay caus	erious eye irritation. n significant effects or critical hazards. se an allergic skin reaction. n significant effects or critical hazards.	
Symptoms related to the physical, ch	emical and tox	cicological characteristics	
Eye contact	Eye contact : Adverse symptoms may include the following: pain or irrita watering, redness		
Inhalation	: No specif		
Skin contact Ingestion	Adverse s No specif	symptoms may include the following: irritation, redness ic data.	
Delayed and immediate effects and a	so chronic eff	ects from short and long term exposure	
Short term exposure			
Potential immediate effects Potential delayed effects	Not avail Not avail		
Long term exposure			
Potential immediate effects Potential delayed effects	Not avail Not avail		
Potential chronic health effects			
Conclusion/Summary	: Mixture.l	Not fully tested.	
General		sitized, a severe allergic reaction may occur when ntly exposed to very low levels.	
Carcinogenicity		d of causing cancer. Risk of cancer depends on duration and	
Mutagenicity		n significant effects or critical hazards.	
Teratogenicity	: Not avail		
Developmental effects	: Not avail		
Fertility effects	INO KNOW	n significant effects or critical hazards.	

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023



Page 13 of 20 Print Date 10/04/2023

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE [™] SK431 White "90"	44766.9 mg/kg	N/A	N/A	250.8 Mg/l	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l
Solvent naphtha (petroleum), light arom.	8400 mg/kg	N/A	N/A	N/A	N/A
Benzene, 1,2,4-trimethyl-	5000 mg/kg	N/A	N/A	18 Mg/l	N/A
1-Propanol, 2-amino-2- methyl-	2900 mg/kg	N/A	N/A	N/A	N/A
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	10000 mg/kg	10000 mg/kg	N/A	N/A	N/A
Benzene, (1-methylethyl)-	1400 mg/kg	N/A	N/A	39 Mg/l	N/A
Benzene, ethyl-	3500 mg/kg	5000 mg/kg	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
	_	dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		
Benzene, 1,2,4-trimethyl-			
	Acute LC50 7.72 Mg/l Fresh	Fish - Pimephales promelas	96 h

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

Page 14 of 20 Print Date 10/04/2023

	water		
	Acute LC50 4.91 Mg/l Marine	Crustaceans - Elasmopus	48 h
	water	pectenicrus	40 11
Benzene, (1-methylethyl)-	water	pectellierus	
benzene, (1 mearytettiyt)	Acute LC50 0.0027 Mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water	Tibli Oneomynemus mykiss	70 H
	Acute EC50 7.4 Mg/l Marine	Crustaceans - Artemia sp.	48 h
	water	1	
	Acute EC50 10.6 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
Benzene, ethyl-			
	Acute LC50 4.2 Mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water		
	Acute EC50 6.53 Mg/l Marine	Crustaceans - Artemia sp.	48 h
	water		
	Acute EC50 2.93 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute EC50 4.9 Mg/l Marine	Algae - Skeletonema costatum	72 h
	water		
	Acute EC50 7.7 Mg/l Marine	Algae - Skeletonema costatum	96 h
	water		

Conclusion/Summary

: Not available.

Persistence and degradability

Conclusion/Summary

: Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Solvent naphtha (petroleum), light	-	10.00 - 2,500.00	high
arom.			
Benzene, 1,2,4-trimethyl-	3.63	243.00	low
1-Propanol, 2-amino-2-methyl-	-0.63	320.00	low
Methanone, [2-hydroxy-4-	6	99.00	low
(octyloxy)phenyl]phenyl-			
Benzene, (1-methylethyl)-	3.55	35.48	low
Benzene, ethyl-	3.6	-	low

Mobility in soil

Soil/water partition coefficient : Not available.

14/20



CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

AVIENT

Page 15 of 20 Print Date 10/04/2023

(KOC)

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever **Disposal methods** : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not	t regulated for transportation.
International Air ICAO/IATA	: Cor	nsult mode specific transport rules
International Water IMO/IMDG	: Cor	nsult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed
	15/20

CORE[™] SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023



Pa	ge 16 of 20
Print Date	10/04/2023

United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Ethyl benzene 2-Ethylhexanoic acid zinc salt Zinc oxide Phenol United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed **United States - Department of commerce - Precursor chemical:** Not listed Listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		Not listed
DEA List I Chemicals (Precursor Chemicals)	•	Not listed
DEA List II Chemicals (Essential		Not listed
Chemicals)	•	not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

CORE[™] SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023



Page 17 of 20 Print Date 10/04/2023

SARA 311/312

Classification

EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

:

Composition/information on ingredients

Name	%	Classification
Titanium oxide (TiO2)	>= 25 - <= 50	CARCINOGENICITY - Category 2
Solvent naphtha (petroleum), light arom.	>= 10 - <= 25	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B ASPIRATION HAZARD - Category 1
Benzene, 1,2,4-trimethyl-	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4
1-Propanol, 2-amino-2- methyl-	>= 1 - <= 3	EYE IRRITATION - Category 2A
Methanone, [2-hydroxy-4- (octyloxy)phenyl]phenyl-	>= 1 - <= 3	SKIN SENSITIZATION - Category 1
Benzene, (1-methylethyl)-	>= 0.3 - < 1	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2
Benzene, ethyl-	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1

<u>SARA 313</u>

Form R - Reporting requirements

Product name	CAS number	%
Benzene, 1,2,4-trimethyl-	95-63-6	>= 5 - < 10
Aluminum oxide	1344-28-1	>= 0.5 - < 1.5
Cumene	98-82-8	>= 0.1 - < 1

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

Page 18 of 20 Print Date 10/04/2023

Ethyl benzene	100-41-4	>= 0.1 - < 1
---------------	----------	--------------

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	The following components are listed:
		Titanium dioxide
		Benzene, 1,2,4-trimethyl-
		2-Amino-2-methylpropanol
		Aluminum oxide
New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
		Ethene, chloro-, homopolymer
		Titanium dioxide
		Solvent naphtha, petroleum, light arom.
		Benzene, 1,2,4-trimethyl-
		2-Amino-2-methylpropanol
		Aluminum oxide
		Ethyl benzene
Pennsylvania	:	The following components are listed:
-		Titanium dioxide
		Benzene, 1,2,4-trimethyl-
		2 Amine 2 methylpropenal
		2-Amino-2-methylpropanol
		Aluminum oxide

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Cumene	-	-
Ethyl benzene	Yes.	-

:

Canada inventory

All components are listed or exempted.



18/20

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

AVIENT

Pa	ge 19 of 20
Print Date	10/04/2023

International regulations				
Inventory list				

Australia	:	Not determined.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

0
0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Illstol y</u>	
Date of printing	: 10/04/2023
Date of issue/Date of revision	: 10/03/2023
Date of previous issue	: 00/00/0000
Version	: 1.0
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container

CORE™ SK431 White "90"

Version Number 1.0 Revision Date 10/03/2023

AVIENT

Page 20 of 20 Print Date 10/04/2023

IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.