

P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 1 of 23 Print Date 11/03/2023 Revision Date 11/02/2023

SAFETY DATA SHEET

P1395A Blue Primer (60% dilution)

Section 1. Identification

P1395A Blue Primer (60% dilution) **GHS** product identifier

Chemical name Mixture CAS number Mixture Other means of identification FO20050390 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number

(with hours of operation) accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A **CARCINOGENICITY - Category 1B**

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

Category 2

GHS label elements



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 2 of 23 Print Date 11/03/2023

Hazard pictograms

Signal word : Danger

Hazard statements : Harmful if swallowed.

Causes skin irritation.
Causes serious eye irritation.

May cause cancer.

May cause damage to organs.

Precautionary statements

Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly

after handling.

Response: IF exposed or concerned: Call a POISON CENTER or doctor. IF

SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice or attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements
Hazards not otherwise classified

None known.
None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20050390

CAS number/other identifiers



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 3 of 23 Print Date 11/03/2023

| Ingredient name | % | CAS number |
|------------------------|---------------|------------|
| Methyl ethyl ketone | >= 25 - <= 50 | 78-93-3 |
| Benzene, methyl- | >= 10 - <= 25 | 108-88-3 |
| Methyl isobutyl ketone | >= 10 - <= 25 | 108-10-1 |
| Cyclohexanone | >= 3 - <= 5 | 108-94-1 |
| Methyl alcohol | >= 3 - <= 5 | 67-56-1 |
| Dimethylformamide | >= 1 -<= 3 | 68-12-2 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Description of necessary first and mea | asur es |
|--|---|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse. |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 4 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

Ingestion: Wash out mouth with water. Remove dentures if any. If material has

been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation
 May cause damage to organs following a single exposure if inhaled.
 Skin contact
 May cause damage to organs following a single exposure in contact

with skin. Causes skin irritation.

Ingestion: Harmful if swallowed. May cause damage to organs following a single

exposure if swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation. Wash contaminated clothing



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 5 of 23 Print Date 11/03/2023

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the chemical

nemical
Hazardous thermal
decomposition products

In a fire or if heated, a pressure increase will occur and the container

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

nitrogen oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 6 of 23 Print Date 11/03/2023

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 7 of 23 Print Date 11/03/2023

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------------|--|
| Methyl ethyl ketone | OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm STEL 885 mg/m3 300 ppm |
| Benzene, methyl- | OSHA PEL 1989 (1989-03-01) TWA 375 mg/m3 100 ppm STEL 560 mg/m3 150 ppm OSHA PEL Z2 (1993-06-30) TWA 200 ppm CEIL 300 ppm AMP 500 ppm NIOSH REL (1994-06-01) TWA 375 mg/m3 100 ppm STEL 560 mg/m3 150 ppm ACGIH TLV (2006-11-17) Ototoxicant TWA 20 ppm |
| Methyl isobutyl ketone | OSHA PEL 1989 (1989-03-01) TWA 205 mg/m3 50 ppm STEL 300 mg/m3 75 ppm OSHA PEL (1993-06-30) TWA 410 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 205 mg/m3 50 ppm STEL 300 mg/m3 75 ppm ACGIH TLV (2009-11-30) TWA 20 ppm ACGIH TLV (1994-09-01) STEL 75 ppm |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 8 of 23 Print Date 11/03/2023

| Cyclohexanone | ACGIH TLV (2003-01-01) Absorbed through skin. TWA 20 ppm STEL 50 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 100 mg/m3 25 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 100 mg/m3 25 ppm OSHA PEL (1993-06-30) TWA 200 mg/m3 50 ppm |
|-------------------|---|
| Methyl alcohol | OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 260 mg/m3 200 ppm STEL 325 mg/m3 250 ppm OSHA PEL (1993-06-30) TWA 260 mg/m3 200 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 260 mg/m3 200 ppm STEL 325 mg/m3 250 ppm |
| Dimethylformamide | ACGIH TLV (2018-03-20) Absorbed through skin. TWA 30 mg/m3 5 ppm NIOSH REL (1994-06-01) Absorbed through skin. TWA 30 mg/m3 10 ppm OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 30 mg/m3 10 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 30 mg/m3 10 ppm |

Appropriate engineering controls: If user operations gen

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to

keep worker exposure to airborne contaminants below any

recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 9 of 23 Print Date 11/03/2023

of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color NO PIGMENT Not available. Odor Not available. Odor threshold Not available. рH **Melting point** Not available. **Boiling point** Not available. 25 °F (-4 °C) Flash point



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 10 of 23 Print Date 11/03/2023 Revision Date 11/02/2023

Burning time Not available. **Burning rate** Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available. (flammable) limits Upper: Not available.

Vapor pressure Not available. Vapor density Not available. **Relative density** Not available. **Solubility** Not available. Solubility in water Not available. Partition coefficient: n-Not applicable.

octanol/water

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature SADT** Not available.

Viscosity **Dynamic:** Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will

not occur.

Keep away from extreme heat and oxidizing agents. Conditions to avoid

Keep away from strong acids. **Incompatible materials**

Oxidizer.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

products

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------|---------|-------------|----------|
| 2-Butanone | | | | |
| | LD50 Oral | Rat | 2,737 mg/kg | - |
| | LD50 Dermal | Rabbit | 6,480 mg/kg | - |
| Benzene, methyl- | | | | |
| | LD50 Oral | Rat | 636 mg/kg | - |
| | LC50 Inhalation | Rat | 49 Mg/l | 4 h |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 11 of 23 Print Date 11/03/2023

| | Vapor | | | |
|--------------------------|-----------------|--------|--------------|-----|
| 2-Pentanone, 4-methyl- | <u> </u> | • | • | • |
| • | LD50 Oral | Rat | 2,080 mg/kg | - |
| Cyclohexanone | • | • | | • |
| • | LD50 Oral | Rat | 1,800 mg/kg | - |
| | LC50 Inhalation | Rat | 8,000 ppm | 4 h |
| | Gas. | | | |
| Methanol | | | | |
| | LD50 Oral | Rat | 5,600 mg/kg | - |
| | LC50 Inhalation | Rat | 145,000 ppm | 1 h |
| | Gas. | | | |
| | LC50 Inhalation | Rat | 64,000 ppm | 4 h |
| | Gas. | | | |
| | LD50 Dermal | Rabbit | 15,800 mg/kg | = |
| Formamide, N,N-dimethyl- | | | | |
| | LD50 Oral | Rat | 2,000 mg/kg | - |
| | LC50 Inhalation | Rat | 3,421 ppm | 1 h |
| | Gas. | | | |
| | LC50 Inhalation | Rat | 1,948 ppm | 4 h |
| | Gas. | | | |
| | LD50 Dermal | Rabbit | 4,720 mg/kg | _ |

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-----------|-------------|
| 2-Butanone | Skin - Mild irritant | Rabbit | - | 24 hrs | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Skin - Mild irritant | Rabbit | - | 24 hrs | - |
| Benzene, methyl- | Skin - Mild irritant | Pig | - | 24 hrs | - |
| | Skin - Mild irritant | Rabbit | - | | - |
| | Skin - Moderate irritant | Rabbit | - | | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Eyes - Mild irritant | Rabbit | - | | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hrs | - |
| | Eyes - Mild irritant | Rabbit | - | 0.008 hrs | - |
| 2-Pentanone, 4-methyl- | Eyes - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Skin - Mild irritant | Rabbit | - | 24 hrs | - |
| | Eyes - Severe irritant | Rabbit | - | | - |
| Cyclohexanone | Eyes - Severe irritant | Rabbit | - | 24 hrs | - |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 12 of 23 Print Date 11/03/2023

| | Skin - Mild irritant | Human | - | 48 hrs | - |
|--------------------------|--------------------------|--------|---|--------|---|
| | Skin - Mild irritant | Rabbit | - | | - |
| | Eyes - Severe irritant | Rabbit | - | | - |
| Methanol | Eyes - Moderate irritant | Rabbit | - | | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hrs | - |
| Formamide, N,N-dimethyl- | Skin - Mild irritant | Human | - | 24 hrs | - |
| | Eyes - Severe irritant | Rabbit | - | | - |
| | Eyes - Severe irritant | Rabbit | - | | - |

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Benzene, methyl- | - | 3 | - |
| 2-Pentanone, 4-methyl- | - | 2B | - |
| Cyclohexanone | - | 3 | - |
| Formamide, N,N- | - | 2A | - |
| dimethyl- | | | |

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 13 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

Conclusion/Summary : Mixture. Not fully tested.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|----------|------------|-------------------|---------------|
| Methanol | Category 1 | = | - |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation: May cause damage to organs following a single exposure if inhaled.Skin contact: May cause damage to organs following a single exposure in contact

with skin. Causes skin irritation.

Ingestion: Harmful if swallowed., May cause damage to organs following a

single exposure if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following: pain or irritation,

watering, redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following: irritation, redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 14 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

Conclusion/Summary : Mixture.Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity : Not available. **Developmental effects** : Not available.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral | Dermal | Inhalation (gases) | Inhalation (vapors) | Inhalation (dusts and mists) |
|-----------------------------------|--------------|-------------------|-----------------------|------------------------|------------------------------------|
| P1395A Blue Primer (60% dilution) | 1823.6 mg/kg | 166214.7 mg/kg | 52011.2 ppm | N/A | N/A |
| 2-Butanone | 2737 mg/kg | 6480 mg/kg | N/A | N/A | N/A |
| Benzene, methyl- | 636 mg/kg | N/A | N/A | 49 Mg/l | N/A |
| 2-Pentanone, 4-methyl- | 2080 mg/kg | N/A | N/A | N/A | N/A |
| Cyclohexanone | 1800 mg/kg | N/A | 8000 ppm | N/A | N/A |
| Methanol | 5600 mg/kg | 15800 mg/kg | 64000 ppm | N/A | N/A |
| Formamide, N,N-dimethyl- | 2000 mg/kg | 4720 mg/kg | 1948 ppm | N/A | N/A |

Other information : This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-----------------------------|----------------------------|----------|
| 2-Butanone | | | |
| | Acute LC50 3,220 Mg/l Fresh | Fish - Pimephales promelas | 96 h |
| | water | | |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 15 of 23 Print Date 11/03/2023

| | Acute EC50 5.091 Mg/l Fresh | Daphnia - Daphnia magna | 48 h |
|--------------------------|--|---------------------------------------|------|
| | water | | |
| | Acute EC50 > 500 Mg/l Marine water | Algae - Skeletonema costatum | 96 h |
| Benzene, methyl- | | | |
| | Acute LC50 5.5 Mg/l Fresh water | Fish - Oncorhynchus kisutch | 96 h |
| | Acute EC50 11.6 Mg/l Fresh water | Crustaceans - Gammarus pseudolimnaeus | 48 h |
| | Acute EC50 6 Mg/l Fresh water | Daphnia - Daphnia magna | 48 h |
| | Acute EC50 > 433 Mg/l Marine | Algae - Skeletonema costatum | 96 h |
| | Chronic NOEC 1 Mg/l Fresh | Daphnia - Daphnia magna | 21 d |
| 2-Pentanone, 4-methyl- | water | | |
| 2-1 chanone, 4-memyi- | Acute LC50 0.505 Mg/l Fresh water | Fish - Pimephales promelas | 96 h |
| | Chronic NOEC 168 Mg/l Fresh water | Fish - Pimephales promelas | 33 d |
| | Chronic NOEC 78 Mg/l Fresh water | Daphnia - Daphnia magna | 21 d |
| Cyclohexanone | | | |
| , | Acute LC50 0.527 Mg/l Fresh water | Fish - Pimephales promelas | 96 h |
| | Acute EC50 32.9 Mg/l | Algae - Chlamydomonas reinhardtii | 72 h |
| | Chronic EC10 3.56 Mg/l | Algae - Chlamydomonas reinhardtii | 72 h |
| Methanol | | | |
| | Acute LC50 290 Mg/l Fresh water | Fish - Danio rerio | 96 h |
| | Acute EC50 24.5 Mg/l Fresh water | Daphnia - Daphnia magna | 48 h |
| | Acute LC50 2,500 Mg/l Marine water | Crustaceans - Crangon crangon | 48 h |
| | Acute EC50 16.912 Mg/l Marine water | Algae - Ulva pertusa | 96 h |
| | Chronic NOEC 9.96 Mg/l Marine water | Algae - Ulva pertusa | 96 h |
| Formamide, N,N-dimethyl- | - | | 1 |
| | Acute EC50 7,100 Mg/l Fresh water | Fish - Lepomis macrochirus | 96 h |
| | Acute EC50 4.5 Mg/l Fresh water | Daphnia - Daphnia magna | 48 h |
| | Acute LC50 > 100 Mg/l Marine water | Crustaceans - Crangon crangon | 48 h |
| | • | | |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 16 of 23 Print Date 11/03/2023

| Chronic NOEC 100 Mg/l Fresh | Fish - Oncorhynchus mykiss | 30 d |
|-------------------------------|----------------------------|------|
| water | | |
| Chronic NOEC 1,500 Mg/l Fresh | Daphnia - Daphnia magna | 21 d |
| water | | |

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--------------------------|--------|-------|-----------|
| 2-Butanone | 0.29 | - | low |
| Benzene, methyl- | 2.73 | 90.00 | low |
| 2-Pentanone, 4-methyl- | 1.9 | - | low |
| Cyclohexanone | 0.86 | - | low |
| Methanol | -0.77 | 10.00 | low |
| Formamide, N,N-dimethyl- | -1.01 | 0.79 | low |

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 17 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

| Ingredient | CAS# | Status | Reference number |
|------------------------|----------|--------|------------------|
| Methyl ethyl ketone | 78-93-3 | Listed | |
| Benzene, methyl- | 108-88-3 | Listed | |
| Methyl isobutyl ketone | 108-10-1 | Listed | |
| Cyclohexanone | 108-94-1 | Listed | |
| Methyl alcohol | 67-56-1 | Listed | |

Section 14. Transport information

U.S.DOT 49CFR : Not regulated for transportation. Ground/Air/Water

International Air ICAO/IATA

: UN1139, Coating Solution, 3, PGII

International Water

IMO/IMDG

: UN1139, COATING SOLUTION, 3, PGII

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 18 of 23 Print Date 11/03/2023

United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Naphthalene

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Benzene, methyl-

1-Cyanoguanidine

Phenol

Ethyl benzene

Benzene

Naphthalene

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name | CAS-No. | RQ for component |
|-------------------|---------|------------------|
| Dimethylformamide | 68-12-2 | 100 lb(s) |
| | | 45.4 kg |
| | | |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 19 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

| Benzene, methyl- | 108-88-3 | 1,000 lb(s) |
|------------------|----------|-------------|
| - | | 454 kg |
| | | 454 kg |
| | | 1,000 lb(s) |
| | | |

SARA 311/312

Classification : ACUTE TOXICITY - oral - Category 4

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 2

Composition/information on ingredients

| Name | % | Classification |
|--------------------------|---------------|--|
| 2-Butanone | >= 25 - <= 50 | FLAMMABLE LIQUIDS - Category 2 |
| | | SKIN IRRITATION - Category 2 |
| | | EYE IRRITATION - Category 2A |
| | | |
| Benzene, methyl- | >= 10 - <= 25 | FLAMMABLE LIQUIDS - Category 2 |
| | | ACUTE TOXICITY - oral - Category 4 |
| | | SKIN IRRITATION - Category 2 |
| | | EYE IRRITATION - Category 2A |
| | | |
| 2-Pentanone, 4-methyl- | >= 10 - <= 25 | FLAMMABLE LIQUIDS - Category 2 |
| | | EYE IRRITATION - Category 2A |
| | | CARCINOGENICITY - Category 2 |
| | | |
| Cyclohexanone | >= 3 - <= 5 | FLAMMABLE LIQUIDS - Category 3 |
| | | ACUTE TOXICITY - oral - Category 4 |
| | | ACUTE TOXICITY - inhalation - Category 4 |
| | | EYE IRRITATION - Category 2A |
| | | |
| Methanol | >= 3 - <= 5 | FLAMMABLE LIQUIDS - Category 2 |
| | | SKIN IRRITATION - Category 2 |
| | | EYE IRRITATION - Category 2A |
| | | SPECIFIC TARGET ORGAN TOXICITY (SINGLE |
| | | EXPOSURE) - Category 1 |
| | | |
| Formamide, N,N-dimethyl- | >= 1 - <= 3 | FLAMMABLE LIQUIDS - Category 3 |
| | | ACUTE TOXICITY - oral - Category 4 |
| | | ACUTE TOXICITY - inhalation - Category 3 |



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 20 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

| | | EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1B |
|--|--|--|
|--|--|--|

SARA 313

Form R - Reporting requirements

| Product name | CAS number | % |
|------------------------|------------|--------------|
| Benzene, methyl- | 108-88-3 | >= 10 - < 30 |
| Methyl isobutyl ketone | 108-10-1 | >= 10 - < 30 |
| Methyl alcohol | 67-56-1 | >= 1 - < 5 |
| Dimethylformamide | 68-12-2 | >= 1 - < 5 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

Methyl ethyl ketone Benzene, methyl-Methyl isobutyl ketone Cyclohexanone

Methyl alcohol Dimethylformamide

New York : The following components are listed:

Methyl ethyl ketone Benzene, methyl-Methyl isobutyl ketone Cyclobeyanone

Cyclohexanone Methyl alcohol Dimethylformamide

New Jersey : The following components are listed:

Methyl ethyl ketone Benzene, methyl-Methyl isobutyl ketone Cyclohexanone Methyl alcohol

Cyclohexanone Methyl alcohol Dimethylformamide

Phenol

Pennsylvania : The following components are listed:

20/23



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 21 of 23 Print Date 11/03/2023

Methyl ethyl ketone

Benzene, methyl-

Methyl isobutyl ketone

Cyclohexanone

Methyl alcohol

Dimethylformamide

California Prop. 65

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Dimethylformamide, which is known to the State of California to cause cancer, and Benzene, methyl-, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Ingredient name | No significant risk level | Maximum acceptable dosage level |
|------------------------|---------------------------|---------------------------------|
| Benzene, methyl- | - | Yes. |
| Methyl isobutyl ketone | - | - |
| Methyl alcohol | - | Yes. |
| Dimethylformamide | - | - |

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia : Not determined.

Canada : All components are listed or exempted.

China : Not determined.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand: Not determined.Philippines: Not determined.Republic of Korea: Not determined.Taiwan: Not determined.Thailand: Not determined.Turkey: Not determined.

United States : All components are active or exempted.



P1395A Blue Primer (60% dilution)

Version Number 1.0 Page 22 of 23 Revision Date 11/02/2023 Print Date 11/03/2023

Viet Nam : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| Health | * | 3 |
|------------------|---|---|
| Flammability | | 0 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 11/03/2023Date of issue/Date of revision: 11/02/2023Date of previous issue: 00/00/0000

Version : 1.0

Key to abbreviations: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.



P1395A Blue Primer (60% dilution)

Version Number 1.0 Revision Date 11/02/2023 Page 23 of 23 Print Date 11/03/2023