

MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

Version Number 1.0 Revision Date 04/19/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XPL189 AMBER 1627
Product code	:	I018900P9327
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to ever
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

sion Number 1.0 ision Date 04/19/2002	Page 2 Print Date 11/4/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

ion Number 1.0 sion Date 04/19/2002	Page 3 Print Date 11/4/2
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields.
Hand protection	: Protective gloves.
Skin and body protection	: Long sleeved clothing.
Additional Protective Measures	: Safety shoes.
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	Time Weighted Average (TWA):	Dust. as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	Dust. as Sn	ACGIH
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	Dust. as Sn	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES



MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

ersion Number 1.0 evision Date 04/19/2002		Page 4 of Print Date 11/4/201
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Evaporation rate Pellets, powder Specific Gravity TRANSPARENT Bulk density Very faint Vapor pressure Not determined Vapor density Not applicable pH Insoluble 	 Not applicable. Not determined Not established Not applicable Not applicable Not applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. 	
	11. TOXICOLOGICAL INFORMATION	

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester		

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	No data available.
Additional advice	:	Not applicable



MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

sion Number 1.0 ision Date 04/19/2002		Page 5 Print Date 11/4/2
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc.	losu	ire List
CAS-No. 57583-35-4 1333-86-4 7439-92-1 7439-97-6		



MATERIAL SAFETY DATA SHEET

XPL189 AMBER 1627

Version Number 1.0 Revision Date 04/19/2002 Page 6 of 6 Print Date 11/4/2011

DSL	: Listed.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.