

MATERIAL SAFETY DATA SHEET

210 WHT 271 PL

Version Number 1.0 Revision Date 03/10/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	210 WHT 271 PL
Product code	:	I021000B1271
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Dibutyltin mercaptide	10584-98-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.





210 WHT 271 PL

sion Date 03/10/2003	Print Date 11/10/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2). Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion	 pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Hazards	fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET

210 WHT 271 PL

ion Number 1.0 sion Date 03/10/2003			Print D	Page 3 ate 11/10/2
	7.	HANDLING AND STORAG	i E	
Handling		Take measures to prevent the bundly in areas with appropriate exondensates may contain combulean hoods, ducts, and other sumese materials.	chaust ventilation. Proce stible or toxic residue. I	essing fume Periodically
Storage		Leep containers dry and tightly nd contamination. Keep in a dr		absorption
8. F	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	to personal respiratory protection	ve equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practice
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH

1		1	1 71	
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1
Dibutyltin mercaptide	0.1 mg/m3	Time Weighted Average	Total dust. as Sn	ACGIH
		(TWA):		
	0.2 mg/m3	Short Term Exposure Limit	Total dust. as Sn	ACGIH
		(STEL):		
Dibutyltin mercaptide	0.1 mg/m3	PEL:	Total dust. as Sn	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES



210 WHT 271 PL

PolyOne.

Version Number 1.0 Revision Date 03/10/2003		Page 4 of 6 Print Date 11/10/2011
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Pellets, powder Speci : WHITE Bulk : Very faint Vapo	poration rate:Not applicable.effic Gravity:Not determineddensity:Not establishedor pressure:Not applicableor density:Not applicable:Not applicable:Not applicable
	10. STABILITY AND REACTI	IVITY
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing age decomposition, do not overhea	ents and open flame. To avoid thermal at.
Incompatible Materials		s and oxidizing agents. Avoid contact d acetal copolymers during processing.
Hazardous decomposition products	(NOx), other hazardous mater Prolonged heating (approxima (200 °C) or short term heating	n monoxide (CO), oxides of nitrogen rials, and smoke are all possible. ately 30 minutes or more) above 392 °F at 482 °F (250 °C) may result in product of carbon monoxide and hydrogen

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
10584-98-2	Dibutyltin mercaptide	Irritant	Eyes, Skin.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	No data available.
Additional advice	:	Not applicable



MATERIAL SAFETY DATA SHEET

210 WHT 271 PL

sion Number 1.0 ision Date 03/10/2003	Page 5 Print Date 11/10/2
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status TSCA Status	 Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: WARNING! This product contains a chemical known to the State of
65	California to cause cancer.
SARA Title III Section 302 Ex	tremely Hazardous Substance
Not applicable	
SARA Title III Section 313 To	xic Chemicals:
	Not applicable

MATERIAL SAFETY DATA SHEET



Version Number 1.0 Revision Date 03/10/2003

Page 6 of 6 Print Date *11/10/2011*

olvOne

Canadian Regulations:	
WHMIS Classification : D2B	
WHMIS Ingredient Disclosure List	
CAS-No. 10584-98-2	
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:	
Australia AICS : Listed.	
China IECS : Not determined.	
Europe EINECS : Not determined.	
Japan ENCS : Not determined.	
Korea KECI : Not determined.	
Philippines PICCS : Listed.	
16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.