

MATERIAL SAFETY DATA SHEET GEON L1547 WHITE 1335

Version Number 1.0 Revision Date 06/08/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON L1547 WHITE 1335
Product code	:	L1547A0A1335
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Dibutyltin mercaptide	10584-98-2	1 - 5
Calcium carbonate	471-34-1	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET GEON L1547 WHITE 1335

Version Number 1.0 Revision Date 06/08/2004 Page 2 of 6 Print Date 11/14/2011

Medical Conditions Aggravated by Exposure:	: None known.
88	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxid of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET GEON L1547 WHITE 1335

Version Number 1.0 Revision Date 06/08/2004 Page 3 of 6 Print Date 11/14/2011

ACGIH

as Sn

	7	HANDLING AND STORAG	ĨĿ	
	7.	HANDLING AND STOKAG	τĽ	
Handling	0 C C	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.		
Storage		Keep containers dry and tightly nd contamination. Keep in a d		e absorption
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	· N	Lo porconal regulatory protecti	ua aquinmant normally r	aquirad
Respiratory protection	. 1	lo personal respiratory protecti	ve equipment normany i	equireu.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	: Long sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.			
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Dibutyltin mercaptide	0.1 mg/m3	PEL:	Total dust. as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.0 / 2		a	1 COTT

9. PHYSICAL AND CHEMICAL PROPERTIES

(STEL):

0.2 mg/m3 Short Term Exposure Limit



MATERIAL SAFETY DATA SHEET **GEON L1547 WHITE 1335**

Version Number 1.0 Revision Date 06/08/2004

Conditions to avoid

Page 4 of 6 Print Date 11/14/2011

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets, powder WHITE Very faint Not determined Not applicable Insoluble 	Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH	 Not applicable Not determined Not established Not applicable Not applicable Not applicable
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		

:	Keep away from oxidizing agents and open flame. To avoid thermal
	decomposition, do not overheat.

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact
		with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.
----------------------------------	---	---

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
10584-98-2	Dibutyltin mercaptide	Irritant	Eyes, Skin.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET GEON L1547 WHITE 1335

Version Number 1.0 Revision Date 06/08/2004 Page 5 of 6 Print Date 11/14/2011

Environmental Toxicity	: Adverse ecological impact is not known or expected under normal u
Bioaccumulation Potential	: No data available
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSO Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State California to cause cancer.
SARA Title III Section 302 E	xtremely Hazardous Substance
Not applicable	

PolyOne

MATERIAL SAFETY DATA SHEET **GEON L1547 WHITE 1335**

Version Number 1.0 Revision Date 06/08/2004 Page 6 of 6 Print Date 11/14/2011

Not applicable Canadian Regulations:		
National Pollutant Release	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	osu	re List
CAS-No. 10584-98-2		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Listed

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.