

MATERIAL SAFETY DATA SHEET **GEON L1555 WHITE 1077**

Version Number 1.0 Revision Date 07/16/2003

Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON L1555 WHITE 1077
Product code	:	L1555J0A1077
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Dibutyltin mercaptide	10584-98-2	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET GEON L1555 WHITE 1077

Version Number 1.0 Revision Date 07/16/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure:	:	: None known.		
		4. FIRST AID MEASURES		
Inhalation		Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion		Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes		Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin		Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5	. FIRE-FIGHTING MEASURES		
Flash point	:	Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: : :	Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).		
Special Fire Fighting Procedures		Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.		
Unusual Fire/Explosion Hazards		May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.		
	6. AC	CIDENTAL RELEASE MEASURES		
Personal precautions		Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions		Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up		Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		



MATERIAL SAFETY DATA SHEET GEON L1555 WHITE 1077

Version Number 1.0 Revision Date 07/16/2003 Page 3 of 6 Print Date 11/11/2011

	7.	HANDLING AND STOR	RAGE	
Handling		Take measures to prevent the nly in areas with appropriate ondensates may contain con- lean hoods, ducts, and other nese materials.	te exhaust ventilation. Pro mbustible or toxic residue.	cessing fume Periodically
Storage		Leep containers dry and tight nd contamination. Keep in		re absorption
8. H	EXPOSURE	CONTROLS / PERSONA	AL PROTECTION	
Respiratory protection	: N	lo personal respiratory prot	ective equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shie	elds.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with g Vash hands before breaks a		safety practice.
Engineering measures		leat only in areas with appr ppropriate exhaust ventilati		. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1
Dibutyltin mercaptide	0.1 mg/m3	Time Weighted Average (TWA):	e Total dust. as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Lin (STEL):	nit Total dust. as Sn	ACGIH
Dibutyltin mercaptide	0.1 mg/m3	PEL:	Total dust. as Sn	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL P	PROPERTIES	
Form	: Solid		aporation rate : No	ot applicable.
Appearance				ot determined
Color	: WHI			ot established
			2	t applicable



MATERIAL SAFETY DATA SHEET **GEON L1555 WHITE 1077**

Version Number 1.0 Revision Date 07/16/2003

Page 4 of 6 Print Date 11/11/2011

Melting point/range Boiling Point: Water solubility	: Not determined Vapor density : Not applicable : Not applicable pH : Not applicable : Insoluble	
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.	
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in produc decomposition and evolution of carbon monoxide and hydrogen chloride. 	t

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	hemical Name	Effect	Target Organ		
10584-98-2	Dibuty	ltin mercaptide	Irritant	Eyes, Skin.		
13463-67-7	Titaniu	m dioxide	Systemic effects	Respiratory system.		
		12. ECOLOGIC	CAL INFORMATION	1		
Persistence and degr	adability	: Not readily bi	odegradable.			
Environmental Toxicity		: Adverse ecological impact is not known or expected under normal use.				
Bioaccumulation Potential		: No data available.				
Additional advice		: Not applicable	e			
		13. DISPOSAL	CONSIDERATIONS			
Product		possible, recy	cling is preferred to di	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste		



MATERIAL SAFETY DATA SHEET GEON L1555 WHITE 1077

rsion Number 1.0 vision Date 07/16/2003		Page 5 of Print Date 11/11/201
		classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	xtrem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 To	oxic C	Themicals:
Not applicable Canadian Regulations:		
Callaulali Regulatiolis.		
National Pollutant Rele	ase Ir	iventory (NPRI)
-	ease Ir	iventory (NPRI)

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON L1555 WHITE 1077**

Version Number 1.0 Revision Date 07/16/2003 Page 6 of 6 Print Date *11/11/2011*

W	HMIS Ingredient Disclo	osu	re List	
	CAS-No. 10584-98-2			
D	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National	Inventories:			
А	ustralia AICS	:	Listed.	
C	China IECS	:	Not determined.	
E	urope EINECS	:	Not determined.	
Ja	apan ENCS	:	Not determined.	
K	Korea KECI	:	Not determined.	
Р	hilippines PICCS	:	Listed.	
			16. OTHER INFORMATION	-

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.