

MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

Version Number 1.0 Revision Date 10/22/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON M6215 BLU 4260
Product code	:	M621500B4260
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	0.1 - 1
Calcium carbonate	471-34-1	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

Version Number 1.0 Revision Date 10/22/2002 Page 2 of 6 Print Date 11/6/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

2/6



MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

ion Number 1.0 sion Date 10/22/2002				Print	Page 3 Date 11/6/2
Handling		nly in areas with appro ondensates may contain	priate ex 1 combu	ild up of electrostatic ch chaust ventilation. Proce stible or toxic residue. I faces to minimize accur	essing fume Periodically
Storage		eep containers dry and nd contamination. Kee		closed to avoid moisture ry, cool place.	e absorption
8. H	EXPOSURE	CONTROLS / PERS	ONAL]	PROTECTION	
Respiratory protection	: N	lo personal respiratory	protectiv	ve equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-	-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance wi Vash hands before brea		industrial hygiene and sa t the end of workday.	afety practice
Engineering measures		leat only in areas with a ppropriate exhaust vent		ate exhaust ventilation. at machinery.	Provide
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Ave (TWA):	erage	Dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICA	L PRO	PERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: BLU : Very : Not o	ts, powder E faint determined applicable	Specifi Bulk de Vapor	c Gravity : Not ensity : Not pressure : Not density : Not	applicable. determined established applicable applicable applicable
	10. 8	STABILITY AND RE	ACTIV	ITY	



MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

Version Number 1.0 Revision Date 10/22/2002 Page 4 of 6 Print Date 11/6/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:



MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

Version Number 1.0 Revision Date 10/22/2002 Page 5 of 6 Print Date 11/6/2011

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	Net as subted for the second station
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or ar exempt.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)



MATERIAL SAFETY DATA SHEET

GEON M6215 BLU 4260

Page 6 of 6 011

Number 1.0 n Date 10/22/2002				Print Date
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Prod
Arsenic	7440-38-2	0.0031	001 lbs	32,258 LB
California Propositio 65		ING! This produnia to cause cance	ict contains a chemica er.	l known in the
RA Title III Section 302 Not applicable	Extremely Haza	rdous Substance		
adian Regulations:				
WHMIS Classification	on : D2A			
DSL	: Listed.			
onal Inventories:				
Australia AICS	: Listed.			
China IECS	: Listed.			
Europe EINECS	: Not det	ermined.		
Japan ENCS	: Not det	ermined.		
Korea KECI	: Listed.			
Philippines PICCS	: Not det	ermined.		
	16.00	THER INFORM		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.