MATERIAL SAFETY DATA SHEET **GEON 121A**

Version Number 1.7 Revision Date 01/05/2012 Page 1 of 6 Print Date 1/29/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON 121A
Product code	:	P0121A00DP
Chemical Name	:	Ethene, chloro-, homopolymer
CAS-No.	:	9002-86-2
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating. At process temperatures, product emissions may cause irritation.
Ingestion	: No adverse health effects are anticipated.
Eyes	: Resin particles, like other inert materials, can be mechanically irritating. At process temperatures, product emissions may cause irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **GEON 121A**

Version Number 1.7 Revision Date 01/05/2012 Page 2 of 6 Print Date 1/29/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Not an anticipated hazard.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: 736 °F ASTM D1929
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Water spray, Dry powder, Foam, Carbon dioxide (CO2). Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. The solid polymer can only be burned with difficulty. Fires will tend to self-extinguish in the absence of a substantial external source of heat or flame. Hydrogen Chloride (HCl) is generated upon product combustion. Prompt cleaning of surfaces with water based detergents is indicated after a fire to minimize corrosive attack. Vinyl resin dust has a very low tendency to explode. The minimum ignition energy for vinyl resin dust clouds is much higher than that of natural materials such as starch and flour or of other plastic materials. However, as with any powder material, care should be taken to avoid creation of dust clouds and to minimize ignition sources. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Material can create slippery conditions.




MATERIAL SAFETY DATA SHEET **GEON 121A**

ion Number 1.7 sion Date 01/05/2012	Page Print Date 1/29
Environmental precautions	: Should not be released into the environment. The product should n
	be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir appropriate container for disposal. Refer to Section 13 of this MSD for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of static electricity. Use only in area provided with appropriate exhaust ventilation. Material can create slippery conditions.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination.
8. EXP	OSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: Under normal handling conditions a respirator may not be required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Th product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	
There are no known hazardou	s components above regulatory thresholds in this product.
Q	PHYSICAL AND CHEMICAL PROPERTIES

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON 121A**

Version Number 1.7 Revision Date 01/05/2012



Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid powder, granular NOT APPLICABLE very faint Not established not applicable insoluble 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined 20 to 25 lbs/ft3 not applicable not applicable not applicable 		
10. STABILITY AND REACTIVITY					

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

There are no known hazardous components above regulatory thresholds in this product.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	Does not bioaccumulate.
Additional advice	:	no data available

13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET **GEON 121A**

sion Number 1.7	Page 5 o			
ision Date 01/05/2012	Print Date 1/29/20			
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.			
IMO/IMDG (maritime)	: Not regulated for transportation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)			
not applicable				
California Proposition : Not applicable 65				
SARA Title III Section 302 Extremely Hazardous Substance				
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
SARA Title III Section 313 To	oxic Chemicals:			
SARA The III Section 313 T	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation			
	identified under this section, this product is Not Applicable under this regulation			

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **GEON 121A**

Version Number	er 1.7
Revision Date	01/05/2012

_

Page 6 of 6 Print Date 1/29/2012

National Pollutant Release Inventory (NPRI)				
not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Listed		
China IECS	:	Listed		
Europe EINECS	:	Listed		
Japan ENCS	:	Listed		
Korea KECI	:	Listed		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.