MATERIAL SAFETY DATA SHEET **Geon E-34**

Version Number 1.0 Revision Date 02/16/2007

Product Use

Page 1 of 6 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Geon E-34
Product code	:	SR20000079
Chemical Name	:	Ethene, chloro-, homopolymer
CAS-No.	:	9002-86-2

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating. At process temperatures, product emissions may cause irritation.
Ingestion	: No adverse health effects are anticipated.
Eyes	: Resin particles, like other inert materials, can be mechanically irritating. At process temperatures, product emissions may cause irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
em ome exposure	
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **Geon E-34**

Version Number 1.0 Revision Date 02/16/2007 Page 2 of 6 Print Date 11/26/2011

Inhalation	: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Not an anticipated hazard.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: 736 °F ASTM D1929
Plash politi	. 750 PASTWD1929
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: water spray, dry powder, foam, carbon dioxide (CO2)none.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: The solid polymer can only be burned with difficulty. Fires will tend to self-extinguish in the absence of a substantial external source of hea or flame. Hydrogen Chloride (HCl) is generated upon product combustion. Prompt cleaning of surfaces with water based detergents is indicated after a fire to minimize corrosive attack. Vinyl resin dust has a very low tendency to explode. The minimum ignition energy for vinyl resin dust clouds is much higher than that of natural materials such as starch and flour or of other plastic materials. However, as with any powder material, care should be taken to avoid creation of dust clouds and to minimize ignition sources. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Material can create slippery conditions.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.



MATERIAL SAFETY DATA SHEET **Geon E-34**

ision Date 02/16/2007	Print Date 11/26/2
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of static electricity. Use only a area provided with appropriate exhaust ventilation. Material can create slippery conditions.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination.
8. EXI	OSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: Under normal handling conditions a respirator may not be required. dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields.
Hand protection	: Protective gloves.
Skin and body protection	: Long sleeved clothing.
Additional Protective Measures	: Safety shoes.
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limit will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	
There are no known hazardo	s components above regulatory thresholds in this product.
9	PHYSICAL AND CHEMICAL PROPERTIES
Form Appearance Color	: SolidEvaporation rate: Not applicable: powder, granularSpecific Gravity:: 1.4: NOT APPLICABLEBulk density: 20 to 25 lbs/ft3

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **Geon E-34**

Version Number 1.0 Revision Date 02/16/2007		Page 4 of 6 Print Date <i>11/26/2011</i>
Odor Melting point/range Boiling Point: Water solubility	 Very faint Vapor pressure Not established Vapour density Not applicable pH Insoluble 	Not applicableNot applicableNot applicable
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: To avoid thermal decomposition, do not ov oxidizing agents and open flame.	verheat. Keep away from
Incompatible Materials	: Avoid contact with strong oxidizers. Also, acetal copolymers and with amine containing processing. At processing conditions, thes destructive and involve rapid degradation. mechanically clean processing equipment to quantities of these materials from coming in Prevent cross contamination of feedstocks.	ng materials during e materials are mutually Thoroughly purge and to avoid even trace n contact with each other.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide ((NOx), other hazardous materials, and smo Prolonged heating (approximately 30 minu (200 °C) or short term heating at 482 °F (25 decomposition and evolution of carbon mo chloride.	ke are all possible. tes or more) above 392 °F 50 °C) may result in product
	11. TOXICOLOGICAL INFORMATION	

There are no known hazardous components above regulatory thresholds in this product.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	Does not bioaccumulate.
Additional advice	:	No data available

13. DISPOSAL CONSIDERATIONS

Product

: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET **Geon E-34**

sion Number 1.0 ision Date 02/16/2007	Page 5 of Print Date 11/26/201
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313	Foxic Chemicals:
	e identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are	e identified under tills section, tills product is Not Applicable under tills regulatio
Unless specific chemicals are Canadian Regulations:	e identified under tins section, tins product is Not Applicable under tins regulation
Canadian Regulations:	lease Inventory (NPRI)



MATERIAL SAFETY DATA SHEET **Geon E-34**

Version Number 1.0 Revision Date 02/16/2007		Page 6 of 6 Print Date 11/26/2011
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.