## MATERIAL SAFETY DATA SHEET GEON E7365 WHITE 1640

Version Number 1.3 Revision Date 08/22/2003

Page 1 of 6 Print Date 11/12/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| NON-EMERGENCY<br>TELEPHONE    | : | Product Stewardship (440)-930-1395   |
|-------------------------------|---|--|
| Emergency telephone<br>number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name                  | : | GEON E7365 WHITE 1640  |
| Product code                  | : | VC10000139   |
| Chemical Name                 | : | Mixture  |
| CAS-No.                       | : | Mixture  |
| Product Use                   | : | Industrial Applications  |

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components            | CAS-No.    | Weight % |
|-----------------------|------------|----------|
| Calcium carbonate     | 471-34-1   | 1 - 5    |
| Dibutyltin mercaptide | 10584-98-2 | 1 - 5    |
| Titanium dioxide      | 13463-67-7 | 5 - 10   |

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

#### POTENTIAL HEALTH EFFECTS

| Routes of Exposure:             | : Inhalation, Ingestion, Skin contact   |
|---------------------------------|---|
| Acute exposure                  |   |
| Inhalation<br>Ingestion<br>Eyes | <ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul> |



## MATERIAL SAFETY DATA SHEET GEON E7365 WHITE 1640

Version Number 1.3 Revision Date 08/22/2003 Page 2 of 6 Print Date 11/12/2011

| Skin  | : Experience shows no unusual dermatitis hazard from routine handling   |
|---|---|
| Chronic exposure  | : Refer to Section 11 for Toxicological Information.  |
| Medical Conditions<br>Aggravated by Exposure:   | : None known.   |
|   | 4. FIRST AID MEASURES   |
| Inhalation  | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.  |
| Ingestion   | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.  |
| Eyes  | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.  |
| Skin  | : Wash off with soap and plenty of water. If skin irritation persists see medical attention.  |
|   | 5. FIRE-FIGHTING MEASURES   |
| Flash point   | : Not applicable  |
| Flammable Limits<br>Upper explosion limit<br>Lower explosion limit<br>Autoignition temperature<br>Suitable extinguishing media<br>Special Fire Fighting<br>Procedures | <ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable.</li> <li>water, dry powder, foam, carbon dioxide (CO2).</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul> |
| Unusual Fire/Explosion<br>Hazards   | : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.  |
|   | 6. ACCIDENTAL RELEASE MEASURES  |
| Personal precautions  | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.  |
| Environmental precautions   | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.  |
| Methods for cleaning up   | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.  |



# MATERIAL SAFETY DATA SHEET GEON E7365 WHITE 1640

Version Number 1.3 Revision Date 08/22/2003 Page 3 of 6 Print Date 11/12/2011

|                                   | 7.       | . HANDLING AND STORAG  | <del>JE</del>           |          |  |  |
|-----------------------------------|----------|--|-------------------------|----------|--|--|
| Handling                          |          | Take measures to prevent the build up of electrostatic charge. Heat<br>only in areas with appropriate exhaust ventilation. Processing fume<br>condensates may contain combustible or toxic residue. Periodically<br>clean hoods, ducts, and other surfaces to minimize accumulation of<br>these materials. |                         |          |  |  |
| Storage                           |          | Keep containers dry and tightly closed to avoid moisture absorption<br>and contamination. Keep in a dry, cool place.   |                         |          |  |  |
| <b>8.</b> E                       | XPOSURE  | CONTROLS / PERSONAL  | PROTECTION              |          |  |  |
| Respiratory protection            | : 1      | No personal respiratory protecti   | ve equipment normally r | equired. |  |  |
| Eye/Face Protection               | : \$     | Safety glasses with side-shields.  |                         |          |  |  |
| Hand protection                   | : F      | Protective gloves.   |                         |          |  |  |
| Skin and body protection          | : I      | Long sleeved clothing.   |                         |          |  |  |
| Additional Protective<br>Measures | : 5      | Safety shoes.  |                         |          |  |  |
| General Hygiene<br>Considerations |          | Handle in accordance with good industrial hygiene and safety practice.<br>Wash hands before breaks and at the end of workday.  |                         |          |  |  |
| Engineering measures              |          | Heat only in areas with appropri<br>appropriate exhaust ventilation  |                         | Provide  |  |  |
| Exposure limit(s)                 |          |  |                         |          |  |  |
| Components                        | Value    | Exposure time  | Exposure type           | List:    |  |  |
| Calcium carbonate                 | 5 mg/m3  | PEL:   | Respirable fraction.    | OSHA Z1  |  |  |
|                                   | 15 mg/m3 | PEL:   | Total dust.             | OSHA Z1  |  |  |

|                       |           | (TWA):                    |                   |         |
|-----------------------|-----------|---------------------------|-------------------|---------|
| Titanium dioxide      | 10 mg/m3  | Time Weighted Average     |                   | ACGIH   |
|                       | _         | (TWA):                    |                   |         |
| Titanium dioxide      | 15 mg/m3  | PEL:                      | Total dust.       | OSHA Z1 |
| Dibutyltin mercaptide | 0.1 mg/m3 | PEL:                      | Total dust. as Sn | OSHA Z1 |
| Dibutyltin mercaptide | 0.1 mg/m3 | Time Weighted Average     | as Sn             | ACGIH   |
|                       | _         | (TWA):                    |                   |         |
|                       | 0.2 mg/m3 | Short Term Exposure Limit | as Sn             | ACGIH   |
|                       |           | (STEL):                   |                   |         |

### 9. PHYSICAL AND CHEMICAL PROPERTIES



# MATERIAL SAFETY DATA SHEET **GEON E7365 WHITE 1640**

Version Number 1.3 Revision Date 08/22/2003 Page 4 of 6 Print Date 11/12/2011

| Form<br>Appearance<br>Color<br>Odor<br>Melting point/range<br>Boiling Point: | <ul> <li>Solid</li> <li>Pellets, powder</li> <li>WHITE</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> </ul> | Evaporation rate<br>Specific Gravity<br>Bulk density<br>Vapor pressure<br>Vapor density<br>pH | <ul> <li>Not applicable.</li> <li>Not determined</li> <li>Not established</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul> |
|--|---|---|--|
| Water solubility Stability   | : Insoluble<br><b>10. STABILITY ANI</b><br>: Stable.  | 1   |  |

| Hazardous Polymerization         | : | Will not occur.   |
|----------------------------------|---|---|
| Conditions to avoid              | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.  |
| Incompatible Materials           | : | Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.  |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.<br>Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name         | Effect           | Target Organ        |
|------------|-----------------------|------------------|---------------------|
| 471-34-1   | Calcium carbonate     | Irritant         | Eyes, Skin.         |
| 10584-98-2 | Dibutyltin mercaptide | Irritant         | Eyes, Skin.         |
| 13463-67-7 | Titanium dioxide      | Systemic effects | Respiratory system. |

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.  | Chemical Name     | Route     | Value       | Species |
|----------|-------------------|-----------|-------------|---------|
| 471-34-1 | Calcium carbonate | Oral LD50 | 6,450 mg/kg | rat     |

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

PolyOne.

## MATERIAL SAFETY DATA SHEET GEON E7365 WHITE 1640

Version Number 1.3 Revision Date 08/22/2003 Page 5 of 6 Print Date 11/12/2011

| Environmental Toxicity       | : Adverse ecological impact is not known or expected under normal use  |
|------------------------------|--|
| Bioaccumulation Potential    | : No data available.   |
| Additional advice            | : Not applicable   |
|                              | 13. DISPOSAL CONSIDERATIONS  |
| Product                      | : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging       | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.  |
|                              | 14. TRANSPORT INFORMATION  |
|                              |  |
| U.S. DOT Classification      | : Not regulated for transportation.  |
| ICAO/IATA                    | : Not regulated for transportation.  |
| IMO / IMDG                   | : Not regulated for transportation.  |
|                              | 15. REGULATORY INFORMATION   |
| US Regulations:              |  |
| OSHA Status                  | : Classified as hazardous based on components.   |
| TSCA Status                  | : All components of this product are listed on or exempt from the TSCA Inventory.  |
| US. EPA CERCLA Hazardou      | Substances (40 CFR 302)  |
| Not applicable               |  |
| California Proposition<br>65 | : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.   |
| SARA Title III Section 302 E | stremely Hazardous Substance   |
|                              | -  |

## MATERIAL SAFETY DATA SHEET GEON E7365 WHITE 1640

Version Number 1.3 Revision Date 08/22/2003 Page 6 of 6 Print Date *11/12/2011* 

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

| CAS-No.    |  |
|------------|--|
| 10584-98-2 |  |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS    | : Listed.         |
|-------------------|-------------------|
| China IECS        | : Not determined. |
| Europe EINECS     | : Not determined. |
| Japan ENCS        | : Not determined. |
| Korea KECI        | : Not determined. |
| Philippines PICCS | : Listed.         |
|                   |                   |

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.