

MATERIAL SAFETY DATA SHEET

GEON 87787 WHITE 1544

Version Number 1.0 Revision Date 05/25/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| NON-EMERGENCY TELEPHONE | : | Product Stewardship (440)-930-1395 |
|-------------------------------|---|--|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | GEON 87787 WHITE 1544 |
| Product code | : | VC10000369 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|------------|----------|
| Calcium carbonate | 471-34-1 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|----------------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |



MATERIAL SAFETY DATA SHEET

GEON 87787 WHITE 1544

Version Number 1.0 Revision Date 05/25/2002 Page 2 of 6 Print Date 11/4/2011

| Medical Conditions : None known. Aggravated by Exposure: : None known. | | | | |
|--|---|--|--|--|
| | 4. FIRST AID MEASURES | | | |
| | 4. FIKST AID MEASURES | | | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. | | | |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. | | | |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. | | | |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. | | | |
| | 5. FIRE-FIGHTING MEASURES | | | |
| Flash point | : Not applicable | | | |
| Flammable Limits | | | | |
| Upper explosion limit | : Not applicable | | | |
| Lower explosion limit | : Not applicable | | | |
| Autoignition temperature | : Not applicable. | | | |
| Suitable extinguishing media | : water, dry powder, foam, carbon dioxide (CO2). | | | |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne | | | |
| | contaminants. | | | |
| Unusual Fire/Explosion Hazards | : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. | | | |
| | 6. ACCIDENTAL RELEASE MEASURES | | | |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. | | | |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. | | | |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods. | | | |
| | 7. HANDLING AND STORAGE | | | |



MATERIAL SAFETY DATA SHEET

GEON 87787 WHITE 1544

| sion Number 1.0 vision Date 05/25/2002 | | | Print | Page 3 of Date 11/4/201 | |
|---|-------------|--|-----------------------|----------------------------|--|
| Handling | 0 C C | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. | | | |
| Storage | | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | | | |
| 8. I | EXPOSURE | CONTROLS / PERSONAL | PROTECTION | | |
| Respiratory protection | : N | Vo personal respiratory protecti | ve equipment normally | required. | |
| Eye/Face Protection | : S | Safety glasses with side-shields. | | | |
| Hand protection | : P | Protective gloves. | | | |
| Skin and body protection | : L | Long sleeved clothing. | | | |
| Additional Protective Measures | : S | Safety shoes. | | | |
| General Hygiene Considerations | | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | | | |
| Engineering measures | | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | | | |
| Exposure limit(s) | | | | | |
| Components | Value | Exposure time | Exposure type | List: | |
| Calcium carbonate | 10 mg/m3 | Time Weighted Average | Total dust. | ACGIH | |

| components | value | Exposure time | Exposure type | List. |
|-------------------|----------|-----------------------|----------------------|---------|
| Calcium carbonate | 10 mg/m3 | Time Weighted Average | Total dust. | ACGIH |
| | | (TWA): | | |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average | Total dust. | ACGIH |
| | | (TWA): | | |
| Titanium dioxide | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Form |
|---------------------|
| Appearance |
| Color |
| Odor |
| Melting point/range |
| Boiling Point: |
| Water solubility |
| |

Solid
Pellets, powder
WHITE
Very faint
Not determined
Not applicable
Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not applicable.
Not determined
Not established
Not applicable
Not applicable
Not applicable



MATERIAL SAFETY DATA SHEET

GEON 87787 WHITE 1544

Version Number 1.0 Revision Date 05/25/2002 Page 4 of 6 Print Date 11/4/2011

| | 10. STABILITY AND REACTIVITY |
|----------------------------------|---|
| Stability | : Stable. |
| Hazardous Polymerization | : Will not occur. |
| Conditions to avoid | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing |
| Hazardous decomposition products | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ | |
|------------|-------------------|------------------|---------------------|--|
| 471-34-1 | Calcium carbonate | Irritant | Eyes, Skin. | |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. | |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|----------|-------------------|-----------|-------------|---------|
| 471-34-1 | Calcium carbonate | Oral LD50 | 6,450 mg/kg | rat |

| 12. ECOLOGICAL INFORMATION | |
|----------------------------|--|
| | |

| Persistence and degrad | lability | : | Not readily biodegradable. |
|-----------------------------|----------|---|--|
| Environmental Toxici | ty | : | Adverse ecological impact is not known or expected under normal use. |
| Bioaccumulation Pote | ntial | : | No data available. |
| Additional advice | | : | Not applicable |

13. DISPOSAL CONSIDERATIONS

4/6



MATERIAL SAFETY DATA SHEET

| EON 87787 WHITE 1 | 544 | | |
|---|--|--|--|
| ersion Number 1.0 evision Date 05/25/2002 | Page 5 o Print Date 11/4/20 | | |
| Product | : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | |
| Contaminated packaging | Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | |
| | 14. TRANSPORT INFORMATION | | |
| U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) | : Not regulated for transportation. | | |
| ICAO/IATA | : Not regulated for transportation. | | |
| IMO / IMDG | : Not regulated for transportation. | | |
| | 15. REGULATORY INFORMATION | | |
| US Regulations: | | | |
| OSHA Status | : Classified as hazardous based on components. | | |
| TSCA Status | : All components of this product are listed on the TSCA inventory or are exempt. | | |
| California Proposition 65 | : WARNING! This product contains a chemical known in the State of California to cause cancer. | | |
| Canadian Regulations: | | | |
| WHMIS Classification | : D2B | | |
| WHMIS Ingredient Disc | losure List | | |
| CAS-No. 57583-35-4 13455-36-2 57583-34-3 57-11-4 75-01-4 | | | |
| DSL | : Listed. | | |
| National Inventories: | | | |
| | | | |
| | | | |



MATERIAL SAFETY DATA SHEET

GEON 87787 WHITE 1544

Version Number 1.0 Revision Date 05/25/2002 Page 6 of 6 Print Date 11/4/2011

| Australia AICS | : | Not determined. |
|-------------------|---|-----------------|
| China IECS | : | Not determined. |
| Europe EINECS | : | Not determined. |
| Japan ENCS | : | Not determined. |
| Korea KECI | : | Listed. |
| Philippines PICCS | : | Not determined. |
| | | |

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.