

MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

Version Number 1.0 Revision Date 05/03/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP CP 15024201202 WHITE
Product code	:	VC10000444
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

sion Date 05/03/2002	Print Date 11/4/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

ersion Number 1.0 evision Date 05/03/2002				Print	Page 3 of Date 11/4/201
Handling	: Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation. Processing fu condensates may contain combustible or toxic residue. Periodica clean hoods, ducts, and other surfaces to minimize accumulation these materials.			essing fume Periodically	
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				e absorption
8. 8	XPOSURE	CONTROLS / 1	PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respir	atory protecti	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with	n side-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure	e time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighte (TWA	ed Average	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES	
Form	: Solid				applicable.
Appearance		ts, powder		2	determined
Color Odor	: WHI : Very		Bulk de		established applicable
Melting point/range		letermined	Vapor		applicable
Boiling Point:		applicable	рН		applicable
Water solubility	: Insol		r**		rr
	10. 8	TABILITY AN	D REACTIV	ITY	



MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

Version Number 1.0 Revision Date 05/03/2002		Page 4 of 6 Print Date 11/4/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.
	11.	TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

	12. ECOLOGI	CAL INFORMATION	J
Persistence and degrada	bility : Not readily b	biodegradable.	
Environmental Toxicity	: Adverse ecol	logical impact is not kno	own or expected under normal use
Bioaccumulation Potent	tial : No data avai	lable.	
Additional advice	: Not applicab	le	
	13. DISPOSAI	CONSIDERATIONS	5
Product	possible, rec generator of classificatior	ycling is preferred to di waste material has the r	ct can be recycled. Where sposal or incineration. The responsibility for proper waste posal in accordance with nd local regulations.
Contaminated packagin	has the respo	in accordance with app	e. The generator of waste materia ste classification, transportation licable federal, state/provincial
		ORT INFORMATION	



MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

Version Number 1.0 Revision Date 05/03/2002 Page 5 of 6 Print Date 11/4/2011

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on the TSCA inventory or a exempt.	are
California Proposition 65	: WARNING! This product contains a chemical known in the State of California to cause cancer.	of

SARA Title III Section 302 Extremely Hazardous Substance

Chemical Name	CAS-No.	RQ for component
Acrylonitrile	107-13-1	100 lbs

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
106-99-0
57583-35-4
1333-86-4
1308-38-9
57583-34-3
57-11-4
100-42-5
14807-96-6
107-13-1
25155-30-0
75-01-4

DSL

: Listed.

: Listed.

National Inventories:

Australia AICS



MATERIAL SAFETY DATA SHEET

EXP CP 15024201202 WHITE

Version Number 1.0 Revision Date 05/03/2002 Page 6 of 6 Print Date 11/4/2011

China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.