

### MATERIAL SAFETY DATA SHEET

# **GEON 87555 SMOKE TRANS 9335**

Version Number 1.0 Page 1 of 7
Revision Date 02/28/2003 Print Date 11/10/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (440)-930-1395

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : GEON 87555 SMOKE TRANS 9335

Product code : VC10000499 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components  | CAS-No.    | Weight % |
|---|------------|----------|
| 8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl | 57583-35-4 | 1 - 5    |
| ester   |            |          |
| Stannane,<br>methyltris(2-ethylhexyloxycarbonylmethylth<br>io)-                         | 57583-34-3 | 1 - 5    |

### 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

# POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.



### MATERIAL SAFETY DATA SHEET

# **GEON 87555 SMOKE TRANS 9335**

 Version Number 1.0
 Page 2 of 7

 Revision Date 02/28/2003
 Print Date 11/10/2011

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eves.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: None known.

### 4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

## 5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable
Lower explosion limit : Not applicable
Autoignition temperature : Not applicable.

Suitable extinguishing media : water, dry powder, foam, carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

pressure mode should be worn to prevent initiatation of an borne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13



### MATERIAL SAFETY DATA SHEET

## **GEON 87555 SMOKE TRANS 9335**

 Version Number 1.0
 Page 3 of 7

 Revision Date 02/28/2003
 Print Date 11/10/2011

of this MSDS for proper disposal methods.

### 7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene

Considerations

Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



## MATERIAL SAFETY DATA SHEET

# **GEON 87555 SMOKE TRANS 9335**

Version Number 1.0 Page 4 of 7
Revision Date 02/28/2003 Print Date 11/10/2011

| Components  | Value     | Exposure time                     | Exposure type | List:   |
|---|-----------|-----------------------------------|---------------|---------|
| 8-Oxa-3,5-dithia-4-sta<br>nnatetradecanoic acid,<br>10-ethyl-4,4-dimethyl-<br>7-oxo-, 2-ethylhexyl<br>ester | 0.1 mg/m3 | Time Weighted Average (TWA):      | as Sn         | ACGIH   |
|   | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn         | ACGIH   |
| 8-Oxa-3,5-dithia-4-sta<br>nnatetradecanoic acid,<br>10-ethyl-4,4-dimethyl-<br>7-oxo-, 2-ethylhexyl<br>ester | 0.1 mg/m3 | PEL:                              | as Sn         | OSHA Z1 |
| 8-Oxa-3,5-dithia-4-sta<br>nnatetradecanoic acid,<br>10-ethyl-4,4-dimethyl-<br>7-oxo-, 2-ethylhexyl<br>ester | 0.1 mg/m3 | Time Weighted Average (TWA):      | as Sn         | ACGIH   |
|   | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn         | ACGIH   |
| Stannane,<br>methyltris(2-ethylhexy<br>loxycarbonylmethylthi<br>o)-   | 0.1 mg/m3 | PEL:                              | as Sn         | OSHA Z1 |
| Stannane,<br>methyltris(2-ethylhexy<br>loxycarbonylmethylthi<br>o)-   | 0.1 mg/m3 | Time Weighted Average (TWA):      | as Sn         | ACGIH   |
|   | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn         | ACGIH   |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

: Solid Evaporation rate : Not applicable. Form Appearance : Pellets, powder Specific Gravity : Not determined Color : TRANSPARENT Bulk density : Not established : Very faint Vapor pressure : Not applicable Odor Melting point/range : Not determined Vapor density Not applicable Boiling Point: Not applicable : Not applicable pН

Water solubility : Insoluble

# 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.



### MATERIAL SAFETY DATA SHEET

## **GEON 87555 SMOKE TRANS 9335**

Version Number 1.0 Page 5 of 7 Revision Date 02/28/2003 Print Date 11/10/2011

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen

chloride.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name  | Effect   | Target Organ |
|------------|--|----------|--------------|
| 57583-35-4 | 8-Oxa-3,5-dithia-4-stannat<br>etradecanoic acid,<br>10-ethyl-4,4-dimethyl-7-o<br>xo-, 2-ethylhexyl ester | Irritant | Eyes, Skin.  |
| 57583-34-3 | Stannane,<br>methyltris(2-ethylhexylox<br>ycarbonylmethylthio)-  | Irritant | Eyes, Skin.  |

## LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No.    | Chemical Name   | Route     | Value     | Species |
|------------|---|-----------|-----------|---------|
| 57583-34-3 | Stannane,<br>methyltris(2-ethylhexylox<br>ycarbonylmethylthio)- | Oral LD50 | 920 mg/kg | rat     |

### 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

**Environmental Toxicity** Adverse ecological impact is not known or expected under normal use.

**Bioaccumulation Potential** No data available.

Additional advice Not applicable

## 13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where

possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste



### MATERIAL SAFETY DATA SHEET

# **GEON 87555 SMOKE TRANS 9335**

 Version Number 1.0
 Page 6 of 7

 Revision Date 02/28/2003
 Print Date 11/10/2011

classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

### 14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

## 15. REGULATORY INFORMATION

**US** Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

65

WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a

chemical known to the State of California to cause birth defects or

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable

Canadian Regulations:



### MATERIAL SAFETY DATA SHEET

# **GEON 87555 SMOKE TRANS 9335**

Version Number 1.0 Page 7 of 7
Revision Date 02/28/2003 Print Date 11/10/2011

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 57583-35-4 57583-34-3

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Listed.

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.