

MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

Version Number 1.0 Page 1 of 7
Revision Date 04/17/2002 Print Date 8/21/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (440)-930-1395

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : GEON E1540 WHITE 1292

Product code : VC10000560 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|-----------------------|------------|----------|
| C.I. Pigment Blue 28 | 1345-16-0 | 1 - 5 |
| Calcium carbonate | 1317-65-3 | 1 - 5 |
| Quartz | 14808-60-7 | 1 - 5 |
| Dibutyltin mercaptide | 10584-98-2 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

 Version Number 1.0
 Page 2 of 7

 Revision Date 04/17/2002
 Print Date 8/21/2012

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not applicable.

Suitable extinguishing media : water, dry powder, foam, carbon dioxide (CO2).

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

 Version Number 1.0
 Page 3 of 7

 Revision Date 04/17/2002
 Print Date 8/21/2012

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

 Version Number 1.0
 Page 4 of 7

 Revision Date 04/17/2002
 Print Date 8/21/2012

| Components | Value | Exposure time | Exposure type | List: |
|-----------------------|-----------|---------------------------|-------------------|---------|
| C.I. Pigment Blue 28 | 0.02 | Time Weighted Average | as Co | ACGIH |
| | mg/m3 | (TWA): | | |
| C.I. Pigment Blue 28 | 0.10 | PEL: | Total dust. as Co | OSHA Z1 |
| | mg/m3 | | | |
| Calcium carbonate | 10 mg/m3 | Time Weighted Average | Total dust. | ACGIH |
| | | (TWA): | | |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable dust. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Quartz | 0.05 | Time Weighted Average | Respirable dust. | ACGIH |
| | mg/m3 | (TWA): | | |
| Quartz | 0.1 mg/m3 | PEL: | Respirable dust. | OSHA |
| | 0.3 mg/m3 | PEL: | Total dust. | OSHA |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average | Total dust. | ACGIH |
| | | (TWA): | | |
| Titanium dioxide | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Dibutyltin mercaptide | 0.1 mg/m3 | Time Weighted Average | Total dust. as Sn | ACGIH |
| | | (TWA): | | |
| | 0.2 mg/m3 | Short Term Exposure Limit | Total dust. as Sn | ACGIH |
| | | (STEL): | | |
| Dibutyltin mercaptide | 0.1 mg/m3 | PEL: | Total dust. as Sn | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

: Not applicable. Evaporation rate Form : Solid Not determined : Pellets, powder Specific Gravity Appearance Color WHITE Bulk density Not established : Very faint Vapor pressure Not applicable Odor Vapor density Not applicable Melting point/range : Not determined Boiling Point: : Not applicable pН : Not applicable

Water solubility : Insoluble

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and

hydrogen chloride.



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

 Version Number 1.0
 Page 5 of 7

 Revision Date 04/17/2002
 Print Date 8/21/2012

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-----------------------|------------------|---------------------------------|
| 1345-16-0 | C.I. Pigment Blue 28 | Irritant | Eyes, Skin, Respiratory system. |
| | | sensitizer | Skin. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |
| 14808-60-7 | Quartz | Systemic effects | Eyes, Respiratory system. |
| 10584-98-2 | Dibutyltin mercaptide | Irritant | Eyes, Skin. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|----------------------|------|------|-----|
| 1345-16-0 | C.I. Pigment Blue 28 | no | 2B | no |
| 14808-60-7 | Quartz | no | 1 | 1 |

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

| | 12 | 2. ECOLOGICAL INFORMATION |
|-------------------------------|----|--|
| Persistence and degradability | : | Not readily biodegradable. |
| Environmental Toxicity | : | Adverse ecological impact is not known or expected under normal use. |
| Bioaccumulation Potential | : | No data available. |
| Additional advice | : | Not applicable |
| | _ | |

13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

Version Number 1.0 Page 6 of 7 Print Date 8/21/2012 Revision Date 04/17/2002

Product : Like most thermoplastics the product can be recycled. Where

> possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Recycling is preferred when possible. The generator of waste material Contaminated packaging

> has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk

ground)

ICAO/IATA

: Not regulated for transportation.

: Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

California Proposition

WARNING! This product contains a chemical known in the State of

California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|------------------|-----------|----------|
| COBALT COMPOUNDS | 1345-16-0 | 1.63 |

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. |
|------------|
| 1305-62-0 |
| 68909-79-5 |
| 14808-60-7 |
| 10584-98-2 |



MATERIAL SAFETY DATA SHEET

GEON E1540 WHITE 1292

 Version Number 1.0
 Page 7 of 7

 Revision Date 04/17/2002
 Print Date 8/21/2012

1118-46-3 75-01-4

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.