PolvOne

## MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 1 of 8 Print Date 3/17/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON DURACAP 86103 BEIGE 3483
Product code	:	VC10000696
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	1 - 5
Dibutyltin mercaptide	10584-98-2	1 - 5
Titanium dioxide	13463-67-7	5 - 10

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 2 of 8 Print Date 3/17/2014

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.

PolyOne.

# MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 3 of 8 Print Date 3/17/2014

	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

## MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 4 of 8 Print Date 3/17/2014

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Dibutyltin mercaptide	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	MX OEL
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets, powder
  TAN
  very faint
  Not determined
  not applicable
  insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicableNot determinedNot establishednot applicable
- : not applicable
- : not applicable

### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal

## MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

 

 Version Number 1.5 Revision Date 03/12/2014
 Page 5 of 8 Print Date 3/17/2014

 decomposition, do not overheat.
 decomposition, do not overheat.

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.

 Hazardous decomposition products
 : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

(NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
10584-98-2	Dibutyltin mercaptide	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available



# MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 6 of 8 Print Date 3/17/2014

DISPOSAL CONSIDERATIONS Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. TRANSPORT INFORMATION Not regulated for transportation. Not regulated for transportation. ReGULATORY INFORMATION
possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. <b>. TRANSPORT INFORMATION</b> Not regulated for transportation. Not regulated for transportation. Not regulated for transportation.
material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. <b>TRANSPORT INFORMATION</b> Not regulated for transportation. Not regulated for transportation. Not regulated for transportation.
Not regulated for transportation. Not regulated for transportation. Not regulated for transportation.
Not regulated for transportation. Not regulated for transportation.
Not regulated for transportation.
REGULATORY INFORMATION
Classified as hazardous based on components.
All components of this product are listed on or exempt from the TSCA Inventory.
ances (40 CFR 302)
Not applicable
ly Hazardous Substance
ed under this section, this product is Not Applicable under this regulat
ly N

PolyOne

### MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 7 of 8 Print Date 3/17/2014

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, thi	s product is Not Ap	plicable under this regulation
	CLC M	XX 7 1 1

Chemical Name	CAS-No.	Weight percent
MANGANESE COMPOUNDSMANGANESE	68412-38-4	0.10 - 1.00
COMPOUNDSANTIMONY COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	1.00 - 5.00
COMPOUNDSANTIMONY		
COMPOUNDSCHROMIUM COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM	12737-27-8	0.10 - 1.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)	

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Manganese antimony titanium brown rutile (C.I.	68412-38-4	0.10 - 1.00	
Pigment Yellow 164)			
		0.10 - 1.00	
Rutile, antimony chromium buff	68186-90-3	1.00 - 5.00	
Iron chromite brown spinel	12737-27-8	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	
10584-98-2	

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Not determined	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	

PolyOne

# MATERIAL SAFETY DATA SHEET GEON DURACAP 86103 BEIGE 3483

Version Number 1.5 Revision Date 03/12/2014 Page 8 of 8 Print Date 3/17/2014

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.