

MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028

Version Number 1.2 Revision Date 10/24/2003

Page 1 of 7 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XV 3645 CLEAR 9028
Product code	:	VC10000740
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028

Version Number 1.2 Revision Date 10/24/2003 Page 2 of 7 Print Date 11/12/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable water, foam, carbon dioxide (CO2), dry powdernone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028

and contamination. Keep in a dry, cool pl 8. EXPOSURE CONTROLS / PERSONAL PROTEC Respiratory protection : No personal respiratory protective equipment Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial Considerations : Heat only in areas with appropriate exhau appropriate exhaus ventilation at machine Exposure limit(s) : Solid Exposure time Exposure limit(s) : Solid Evaporation rate Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Odor : Very faint Vapor pressure Melting point/range : Not determined Vapor density	ilation. Proc xic residue. nimize accus void moisture ce.	essing fume Periodically			
and contamination. Keep in a dry, cool pl 8. EXPOSURE CONTROLS / PERSONAL PROTEC Respiratory protection : No personal respiratory protective equipm Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial Considerations : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) : PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapor pressure Melting point/range : Not applicable pH	ce. TION				
Respiratory protection : No personal respiratory protective equipm Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial Considerations : Handle in accordance with good industrial Considerations : Heat only in areas with appropriate exhau appropriate exhaus twentilation at machine Exposure limit(s) : : Heat only in areas with appropriate exhau appropriate exhaus twentilation at machine Exposure limit(s) : : No Solid : Evaporation rate Appearance : Pellets, powder Specific Gravity Color : : Not determined Vapor pressure Melting point/range : Not determined Vapour density		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial Wash hands before breaks and at the end of the exhaust appropriate exhaus appropriate exhaust ventilation at machine Engineering measures : Heat only in areas with appropriate exhaust appropriate exhaust ventilation at machine Exposure limit(s) : Yalue Exposure time Expo Value : Yalue Yalue Yalue Yalue Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : : Yapor pressure Melting point/range : Not applicable PH					
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial General Hygiene : Handle in accordance with good industrial Considerations : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Engineering measures : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) : Image: Solid Structure : PHYSICAL AND CHEMICAL PROPERTIE Form : Solid : Pellets, powder : Specific Gravity Odor : Very faint Vapor pressure Melting point/range : Not applicable pH	nt normally	required.			
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial Considerations : Wash hands before breaks and at the end of Engineering measures : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) : Malue Exposure time Exposure Di(2-ethylhexyl)phthal : 5 mg/m3 PEL: N PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapour density Boiling Point: : Not determined Vapour density					
Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial Wash hands before breaks and at the end of Wash hands before breaks and at the end of Engineering measures Engineering measures : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) Image: Components in the end of the end of the end of Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Image: Components intermed end of the end of t					
Measures					
Considerations Wash hands before breaks and at the end of Engineering measures Engineering measures : Heat only in areas with appropriate exhau appropriate exhaust ventilation at machine Exposure limit(s) <u>Components</u> Value Exposure time Exposure limit(s) <u>Components</u> Value Exposure time Exposure limit(s) <u>Di(2-ethylhexyl)phthal</u> 5 mg/m3 PEL: Value PEL: Value Second PERTIE <u>PHYSICAL AND CHEMICAL PROPERTIE</u> Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapor pressure Melting point/range : Not determined Vapour density Boiling Point: : Not applicable pH					
appropriate exhaust ventilation at machine Exposure limit(s) Exposure time Exposure Di(2-ethylhexyl)phthal 5 mg/m3 PEL: N ate 9. PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapour pressure Melting point/range : Not determined Vapour density Boiling Point: : Not applicable pH		safety practic			
Components Value Exposure time Exposure time Di(2-ethylhexyl)phthal 5 mg/m3 PEL: N ate 9. PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapour pressure Melting point/range : Not determined Vapour density Boiling Point: : Not applicable pH		Provide			
Di(2-ethylhexyl)phthal 5 mg/m3 PEL: N 9. PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapor pressure Melting point/range : Not determined Vapour density Boiling Point: : Not applicable pH					
ate 9. PHYSICAL AND CHEMICAL PROPERTIE Form : Solid Evaporation rate Appearance : Pellets, powder Specific Gravity Color : TRANSPARENT Bulk density Odor : Very faint Vapor pressure Melting point/range : Not determined Vapour density Boiling Point: : Not applicable pH	ure type	List:			
Form: SolidEvaporation rateAppearance: Pellets, powderSpecific GravityColor: TRANSPARENTBulk densityOdor: Very faintVapor pressureMelting point/range: Not determinedVapour densityBoiling Point:: Not applicablepH	npor.	OSHA Z			
Appearance: Pellets, powderSpecific GravityColor: TRANSPARENTBulk densityOdor: Very faintVapor pressureMelting point/range: Not determinedVapour densityBoiling Point:: Not applicablepH					
Odor: Very faintVapor pressureMelting point/range: Not determinedVapour densityBoiling Point:: Not applicablepH		t applicable t determined			
Melting point/range: Not determinedVapour densityBoiling Point:: Not applicablepH		t established			
Boiling Point: : Not applicable pH		t applicable			
		t applicable			
10. STABILITY AND REACTIVITY					
Stability : Stable.					



MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028

Version Number 1.2 Revision Date 10/24/2003 Page 4 of 7 Print Date *11/12/2011*

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system, Skin, digestive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
117-81-7	Di(2-ethylhexyl)phthalate	no	no	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

MATERIAL SAFETY DATA SHEET

XV 3645 CLEAR 9028

Version Number 1.2 Revision Date 10/24/2003 Page 5 of 7 Print Date 11/12/2011

Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)



MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028

Version Number 1.2 Revision Date 10/24/2003

Page 6 of 7 Print Date 11/12/2011

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Di(2-ethylhexyl)ph thalate	117-81-7	30.3461	100 lbs	330 LB

California Proposition 65

: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE (DEHP)	117-81-7	30.34

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Di(2-ethylhexyl)phthalate	117-81-7	30.34	25
Misc00005- Misc Zinc Cpd's	Not Available	0.25	241

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
117-81-7

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined

:

POLYONE CORPORATION MATERIAL SAFETY DATA SHEET XV 3645 CLEAR 9028 Version Number 1.2 Pag Revision Date 10/24/2003 Print Date 11/ Korea KECI : Not determined Philippines PICCS : Listed 16. OTHER INFORMATION	ge 7 of 7 /12/2011
XV 3645 CLEAR 9028 Version Number 1.2 Page 2000 Revision Date 10/24/2003 Print Date 11/2 Korea KECI : Not determined Philippines PICCS : Listed	ge 7 of 7 ′ <u>12/2011</u>
Version Number 1.2 Revision Date 10/24/2003 Print Date 11/ Korea KECI : Not determined Philippines PICCS : Listed	ge 7 of 7 /12/2011
Philippines PICCS : Listed	
Philippines PICCS : Listed	
16. OTHER INFORMATION	
specification. The information relates only to the specific material designated and may not be valid for material when used in combination with any other materials and/or in any particular process or process conditions.	