

MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

Version Number 1.0 Revision Date 04/30/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON EXP 15024205103 WHITE
Product code	:	VC10000760
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	



MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

Version Number 1.0 Revision Date 04/30/2002 Page 2 of 6 Print Date 11/4/2011

Medical Conditions	: None known.		
Aggravated by Exposure:	. None known.		
	4. FIRST AID MEASURES		
Y 1 1 . '			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: Not applicable		
Flammable Limits			
Upper explosion limit	: Not applicable		
Lower explosion limit	: Not applicable		
Autoignition temperature	: Not applicable.		
Suitable extinguishing media	: water, dry powder, foam, carbon dioxide (CO2).		
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures	pressure mode should be worn to prevent inhalation of airborne		
	contaminants.		
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under		
Hazards	fire conditions.		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		



MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

ion Number 1.0 sion Date 04/30/2002			Print	Page 3 c Date 11/4/20	
Handling	oi co cl	ake measures to prevent the bundle in areas with appropriate expondensates may contain combune an hoods, ducts, and other sur-	xhaust ventilation. Produstible or toxic residue.	cessing fume Periodically	
Storage	: K	nese materials. Teep containers dry and tightly and contamination. Keep in a d		e absorption	
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P:	Protective gloves.			
Skin and body protection	: L	: Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations					
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1	

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

: Solid : Pellets, powder : WHITE : Very faint : Not determined : Not applicable : Insoluble

Bulk density Vapor pressure Vapor density pН

Evaporation rate: Not applicable.Specific Gravity: Not determined : Not established : Not applicable : Not applicable : Not applicable



MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

Version Number 1.0 Revision Date 04/30/2002 Page 4 of 6 Print Date 11/4/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	appricable rederat, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

ion Number 1.0 sion Date 04/30/2002	Print Date	age 5 11/4/2
Contaminated packaging	: Recycling is preferred when possible. The generator of waster has the responsibility for proper waste classification, transporta and disposal in accordance with applicable federal, state/provin and local regulations.	ation
	14. TRANSPORT INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on the TSCA inventor exempt.	y or ar
California Proposition 65	: WARNING! This product contains a chemical known in the S California to cause cancer., WARNING! This product contain chemical known in the State of California to cause birth defect other reproductive harm.	s a
Canadian Regulations:		
WHMIS Classification	: D2A	
WHMIS Ingredient Dis	losure List	
CAS-No. 57583-35-4 8007-18-9 7440-43-9 7439-92-1 7439-97-6 57583-34-3 57-11-4 151-21-3 75-01-4		
DSL	: Listed.	
National Inventories:		



MATERIAL SAFETY DATA SHEET

GEON EXP 15024205103 WHITE

Version Number 1.0 Revision Date 04/30/2002 Page 6 of 6 Print Date 11/4/2011

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.