

MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

Version Number 1.0 Revision Date 09/10/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON EXP DB 15020615002 WHITE 1388
Product code	:	VC10001105
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

Version Number 1.0 Revision Date 09/10/2002 Page 2 of 6 Print Date 11/6/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

ion Number 1.0 sion Date 09/10/2002			Print	Page 3 Date 11/6/2
Handling	• т	ake measures to prevent the bu	uild up of electrostatic cl	narge Heat
Tranoning.		nly in areas with appropriate e ondensates may contain combu- lean hoods, ducts, and other su nese materials.	xhaust ventilation. Procustible or toxic residue.	essing fume Periodically
Storage		Leep containers dry and tightly nd contamination. Keep in a d		e absorption
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protecti	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practice
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	4	Total dust.	
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	(TWA): PEL:	Respirable dust.	ACGIH OSHA Z1
	5 mg/m3 15 mg/m3	(TWA): PEL: PEL:		ACGIH OSHA Z1 OSHA Z1
Calcium carbonate	5 mg/m3	(TWA): PEL:	Respirable dust.	ACGIH OSHA Z1
	5 mg/m3 15 mg/m3	(TWA): PEL: PEL: Time Weighted Average	Respirable dust.	ACGIH OSHA Z1 OSHA Z1
Titanium dioxide	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3	(TWA): PEL: PEL: Time Weighted Average (TWA):	Respirable dust. Total dust. Total dust.	ACGIH OSHA Z1 OSHA Z1 ACGIH
Titanium dioxide Titanium dioxide	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Respirable dust. Total dust. Total dust. DPERTIES	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Titanium dioxide Titanium dioxide Form	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Respirable dust. Total dust. Total dust. OPERTIES ration rate : Not	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Titanium dioxide Titanium dioxide Form Appearance	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts, powder Specif	Respirable dust. Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Titanium dioxide Titanium dioxide Form	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO the Evapo the Evapo the Evapo the Evapo the Evapo the Evapo the Bulk d	Respirable dust. Total dust. Total dust. OPERTIES ration rate : Not ic Gravity : Not lensity : Not	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1
Titanium dioxide Titanium dioxide Form Appearance Color Odor	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO d Evapo ets, powder Specifi TE Bulk d r faint Vapor	Respirable dust. Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1
Titanium dioxide Titanium dioxide Form Appearance Color	5 mg/m3 15 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very : Not of	(TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO d Evapo ets, powder Specifi TE Bulk d r faint Vapor	Respirable dust. Total dust. Total dust. OPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not density : Not	ACGIH OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1



MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

Version Number 1.0 Revision Date 09/10/2002 Page 4 of 6 Print Date 11/6/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION	
Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.	
Bioaccumulation Potential	: No data available.	
Additional advice	: Not applicable	
13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
4/6		



MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

sion Date 09/10/2002		Print Date 11/6/2
Contaminated packaging		Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	D2A
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.



MATERIAL SAFETY DATA SHEET

GEON EXP DB 15020615002 WHITE 1388

Version Number 1.0 Revision Date 09/10/2002

Page 6 of 6 Print Date 11/6/2011

Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.