

MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

Version Number 1.0 Revision Date 11/26/2002 Page 1 of 6 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE Emergency telephone	:	Product Stewardship (440)-930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number		or accident).
Product name	:	GEON E7380 BEIGE 3485
Product code	:	VC10001326
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

Version Number 1.0 Revision Date 11/26/2002 Page 2 of 6 Print Date 11/7/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	Mous to fresh sir in asso of assidental inhelation of fumos from
minaration	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable.
Suitable extinguishing media	: water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Hazards	fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as
r ensonal precautions	impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

sion Number 1.0 ision Date 11/26/2002			Print	Page 3 o Date 11/7/20	
Handling	0 C C	Take measures to prevent the buonly in areas with appropriate expondensates may contain combucter hoods, ducts, and other sublese materials.	xhaust ventilation. Procustible or toxic residue.	cessing fume Periodically	
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. F	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	No personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: Protective gloves.				
Skin and body protection	: I	: Long sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	

componento		Linposure time	Lipobare type	2150
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

- : Solid : Pellets, powder : TAN : Very faint : Not determined : Not applicable : Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН
- : Not applicable. Not determined : : Not established : Not applicable : Not applicable : Not applicable



MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

Version Number 1.0 Revision Date 11/26/2002 Page 4 of 6 Print Date 11/7/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

sion Number 1.0 ision Date 11/26/2002			Print	Page 5 c Date 11/7/20
Contaminated packaging	eferred when possible. The generator of waste material ibility for proper waste classification, transportation accordance with applicable federal, state/provincial ations.			
	14. TRANSPOR	RT INFORMATION	I	
U.S. DOT Classification	: Not regulated	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		
IMO / IMDG	: Not regulated	for transportation.		
	15. REGULATO	RY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as h	azardous based on co	omponents.	
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardou	s Substances (40 CFF	R 302)		
Not applicable				
California Proposition 65	: WARNING! California to c	This product contains ause cancer.	a chemical known t	o the State of
SARA Title III Section 313 T	oxic Chemicals:			
Chemical Nam		CAS-No.	Weight %	
	E COMPOUNDS	68412-38-4	00.14	
ANTIMONY COMPOUNDS CHROMIUM III COMPOUNDS ANTIMONY COMPOUNDS		68186-90-3	00.74	_
CHROMIUM III COMPOUNDS		12737-27-8	00.15	
Canadian Regulations:				
WHMIS Classification	n : D2A			
DSL			uct are listed on the	



MATERIAL SAFETY DATA SHEET

GEON E7380 BEIGE 3485

Version Number 1.0 Revision Date 11/26/2002 Page 6 of 6 Print Date 11/7/2011

Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.