

MATERIAL SAFETY DATA SHEET

0953 GREY 8004D

Version Number 1.0 Revision Date 12/15/2002 Page 1 of 6 Print Date 11/7/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	0953 GREY 8004D
Product code	:	VC10001390
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

0953 GREY 8004D

sion Date 12/15/2002	Page 2 Print Date 11/7/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET

0953 GREY 8004D

	7.	HANDLING A	ND STORAC	Æ		
Handling		: Take measures to prevent the build up of electrostatic charge. only in areas with appropriate exhaust ventilation. Processing condensates may contain combustible or toxic residue. Periodi clean hoods, ducts, and other surfaces to minimize accumulation these materials.				
Storage		: Keep containers dry and tightly closed to avoid moisture absorpt and contamination. Keep in a dry, cool place.				
8. H	EXPOSURE	CONTROLS / I	PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respir	atory protecti	ve equipment normally	y required.	
Eye/Face Protection	: S	afety glasses with	n side-shields.			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved cloth	ning.			
Additional Protective Measures	: S	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure	e time	Exposure type	List:	
Titanium dioxide	10 mg/m3	Time Weighte (TWA	-	Dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL	:	Total dust.	OSHA Z	
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES		
Form	: Solic	1			ot applicable.	
Appearance				•	ot determined	
Color	: GRE		Bulk d		ot established	
Odor		faint			ot applicable	
Melting point/range		determined	-		ot applicable	
Boiling Point: Water solubility	: Insol	applicable luble	рН	: IN	ot applicable	
	10. 5	STABILITY AN	D REACTIV	ITY		

MATERIAL SAFETY DATA SHEET

0953 GREY 8004D



Version Number 1.0 Revision Date 12/15/2002		Page 4 of 6 Print Date 11/7/2011
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability: Not readily biodegradable.Environmental Toxicity: Adverse ecological impact is not known or expected under normal use.Bioaccumulation Potential: No data available.

Additional advice : Not applicable



MATERIAL SAFETY DATA SHEET

0953 GREY 8004D

	13. DISP	OSAL CONSIDI	ERATIONS		
Product	possib genera classif	le, recycling is pro tor of waste mater ication, transporta	ts the product can be r eferred to disposal or in rial has the responsibilition and disposal in ac provincial and local re	ncineration. The ity for proper waste cordance with	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRA	NSPORT INFO	RMATION		
U.S. DOT Classification	: Not re	gulated for transp	ortation.		
ICAO/IATA	: Not re	gulated for transp	ortation.		
IMO / IMDG	: Not re	gulated for transp	ortation.		
	15. REGU	JLATORY INFO	ORMATION		
US Regulations:					
OSHA Status	: Classif	fied as hazardous	based on components.		
TSCA Status	TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardo	us Substances	(40 CFR 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product	
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	3.5307	100 lbs	2,832 LB	
California Propositio		UNCL This mod	unt contains a chamina	l known to the State of	

MATERIAL SAFETY DATA SHEET



0953 GREY 8004D

Version Number 1.0		Page 6 of
Revision Date 12/15/2002		Print Date 11/7/201
Canadian Regulations:		
WHMIS Classification	1 :	D2B
WHMIS Ingredient Dis	sclosu	ure List
CAS-No. 85-68-7		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.