

MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

Version Number 1.0 Revision Date 04/21/2003 Page 1 of 7 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON X155-058-015-01
Product code	:	VC10001763
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10 - 30
phenylmethylester		
Calcium carbonate	1317-65-3	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

Version Number 1.0 Revision Date 04/21/2003 Page 2 of 7 Print Date 11/11/2011

Medical Conditions : None known. Aggravated by Exposure:				
		4. FIRST AID MEASURES		
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
		5. FIRE-FIGHTING MEASURES		
Flash point	:	Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	::	Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).		
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.		
Unusual Fire/Explosion Hazards	:	May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.		
	6. A	CCIDENTAL RELEASE MEASURES		
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

ion Number 1.0 sion Date 04/21/2003			Print I	Page 3 Date 11/11/2	
	7.	HANDLING AND STOP	RAGE		
Handling	 Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. 				
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. E	XPOSURE	CONTROLS / PERSON	AL PROTECTION		
Respiratory protection	: N	lo personal respiratory prot	ective equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shie	elds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with g Vash hands before breaks a	ood industrial hygiene and nd at the end of workday.	safety practice	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	10 mg/m3	Time Weighted Averag (TWA):		ACGIH	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL F	PROPERTIES		
Form Appearance Color Odor	: NO I : Very	ets, powder Spe PIGMENT Bu faint Va	ecific Gravity : No lk density : No por pressure : No	ot applicable. ot determined ot established ot applicable	
Melting point/range Boiling Point: Water solubility		applicable pH		ot applicable ot applicable	



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

Version Number 1.0 Revision Date 04/21/2003 Page 4 of 7 Print Date 11/11/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Adverse ecological impact is not known or expected under normal use.



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

ion Number 1.0 sion Date 04/21/2003			Pri	Page 5 Int Date 11/11/2
Bioaccumulation Potential	: No data avai	lable.		
Additional advice	: Not applicab	ble		
	13. DISPOSAI	CONSIDERATION	IS	
Product	possible, rec generator of classification	ermoplastics the prod ycling is preferred to o waste material has the n, transportation and d ederal, state/provincial	lisposal or incine responsibility fo isposal in accord	ration. The or proper waste ance with
Contaminated packaging : Recycling is preferred when possible. The generator of waste mathematical has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provinci and local regulations.				
	14. TRANSPO	ORT INFORMATIO	N	
U.S. DOT Classification	: Not regulate	d for transportation.		
ICAO/IATA	AO/IATA : Not regulated for transportation.			
IMO / IMDG	: Not regulate	d for transportation.		
	15. REGULAT	ORY INFORMATIC	DN	
US Regulations:				
OSHA Status	: Classified as	hazardous based on c	omponents.	
TSCA Status	: All compon Inventory.	ents of this product are	listed on or exen	npt from the TSC
US. EPA CERCLA Hazardou	s Substances (40 CI	FR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Proc
1,2-Benzenedicarboxyl acid, butyl phenylmethylester	ic 85-68-7	12.4553	100 lbs	803 LB
California Proposition 65	California to	This product contain cause cancer., WARN own to the State of Ca	NING! This prod	uct contains a



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

Version Number 1.0 Revis

rsion Number 1.0 vision Date 04/21/2003		Print Date	Page 6 of 7 11/11/2011
	other reproductive harm.		
SARA Title III Section 302 Extrem	nely Hazardous Substance		
Not applicable			
SARA Title III Section 313 Toxic	Chemicals:		
Not applicable			
Canadian Regulations:			
WHMIS Classification :	D2B		
WHMIS Ingredient Disclos	ure List		
CAS-No. 85-68-7 513-77-9			
DSL :	All components of this product are on the Can Substances List (DSL) or are exempt.	adian Domesti	ic
National Inventories:			
Australia AICS :	Not determined.		
China IECS :	Not determined.		
Europe EINECS :	Not determined.		
Japan ENCS :	Not determined.		
Korea KECI :	Not determined.		
Philippines PICCS :	Not determined.		
	16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

GEON X155-058-015-01

Version Number 1.0 Revision Date 04/21/2003 Page 7 of 7 Print Date 11/11/2011