MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

Version Number 1.0 Revision Date 08/08/2003 Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MSDS X150-242-112-03 BURGUNDY
Product code	:	VC10002197
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	471-34-1	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

Version Number 1.0 Revision Date 08/08/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Hazards	fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

sion Number 1.0 ision Date 08/08/2003				I	Print D	Page 3 ate 11/11/2
Handling		nly in areas with ondensates may c	appropriate e contain combu	aild up of electros xhaust ventilation astible or toxic res rfaces to minimiz	. Proce sidue. 1	essing fume Periodically
Storage		eep containers dana dana dana dana dana dana dana dan		closed to avoid m ry, cool place.	noisture	e absorption
8. E	XPOSURE	CONTROLS / I	PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respir	atory protecti	ve equipment nor	mally r	required.
Eye/Face Protection	: S	afety glasses witl	h side-shields			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved cloth	ning.			
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations				industrial hygien at the end of work		afety practice
Engineering measures		leat only in areas		iate exhaust venti at machinery.	lation.	Provide
Exposure limit(s)						
Components	Value	Exposure	e time	Exposure ty	pe	List:
Calcium carbonate	5 mg/m3	PEL		Respirable frac		OSHA Z1
	15 mg/m3	PEL		Total dust		OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighte (TWA				ACGIH
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES		
Form Appearance	: Solic : Pelle	l ts, powder		ration rate ic Gravity		applicable. determined
Color	: PUR		Bulk d		: Not	established
Odor	: Very	faint		pressure		applicable
Melting point/range		determined	-	density		applicable
Boiling Point: Water solubility	: Not : : Insol	applicable uble	рН		: Not	applicable
	10. 8	STABILITY AN	D REACTIV	ITY		



MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

Version Number 1.0 Revision Date 08/08/2003 Page 4 of 6 Print Date 11/11/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

	1	3. DISPOSAL CONSIDERATIONS	
Additional advice	:	Not applicable	
Bioaccumulation Potential	:	No data available.	
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.	
Persistence and degradability	:	Not readily biodegradable.	

Product

: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with



MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

sion Number 1.0 ision Date 08/08/2003		Page 5 0 Print Date 11/11/20
		applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15.	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Subs	tances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	reme	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	xic C	hemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se In	ventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.



MATERIAL SAFETY DATA SHEET MSDS X150-242-112-03 BURGUNDY

Version Number 1.0 Revision Date 08/08/2003 Page 6 of 6 Print Date *11/11/2011*

National Inventories: Australia AICS : Not determined.	
Australia AICS . Not determined	
Australia (Alesson) - Alesson (Alesson) - Ales	
China IECS : Listed.	
Europe EINECS : Not determined.	
Japan ENCS : Not determined.	
Korea KECI : Not determined.	
Philippines PICCS : Listed.	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.