

MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003

Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON EXP DB 15020606404 WHITE 1042
Product code	:	VC10002199
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions.
	. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003

Page 3 of 6 Print Date 11/11/2011

	7.	HANDLING AND STOR	AGE	
Handling		ake measures to prevent the nly in areas with appropriate ondensates may contain com lean hoods, ducts, and other nese materials.	e exhaust ventilation. Proc bustible or toxic residue.	essing fume Periodically
Storage		eep containers dry and tight nd contamination. Keep in a		e absorption
8. E	XPOSURE	CONTROLS / PERSONA	L PROTECTION	
Respiratory protection	: N	o personal respiratory prote	ctive equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shiel	ds.	
Hand protection	: P	: Protective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL PI	ROPERTIES	
-	a 11			
Form	: Solic			applicable.
Appearance			2	t determined
Color Odor	: WHI		5	t established
Odor Melting point/range				t applicable t applicable
Boiling Point:		applicable pH		t applicable
Water solubility	: Insol		. 1901	applicable



MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003 Page 4 of 6 Print Date 11/11/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

POLYONE CORPORATION	N
I ULI UNE CUNI UNATIOI	



MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003 Page 5 of 6 Print Date 11/11/2011

Contaminated packagin	g :	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	1	4. TRANSPORT INFORMATION		
U.S. DOT Classification ICAO/IATA IMO / IMDG	n : :	Not regulated for transportation. Not regulated for transportation. Not regulated for transportation.		
	15	5. REGULATORY INFORMATION		
	1.	. RECLATORT INFORMATION		
US Regulations:				
OSHA Status	:	Classified as hazardous based on components.		
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Haz	zardous Sub	stances (40 CFR 302)		
Not applica	ıble			
California Propo 65	osition :	WARNING! This product contains a chemical known to the State of California to cause cancer.		
SARA Title III Section	SARA Title III Section 302 Extremely Hazardous Substance			
Not applicable				
SARA Title III Section	SARA Title III Section 313 Toxic Chemicals:			
Not applicable Canadian Regulations:				
National Polluta	nt Release In	nventory (NPRI)		
Not applicable				
WHMIS Classif	ication :	D2B		
DSL	:	All components of this product are on the Canadian Domestic		

PolyOne

MATERIAL SAFETY DATA SHEET GEON EXP DB 15020606404 WHITE 1042

Version Number 1.0 Revision Date 08/12/2003 Page 6 of 6 Print Date *11/11/2011*

		Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.