

MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004

Page 1 of 6 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MSDS X150-206-120-100
Product code	:	VC10002645
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		



MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004 Page 2 of 6 Print Date 11/13/2011

Medical Conditions Aggravated by Exposure:	:	None known.			
		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
		5. FIRE-FIGHTING MEASURES			
Flash point	:	Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:::::::::::::::::::::::::::::::::::::::	Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides			
Hazalus		of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. A	CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			



MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004 Page 3 of 6 Print Date 11/13/2011

	7.	HANDLING A	ND STORAG	řE		
Handling		Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage	: Keep containers dry and tightly closed to avoid moisture absorptio and contamination. Keep in a dry, cool place.					e absorption
8.]	EXPOSURE	CONTROLS /]	PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respir	atory protectiv	ve equipment norr	nally 1	required.
Eye/Face Protection	: S	: Safety glasses with side-shields.				
Hand protection	: P	: Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.				
Additional Protective Measures	: S	: Safety shoes.				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		eat only in areas		ate exhaust ventila at machinery.	ation.	Provide
Exposure limit(s)						
Components	Value	Exposur	e time	Exposure typ	e e	List:
Titanium dioxide	10 mg/m3	Time Weighte (TW)	-			ACGIH
	15 mg/m3	PEI		Total dust.		OSHA Z1
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES		
Form	: Solid	1	Evapor	ration rate :	Not	applicable
Appearance		ts, powder		c Gravity: :		determined
Color		PIGMENT	Bulk de			established
Odor	•	faint		pressure :		applicable
Melting point/range		letermined	-	r density :		applicable
Boiling Point:		applicable	pН	:	Not	applicable
Water solubility	: Insol	uble				
	10. 5	STABILITY AN	D REACTIV	ITY		

3/6



MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004 Page 4 of 6 Print Date *11/13/2011*

Stability Hazardous Polymerization	:	Stable. Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

 Not readily bio Adverse ecolo No data availa Not applicable 	ogical impact is not kno	Respiratory system.			
 Not readily bio Adverse ecolo No data availa Not applicable 	odegradable. ogical impact is not kno ıble				
 Not readily bio Adverse ecolo No data availa Not applicable 	odegradable. ogical impact is not kno ıble				
Adverse ecoloNo data availaNot applicable	ogical impact is not kno	own or expected under normal use			
: No data availa : Not applicable	able	own or expected under normal use			
: Not applicable					
	2				
13. DISPOSAL		: Not applicable			
	CONSIDERATIONS				
possible recyc generator of w classification,	ling is preferred to dis vaste material has the r transportation and disp	esponsibility for proper waste posal in accordance with			
has the respon	sibility for proper was	te classification, transportation			
	possible recyc generator of w classification, applicable fed : Recycling is p has the respon	 Like most thermoplastic plastics the possible recycling is preferred to dis generator of waste material has the r classification, transportation and dispapplicable federal, state/provincial a Recycling is preferred when possible has the responsibility for proper was and disposal in accordance with approximation of the state of t			



MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004 Page 5 of 6 Print Date 11/13/2011

	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Not regulated for transportation.
IMO / IMDG (maritime)	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ex	treme	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 To	oxic C	Shemicals:
Not applicable		
Canadian Regulations:		
National Pollutant Relea	ase In	aventory (NPRI)
Not applicable		
WHMIS Classification	:	D2B
		All components of this product are on the Canadian Domestic



MATERIAL SAFETY DATA SHEET **MSDS X150-206-120-100**

Version Number 1.0 Revision Date 02/10/2004

Page 6 of 6 Print Date *11/13/2011*

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.