MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

Version Number 1.0 Revision Date 05/18/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone:Emergency telephone:number | Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--------------------------------------|---|
| Product name : | MSDS X155-021-067-04 BLACK |
| Product code : | VC10002874 |
| Chemical Name : | Mixture |
| CAS-No. : | Mixture |
| Product Use : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|-----------|----------|
| Barium stearate | 6865-35-6 | 1 - 5 |
| Calcium carbonate | 1317-65-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|----------------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| | |

PolyOne.

MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

Version Number 1.0 Revision Date 05/18/2004 Page 2 of 6 Print Date 11/14/2011

| Chronic exposure | : Refer to Section 11 for Toxicological Information. | |
|--|--|------|
| Medical Conditions Aggravated by Exposure: | : None known. | |
| | 4. FIRST AID MEASURES | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice. | s of |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. | 5 |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention. | r at |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists s medical attention. | seek |
| | 5. FIRE-FIGHTING MEASURES | |
| Flash point | : Not applicable | |
| Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positir pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), ox of nitrogen (NOx), other hazardous materials, and smoke are all possible. | ıder |
| | ACCIDENTAL RELEASE MEASURES | |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. | |
| Environmental precautions | : Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil. | not |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods. | |

PolyOne.

MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

Version Number 1.0 Revision Date 05/18/2004

| | Page 3 of 6 |
|------------|-------------|
| Print Date | 11/14/2011 |
| | |

| | 1. | HANDLING AND STO | KAGE | |
|------------------------------------|-----------|--|---|------------------------------|
| Handling | | nly in areas with appropriation of the second s | ne build up of electrostatic c tte exhaust ventilation. Pro- ombustible or toxic residue. er surfaces to minimize accu | cessing fume Periodically |
| Storage | | eep containers dry and tig nd contamination. Keep in | htly closed to avoid moistur a dry, cool place. | e absorption |
| 8. I | EXPOSURE | CONTROLS / PERSON | AL PROTECTION | |
| Respiratory protection | : N | o personal respiratory pro | tective equipment normally | required. |
| Eye/Face Protection | : S | afety glasses with side-shi | elds. | |
| Hand protection | : P | rotective gloves. | | |
| Skin and body protection | : L | ong sleeved clothing. | | |
| Additional Protective Measures | : S | afety shoes. | | |
| General Hygiene Considerations | | andle in accordance with g ash hands before breaks a | good industrial hygiene and and at the end of workday. | safety practice |
| Engineering measures | | eat only in areas with appropriate exhaust ventilat | ropriate exhaust ventilation. ion at machinery. | Provide |
| Exposure limit(s) | | | | |
| Components | Value | Exposure time | Exposure type | List: |
| Barium stearate | 10 mg/m3 | Time Weighted Averag (TWA): | | ACGIH |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 9. PHYSIC | CAL AND CHEMICAL | PROPERTIES | |
| Form | : Solid | L Fu | aporation rate : No | t applicable |
| Appearance | | | | t determined |
| Color | : BLA | | 2 | t established |
| Odor | | | | t applicable |
| Melting point/range | | | | t applicable |
| יי היי ⁻ | : Not a | applicable pH | | t applicable |
| Boiling Point: Water solubility | : Insol | | | ** |

PolvOne

MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

Version Number 1.0 Revision Date 05/18/2004 Page 4 of 6 Print Date 11/14/2011

| | 10. STABILITY AND REACTIVITY |
|----------------------------------|---|
| Stability | : Stable. |
| Hazardous Polymerization | : Will not occur. |
| Conditions to avoid | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-----------|-------------------|------------------|---------------------------------|
| 6865-35-6 | Barium stearate | Irritant | Eyes, Skin, Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-----------------|-----------|-------------|---------|
| 6865-35-6 | Barium stearate | Oral LD50 | 2,506 mg/kg | rat |

12. ECOLOGICAL INFORMATION

| Persistence and degradability | : | Not readily biodegradable. |
|----------------------------------|---|--|
| Environmental Toxicity | : | Adverse ecological impact is not known or expected under normal use. |
| Bioaccumulation Potential | : | No data available |
| Additional advice | : | Not applicable |
| | | |

13. DISPOSAL CONSIDERATIONS

PolyOne.

MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

| on Date 05/18/2004 Page 5 Print Date 11/14/2 | | | |
|--|-------------------------------------|--|---|
| | | | |
| Product | possible recycling is pro | eferred to disposa erial has the respo ation and disposa | onsibility for proper waste l in accordance with |
| Contaminated packaging | has the responsibility for | or proper waste cl | he generator of waste material assification, transportation ble federal, state/provincial |
| | 14. TRANSPORT INFO | RMATION | |
| | | | |
| U.S. DOT Classification | : Not regulated for transp | | |
| ICAO/IATA (air) | : Not regulated for transp | portation. | |
| IMO / IMDG (maritime) | : Not regulated for transp | portation. | |
| | 15. REGULATORY INF | ORMATION | |
| US Regulations: | | | |
| OSHA Status | : Classified as hazardous | based on compo | nents. |
| TSCA Status | : All components of this Inventory. | product are listed | on or exempt from the TSCA |
| US. EPA CERCLA Hazardou | s Substances (40 CFR 302) | | |
| Not applicable | | | |
| California Propositior | : WARNING! This proc | luct contains a ch | emical known to the State of |
| 65 | California to cause cand | | ennear known to the State of |
| SARA Title III Section 302 E | xtremely Hazardous Substance | 2 | |
| Not applicable | | | |
| SARA Title III Section 313 T | oxic Chemicals: | | |
| Chemical Name | | CAS-No. | Weight % |
| | NDS [EXCEPT BASO4] | 6865-35-6 | 0.81 |
| Canadian Regulations: | | | |
| | | | |

PolyOne

MATERIAL SAFETY DATA SHEET MSDS X155-021-067-04 BLACK

Version Number 1.0 Revision Date 05/18/2004 Page 6 of 6 Print Date 11/14/2011

| Chemical Name | | | CAS-No. | Weight % | NPRI ID# |
|----------------------|---|--|-----------|----------|----------|
| Zinc stearate | | | 557-05-1 | 0.10 | 241 |
| Zinc dilaurate | | | 2452-01-9 | 0.12 | 241 |
| WHMIS Classification | : | Not controlled. | | | |
| DSL | : | All components of Substances List (DS | | | Domestic |
| onal Inventories: | | | | | |
| Australia AICS | : | Listed | | | |
| China IECS | : | Listed | | | |
| Europe EINECS | : | Not determined | | | |
| Japan ENCS | : | Not determined | | | |
| Korea KECI | : | Not determined | | | |
| Philippines PICCS | • | Listed | | | |

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.