MATERIAL SAFETY DATA SHEET **MSDS X155-021-076-01 CLEAR**

Version Number 1.2 Revision Date 03/12/2014 Page 1 of 6 Print Date 3/18/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone mumber	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MSDS X155-021-076-01 CLEAR
Product code	:	VC10003001
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET MSDS X155-021-076-01 CLEAR

Version Number 1.2 Revision Date 03/12/2014 Page 2 of 6 Print Date 3/18/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET MSDS X155-021-076-01 CLEAR

rsion Number 1.2 vision Date 03/12/2014		Page 3 of Print Date 3/18/201
Storage		only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	•	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		
There are no known hazardo	us com	ponents above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid : pellets, powder : NO PIGMENT : very faint : Not determined : not applicable : insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН
- Not applicable : Not determined : : Not established : not applicable : not applicable : not applicable

PolyOne

MATERIAL SAFETY DATA SHEET MSDS X155-021-076-01 CLEAR

Version Number 1.2 Revision Date 03/12/2014 Page 4 of 6 Print Date 3/18/2014

10. STABILITY AND REACTIVITY		
Stability	: The product is stable if stored and handled as prescribed.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.	
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °I (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. 	
	11. TOXICOLOGICAL INFORMATION	
There are no known hazardous		
There are no known hazardous	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product.	
There are no known hazardous	11. TOXICOLOGICAL INFORMATION	
There are no known hazardous Persistence and degradability	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product.	
	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product. 12. ECOLOGICAL INFORMATION	
Persistence and degradability	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product. 12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal	
Persistence and degradability Environmental Toxicity	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product. 12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal use.	
Persistence and degradability Environmental Toxicity Bioaccumulation Potential	11. TOXICOLOGICAL INFORMATION components above regulatory thresholds in this product. 12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal use. : no data available	

14. TRANSPORT INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET MSDS X155-021-076-01 CLEAR

Version Number 1.2 Revision Date 03/12/2014 Page 5 of 6 Print Date 3/18/2014

U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO/IMDG (maritime)	:	Not regulated for transportation.
	15	S. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Subs	stances (40 CFR 302)
not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Ea	ktrem	ely Hazardous Substance
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic C	Chemicals:
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Rele	ase Ir	nventory (NPRI)
not applicable		
	ı :	Not controlled.
WHMIS Classification		
WHMIS Classification	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
	:	

PolyOne

MATERIAL SAFETY DATA SHEET MSDS X155-021-076-01 CLEAR

Version Number 1.2 Revision Date 03/12/2014 Page 6 of 6 Print Date 3/18/2014

China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.