

MATERIAL SAFETY DATA SHEET **GEON L7417 WHITE 1255**

Version Number 1.0 Revision Date 07/29/2004

Page 1 of 6 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	:	GEON L7417 WHITE 1255
Product code :	:	VC10003018
Chemical Name :	:	Mixture
CAS-No.	:	Mixture
Product Use :	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	471-34-1	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	e: : Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET GEON L7417 WHITE 1255

Version Number 1.0 Revision Date 07/29/2004 Page 2 of 6 Print Date 11/15/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
sower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



MATERIAL SAFETY DATA SHEET GEON L7417 WHITE 1255

rsion Number 1.0 vision Date 07/29/2004			Print Da	Page 3 of e ate 11/15/201
Storage	:	condensates may contain combu clean hoods, ducts, and other su these materials. Keep containers dry and tightly and contamination. Keep in a d	rfaces to minimize accun closed to avoid moisture	nulation of
8. EXI	POSURI	E CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	:	No personal respiratory protecti	ve equipment normally r	equired.
Eye/Face Protection	:	Safety glasses with side-shields.		
Hand protection	:	Protective gloves.		
Skin and body protection	:	Long sleeved clothing.		
Additional Protective Measures	: :	Safety shoes.		
General Hygiene Considerations		Handle in accordance with good Wash hands before breaks and a may contain residual vinyl chlor 75-01-4) below 8.5 ppm (0.0008 working conditions with adequa will be exceeded for residual VC necessary precautions (e.g. mech ventilation, air-monitoring, resp airborne levels of any vapors inc released during heating or proce	t the end of workday. The ride monomer (VCM) (C 35%). It is unlikely, under te ventilation, that the ex CM. However, the user shanical ventilation, local iratory protection, etc.) to cluding VCM or dusts that	his product AS number or normal posure limits nould take the exhaust o ensure at may be
Engineering measures		Heat only in areas with appropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	L ist.

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid: Pellets, powder

Evaporation rate Specific Gravity: Not applicableNot determined

3/6



MATERIAL SAFETY DATA SHEET **GEON L7417 WHITE 1255**

Version Number 1.0 Revision Date 07/29/2004

Page 4 of 6 Print Date 11/15/2011

Color Odor Melting point/range Boiling Point: Water solubility	: Ve : Ne : Ne	HITE ery faint ot determined ot applicable soluble	Bulk density Vapor pressure Vapour density pH	:::::::::::::::::::::::::::::::::::::::	Not established Not applicable Not applicable Not applicable	
	1(). STABILITY AND RE	EACTIVITY			
Stability	:	Stable.				
Hazardous Polymerization	:	Will not occur.				
Conditions to avoid	:	Keep away from oxidiz decomposition, do not o		ame.	To avoid thermal	
Incompatible Materials	:	Incompatible with stron with acetal homopolym				
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), other hazardous Prolonged heating (app (200 °C) or short term h decomposition and evol chloride.	materials, and smoke roximately 30 minutes eating at 482 °F (250	are a s or n °C) n	all possible. nore) above 392 °F nay result in product	
11. TOXICOLOGICAL INFORMATION						

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	No data available

PolyOne.

MATERIAL SAFETY DATA SHEET GEON L7417 WHITE 1255

Version Number 1.0 Revision Date 07/29/2004 Page 5 of 6 Print Date 11/15/2011

Additional advice	:	Not applicable
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Not regulated for transportation.
IMO / IMDG (maritime)	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	ub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Extra	em	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Toxi	c C	Chemicals:

PolvOne

MATERIAL SAFETY DATA SHEET **GEON L7417 WHITE 1255**

Version Number 1.0 Revision Date 07/29/2004 Page 6 of 6 Print Date 11/15/2011

Not applicable Canadian Regulations:				
National Pollutant Release	se Iı	nventory (NPRI)		
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.