MATERIAL SAFETY DATA SHEET EXP CP X15502108501 NATURAL

Version Number 1.4 Revision Date 02/15/2007 Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	EXP CP X15502108501 NATURAL
Product code :	VC10003170
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30
Di(2-ethylhexyl)phthalate	117-81-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed.
Eyes Skin	 Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Skii	. Experience shows no unusual dermatitis nazare nom routile nandning.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET EXP CP X15502108501 NATURAL

Version Number 1.4 Revision Date 02/15/2007 Page 2 of 7 Print Date 11/26/2011

	4. FIRST AID MEASURES			
Inhalation	 Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. 			
Ingestion				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under 			
Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume			

PolyOne.

MATERIAL SAFETY DATA SHEET **EXP CP X15502108501 NATURAL**

sion Number 1.4 vision Date 02/15/2007	Page Print Date 11/26
Storage	 condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields.
Hand protection	: Protective gloves.
Skin and body protection	: Long sleeved clothing.
Additional Protective Measures	: Safety shoes.
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure lime will be exceeded for residual VCM. However, the user should take to necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

MATERIAL SAFETY DATA SHEET **EXP CP X15502108501 NATURAL**

Version Number 1.4 Revision Date 02/15/2007

Page 4 of 7 Print Date 11/26/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Di(2-ethylhexyl)phthal ate	5 mg/m3	PEL:	Vapor.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):		MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Solid
Pellets, powder
NO PIGMENT
Very faint
Not determined
Not applicable
Insoluble

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- : Not applicable
- Not determinedNot established
- : Not established : Not applicable
- : Not applicable
- : Not applicable

lule

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

MATERIAL SAFETY DATA SHEET EXP CP X15502108501 NATURAL

Version Number 1.4 Revision Date 02/15/2007

Page 5 of 7 Print Date 11/26/2011

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system (CNS), Skin, digestive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

12. ECOLOGICAL INFORMATION

	13. DISPOSAL CONSIDERATIONS
Additional advice	: Not applicable
Bioaccumulation Potential	: No data available
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Persistence and degradability	: Not readily biodegradable.

: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The

PolyOne.

MATERIAL SAFETY DATA SHEET EXP CP X15502108501 NATURAL

ersion Number 1.4 evision Date 02/15/2007			Print	Page 6 of Date 11/26/201	
	classific	ation, transportation ar	s the responsibility for p nd disposal in accordance icial and local regulation	ce with	
Contaminated packaging	has the r and disp	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRAN	SPORT INFORMAT	TION		
U.S. DOT Classification	: Not regu	ilated for transportation	n.		
ICAO/IATA (air)	: Not regu	ilated for transportation	n.		
IMO / IMDG (maritime)	: Not regu	ilated for transportation	n.		
	15. REGUI	LATORY INFORMA	TION		
US Regulations:					
OSHA Status	: Classifie	ed as hazardous based	on components.		
TSCA Status	: All com Inventor		t are listed on or exempt	t from the TSCA	
US. EPA CERCLA Hazard	ous Substances (4	0 CFR 302)			
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product]	
Di(2-ethylhexyl)ph thalate	117-81-7	100 lbs	409 LB		
California Propositi 65	Californ chemica	ia to cause cancer., W	ntains a chemical known ARNING! This produc f California to cause bir	t contains a	
SARA Title III Section 302	Extremely Hazar	dous Substance			
Unless specific chemicals a	re identified under	r this section, this prod	luct is Not Applicable u	nder this regulation	
SARA Title III Section 313	Toxic Chemicals	:			

PolyOne

MATERIAL SAFETY DATA SHEET EXP CP X15502108501 NATURAL

Version Number 1.4 Revision Date 02/15/2007 Page 7 of 7 Print Date 11/26/2011

Chemical Name		CAS-		pplicable under this 1 Weight %		
DI(2-ETHYLHEXYL)PHTHALATE (DEHP)		117-81	117-81-7		10.00 - 30.00	
anadian Regulations:						
National Pollutant Relea	ase Inventory (NPRI)					
Chemical Name Di(2-ethylhexyl)phthalate		CAS-No. 117-81-7	Weight 10.00 -		NPRI ID#	
		117 01 7	10100	20100		
WHMIS Ingredient Dise CAS-No. 117-81-7						
DSL		ts of this product a t (DSL) or are exe		anadian	Domestic	
				anadian	Domestic	
DSL National Inventories: Australia AICS		t (DSL) or are exe		anadian	Domestic	
National Inventories:	Substances Lis	t (DSL) or are exe		anadian	Domestic	
National Inventories: Australia AICS	Substances Lis	t (DSL) or are exe 1		anadian	Domestic	
National Inventories: Australia AICS China IECS	Substances Lis : Not determined : Not determined	t (DSL) or are exe 1 1		anadian	Domestic	
lational Inventories: Australia AICS China IECS Europe EINECS	Substances Lis Not determined Not determined Not determined	t (DSL) or are exe 1 1 1		anadian	Domestic	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.