MATERIAL SAFETY DATA SHEET **BLKPWDMB (5.00% Black 9887)**

Version Number 1.2 Revision Date 10/30/2012 Page 1 of 6 Print Date 10/30/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLKPWDMB (5.00% Black 9887)
Product code	:	VC10003236
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Iron chromite brown spinel	12737-27-8	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET BLKPWDMB (5.00% Black 9887)

Version Number 1.2 Revision Date 10/30/2012 Page 2 of 6 Print Date 10/30/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

PolyOne.

MATERIAL SAFETY DATA SHEET BLKPWDMB (5.00% Black 9887)

sion Number 1.2 ision Date 10/30/2012			Print D	Page 3 Date 10/30/2
	ci ci	nly in areas with appropriate ondensates may contain com lean hoods, ducts, and other nese materials.	bustible or toxic residue.	Periodically
Storage		eep containers dry and tight nd contamination. Keep in a		e absorption
8.	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection		o personal respiratory protections occur wear a		
Eye/Face Protection	: S	afety glasses with side-shield	ds	
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	p p n n e u v v p V V V	landle in accordance with go ractice. Wash hands before roduct may contain residual umber 75-01-4) below 8.5 pp ormal working conditions with xposure limits will be exceed ser should take the necessary entilation, local exhaust vent rotection, etc.) to ensure airb 'CM or dusts that may be rel elow regulated levels.	breaks and at the end of w vinyl chloride monomer (om (0.00085%). It is unlik ith adequate ventilation, the led for residual VCM. Ho precautions (e.g. mechan ilation, air-monitoring, re- orne levels of any vapors	orkday. This VCM) (CAS ely, under nat the wever, the ical spiratory including
Engineering measures		leat only in areas with appropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Iron chromite brown spinel	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL PR	ROPERTIES	
Form Appearance	: solid : pelle			t applicable t determined

MATERIAL SAFETY DATA SHEET BLKPWDMB (5.00% Black 9887)

Version Number 1.2 Revision Date 10/30/2012

_

Page 4 of 6 Print Date 10/30/2012

Odour Melting point/range Boiling Point: Water solubility	very faintNot determinednot applicableinsoluble	Vapour pressure Vapour density pH	not applicablenot applicablenot applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	s prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials		strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), other hazar Prolonged heating (200 °C) or short te	O2), carbon monoxide (C0 dous materials, and smoke (approximately 30 minute erm heating at 482 °F (250 ition and evolution of carb	e are all possible. s or more) above 392 °F) °C) may result in

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12737-27-8	Iron chromite brown	Irritant	Eyes, Skin, Respiratory
	spinel		system.

Additional Health Hazard Information:

Iron chromite brown spinel 12737-27-8 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **BLKPWDMB (5.00% Black 9887)**

Version Number 1.2 Revision Date 10/30/2012 Page 5 of 6 Print Date 10/30/2012

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
	Extremely Hererdove Substance
SARA Title III Section 302 l	Extremely mazaruous Substance

MATERIAL SAFETY DATA SHEET **BLKPWDMB (5.00% Black 9887)**

Version Number 1.2 Revision Date 10/30/2012 Page 6 of 6 Print Date 10/30/2012

SARA Title III Section 313 Toxic Chemicals:

U	nless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	s regulation
	Chemical Name	CAS-No.	Weight percent	
	CHROMIUM III COMPOUNDSCHROMIUM	12737-27-8	5.00 - 10.00	
	COMPOUNDS			

Canadian Regulations:

Chemical Name			CAS-No.	Weight	NPRI ID#
Iron chromite brown spinel			12737-27-8	percent 5.00 - 10.00	
WHMIS Classification	:	D2B			
WHMIS Ingredient Disc	closu	are List			
CAS-No.					
12737-27-8					
DSL	:			re on the Canadiar	Domestic
		Substances List	t (DSL) or are exe	mpt.	
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	l		
Japan LIVES					
Korea KECI	:	Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.