MATERIAL SAFETY DATA SHEET GEON B5500 RED

Version Number 1.3 Revision Date 02/20/2007

Page 1 of 6 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON B5500 RED
Product code	:	VC10003408
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %	
Calcium carbonate	1317-65-3	10 - 30	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **GEON B5500 RED**

Version Number 1.3 Revision Date 02/20/2007 Page 2 of 6 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



MATERIAL SAFETY DATA SHEET **GEON B5500 RED**

sion Number 1.3 vision Date 02/20/2007			Print D	Page 3 of 6 ate 11/26/2011	
	c	ondensates may contain combu lean hoods, ducts, and other su nese materials.			
Storage		eep containers dry and tightly nd contamination. Keep in a d		absorption	
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection		o personal respiratory protecti usty conditions occur wear app			
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.					
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	10 mg/m3	Time Weighted Average (TWA):		MX OEL	
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL	
	9. PHYSICAL AND CHEMICAL PROPERTIES				
Form Appearance	: Solic : Pelle	1		applicable determined	
		3/6			

MATERIAL SAFETY DATA SHEET **GEON B5500 RED**

Version Number 1.3 Revision Date 02/20/2007 Page 4 of 6 Print Date 11/26/2011

Color Odor Melting point/range Boiling Point: Water solubility	 : RED : Very faint : Not determined : Not applicable : Insoluble 	Bulk density Vapor pressure Vapour density pH	Not establishedNot applicableNot applicableNot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open to not overheat.	flame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), other hazar Prolonged heating	O2), carbon monoxide (C cdous materials, and smok (approximately 30 minute erm heating at 482 °F (250	e are all possible.

11. TOXICOLOGICAL INFORMATION

chloride.

decomposition and evolution of carbon monoxide and hydrogen

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where



MATERIAL SAFETY DATA SHEET **GEON B5500 RED**

/ersion Number 1.3 Revision Date 02/20/2007		Page 5 of 6 Print Date 11/26/2011			
Contaminated packaging	:	possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	1	4. TRANSPORT INFORMATION			
U.S. DOT Classification ICAO/IATA (air)	:	Not regulated for transportation. Not regulated for transportation.			
IMO / IMDG (maritime)	:	Not regulated for transportation.			
	15	5. REGULATORY INFORMATION			
US Regulations:					
OSHA Status	:	Classified as hazardous based on components.			
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardou	ıs Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65	n :	Not applicable			
SARA Title III Section 302 E	Extrem	ely Hazardous Substance			
Unless specific chemicals are	identi	fied under this section, this product is Not Applicable under this regulation			
SARA Title III Section 313 T	SARA Title III Section 313 Toxic Chemicals:				
Unless specific chemicals are	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
Canadian Regulations:					

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET GEON B5500 RED

Version Number 1.3 Revision Date 02/20/2007

_

Page 6 of 6 Print Date 11/26/2011

National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.