MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010 Page 1 of 7 Print Date 1/14/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	NOVABLEND 4525 Trans 9123
Product code	VC10003601
Chemical Name	Mixture
CAS-No.	Mixture
Product Use	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Dioctyltin bis(2-ethylhexylmercaptoacetate)	15571-58-1	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Chrome exposure		

PolyOne.

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010 Page 2 of 7 Print Date 1/14/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

sion Number 1.4 sion Date 09/13/2010	Page : Print Date 1/14/
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically
	clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Thi product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 5 ppb (0.0000005%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolyOne

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010

Page 4 of 7 Print Date 1/14/2012

Components	Value	Exposure time	Exposure type	List:
Dioctyltin bis(2- ethylhexylmercaptoace tate)	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	e as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Lin (STEL):	nit as Sn	ACGIH
	9. PHYSI	CAL AND CHEMICAL P	PROPERTIES	
Appearance Colour Odour Melting point/range Boiling Point: Water solubility	: TRA : very : Not	NSPARENT But faint Va determined Va upplicable pH	lk density : pour pressure : pour density :	Not determined Not established not applicable not applicable not applicable
	10. 5	STABILITY AND REAC	ΓΙVITY	
Stability	: S	table		
Hazardous Polymerizatio	n : V	Vill not occur.		
Conditions to avoid		Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
Incompatible Materials		Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.		
Hazardous decomposition products	()	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.		

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
15571-58-1	Dioctyltin bis(2- ethylhexylmercaptoacetate)	Systemic effects	Respiratory system, central nervous system (CNS).

PolyOne.

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010 Page 5 of 7 Print Date 1/14/2012

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species	
15571-58-1	Dioctyltin bis(2- ethylhexylmercaptoacetate)	Oral LD50	2,100 mg/kg	rat	
	12. ECOLOGICA	AL INFORMAT	ION		
Persistence and degrad	ability : Not readily bio	degradable.			
Environmental Toxicit	y : Adverse ecolog use.	: Adverse ecological impact is not known or expected under normal use.			
Bioaccumulation Poten	ntial : no data availab	le			
Additional advice	: not applicable				
	13. DISPOSAL (CONSIDERATIO	ONS		
Product:Like most thermoplastic plas possible recycling is preferre generator of waste material h classification, transportation applicable federal, state/provContaminated packaging:Recycling is preferred when material has the responsibilit transportation and disposal in state/provincial and local reg		ing is preferred to aste material has t ransportation and oral, state/provinc referred when pos e responsibility for and disposal in ac	o disposal or inciner the responsibility for disposal in accord al and local regulat sible. The generato or proper waste class cordance with appl	ration. The or proper waste ance with tions. or of waste ssification,	
	14. TRANSPOR	T INFORMATI	ON		
U.S. DOT Classificatio	on : Not regulated f	or transportation.			
ICAO/IATA : Not regulated f		for transportation.			
IMO/IMDG (maritime) : Not regulated for transportation.					
	15. REGULATO	RY INFORMAT	ION		
US Regulations:					
OSHA Status	: Classified as ha	azardous based or	n components.		
TSCA Status	: All component TSCA Inventor	-	are listed on or exe	mpt from the	

PolyOne

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010 Page 6 of 7 Print Date 1/14/2012

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
15571-58-1
13371-38-1

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

PolyOne

MATERIAL SAFETY DATA SHEET NOVABLEND 4525 Trans 9123

Version Number 1.4 Revision Date 09/13/2010 Page 7 of 7 Print Date 1/14/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.