PolvOne

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014

Page 1 of 8 Print Date 3/19/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | GEON 8700A BLUE 4603 |
| Product code | : | VC10003769 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | • | Industrial Applications |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|-------------------|------------|----------------|
| Talc | 14807-96-6 | 0.1 - 1 |
| Calcium stearate | 1592-23-0 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Calcium carbonate | 471-34-1 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact | |
|---------------------|---|--|
| Acute exposure | | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. | |
| Ingestion | : May be harmful if swallowed. | |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. | |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. | |

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014 Page 2 of 8 Print Date 3/19/2014

| Medical Conditions: None known.Aggravated by Exposure: | | | |
|---|--|--|--|
| | 4. F | IRST AID MEASURES | |
| Inhalation | overl | e to fresh air in case of accidental inhalation of fumes from heating or combustion. When symptoms persist or in all cases of t seek medical advice. | |
| Ingestion | | ot induce vomiting without medical advice. When symptoms st or in all cases of doubt seek medical advice. | |
| Eyes | | e immediately with plenty of water, also under the eyelids, for at 15 minutes. If eye irritation persists, seek medical attention. | |
| Skin | | n off with soap and plenty of water. If skin irritation persists medical attention. | |
| | 5. FII | REFIGHTING MEASURES | |
| Flash point | : not a | pplicable | |
| Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media | : not a : Not a | pplicable pplicable pplicable on dioxide blanket, Water spray, Dry powder, Foam. | |
| Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | press conta : May fire c oxide all po | ace self-contained breathing apparatus (SCBA) used in positive ure mode should be worn to prevent inhalation of airborne uminants. emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under onditions. Carbon dioxide (CO2), carbon monoxide (CO), es of nitrogen (NOx), other hazardous materials, and smoke are ossible. | |
| | ACCID | ENTAL RELEASE MEASURES | |
| Personal precautions | | appropriate personal protection during cleanup, such as rvious gloves, boots and coveralls. | |
| Environmental precautions | | ld not be released into the environment. The product should not lowed to enter drains, water courses or the soil. | |
| Methods for cleaning up | | n up promptly by sweeping or vacuum. Package all material in ic, cardboard or metal containers for disposal. | |

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014 Page 3 of 8 Print Date 3/19/2014

| | 7. HANDLING AND STORAGE | | |
|-----------------------------------|---|---|--|
| Handling | : Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation. Processing fur condensates may contain combustible or toxic residue. Periodical clean hoods, ducts, and other surfaces to minimize accumulation of these materials. | ne lly | |
| Storage | : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | |
| 8. EXI | POSURE CONTROLS/PERSONAL PROTECTION | | |
| Respiratory protection | : No personal respiratory protective equipment normally required. dusty conditions occur wear appropriate respiratory protection. | If | |
| Eye/Face Protection | : Safety glasses with side-shields | | |
| Hand protection | : Protective gloves | | |
| Skin and body protection | : Long sleeved clothing | | |
| Additional Protective Measures | : Safety shoes | | |
| General Hygiene Considerations | : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. T product may contain residual vinyl chloride monomer (VCM) (CA number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing a below regulated levels. | AS | |
| Engineering measures | : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | | |
| Exposure limit(s) | | | |
| Exposure min(s) | | | |

PolyOne

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014 Page 4 of 8 Print Date 3/19/2014

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|-----------|--------------------------------------|----------------------|----------|
| Calcium stearate | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 5 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | OSHA Z1A |
| | 15 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | | MX OEL |
| | 5 mg/m3 | Recommended exposure limit (REL): | Respirable. | NIOSH |
| | 10 mg/m3 | Recommended exposure limit (REL): | Total | NIOSH |
| Talc | 2 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |
| | 2 mg/m3 | Recommended exposure limit (REL): | Respirable. | NIOSH |
| | 2 mg/m3 | Time Weighted Average (TWA): | Respirable dust. | OSHA Z1A |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | Respirable. | Z3 |
| | 0.3 mg/m3 | Time Weighted Average (TWA): | Total dust. | Z3 |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets, powder
 BLUE
 very faint
 Not determined
 not applicable
 insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY

PolvOne

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014 Page 5 of 8 Print Date 3/19/2014

| Stability | : | The product is stable if stored and handled as prescribed. |
|----------------------------------|---|---|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-------------------|------------------|------------------------------------|
| 14807-96-6 | Talc | Systemic effects | Eyes, Respiratory system, Skin. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 471-34-1 | Calcium carbonate | Irritant | Eyes, Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------|--------------------------------------|--|-------------|
| 1592-23-0 | Calcium stearate | Oral LD50 | > 10 gm/kg | rat |
| 471-34-1 | Calcium carbonate | Oral LD50Oral LD50Oral LD50 | 6,450 mg/kg6,450 mg/kg6,450 mg/kg | ratratmouse |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 14807-96-6 | Talc | no | 2B | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014

Page 6 of 8 Print Date 3/19/2014

1 - The component is carcinogenic to humans. 2A - The component is probably carcinogenic to humans. 2B - The component is possibly carcinogenic to humans. NTP Carcinogen Classifications: 1 - The component is known to be a human carcinogen. 2 - The component is reasonably anticipated to be a human carcinogen. **12. ECOLOGICAL INFORMATION** Persistence and degradability : Not readily biodegradable. Environmental Toxicity Adverse ecological impact is not known or expected under normal : use. **Bioaccumulation Potential** no data available ٠ Additional advice not applicable : 13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging Recycling is preferred when possible. The generator of waste : material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification Not regulated for transportation. : ICAO/IATA Not regulated for transportation. : IMO/IMDG (maritime) Not regulated for transportation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302)

PolyOne

MATERIAL SAFETY DATA SHEET GEON 8700A BLUE 4603

Version Number 1.2 Revision Date 03/12/2014 Page 7 of 8 Print Date 3/19/2014

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight | NPRI ID# |
|--------------------------------|------------|-------------|----------|
| | | percent | |
| Hematite, chromium green black | 68909-79-5 | 0.10 - 1.00 | |
| Phthalocyanine blue | 147-14-8 | 1.00 - 5.00 | |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|----------|--|
| 147-14-8 | |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Listed |
|----------------|---|----------------|
| China IECS | : | Not determined |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Listed |

:

PolyOne

MATERIAL SAFETY DATA SHEET **GEON 8700A BLUE 4603**

Version Number 1.2 Revision Date 03/12/2014 Page 8 of 8 Print Date 3/19/2014

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.