## MATERIAL SAFETY DATA SHEET GEON MP65M BLACK 2999

Version Number 1.0 Revision Date 09/10/2007 Page 1 of 6 Print Date 11/28/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	GEON MP65M BLACK 2999
Product code :	VC10004934
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **GEON MP65M BLACK 2999**

Version Number 1.0 Revision Date 09/10/2007 Page 2 of 6 Print Date 11/28/2011

	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>			
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume			

POLYONE CORPORATION

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **GEON MP65M BLACK 2999**

Version Number 1.0 Revision Date 09/10/2007 Page 3 of 6 Print Date 11/28/2011

	condensates may contain combustible or toxic resclean hoods, ducts, and other surfaces to minimiz these materials.	
Storage	Keep containers dry and tightly closed to avoid m and contamination. Keep in a dry, cool place.	oisture absorption
8. EXP	RE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	No personal respiratory protective equipment nor dusty conditions occur wear appropriate respirato	
Eye/Face Protection	Safety glasses with side-shields	
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	Handle in accordance with good industrial hygien Wash hands before breaks and at the end of work may contain residual vinyl chloride monomer (Vo 75-01-4) below 8.5 ppm (0.00085%). It is unlikel working conditions with adequate ventilation, tha will be exceeded for residual VCM. However, the necessary precautions (e.g. mechanical ventilation ventilation, air-monitoring, respiratory protection airborne levels of any vapors including VCM or or released during heating or processing are below re	day. This product CM) (CAS number y, under normal t the exposure limits e user should take the n, local exhaust , etc.) to ensure husts that may be
Engineering measures	Heat only in areas with appropriate exhaust ventil appropriate exhaust ventilation at machinery.	ation. Provide
Exposure limit(s)		

Value Exposure time Components Exposure type List: PEL: Calcium carbonate 5 mg/m3 Respirable fraction. OSHA Z1 15 mg/m3 PEL: Total dust. OSHA Z1 Time Weighted Average MX OEL 10 mg/m3 (TWA): Short Term Exposure Limit 20 mg/m3 MX OEL (STEL):

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid: pellets, powder

Evaporation rate Specific Gravity Not applicableNot determined

3/6

PolyOne.

## MATERIAL SAFETY DATA SHEET **GEON MP65M BLACK 2999**

Version Number 1.0 Revision Date 09/10/2007 Page 4 of 6 Print Date 11/28/2011

Color Odour Melting point/range Boiling Point: Water solubility	: BLACKBulk density: Not established: Very faintVapour pressure: Not applicable: Not determinedVapour density: Not applicable: Not applicablepH: Not applicable: Insoluble: Insoluble: Not applicable
	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.</li> </ul>

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

egradable.
cal impact is not known or expected under normal use.
e
ONSIDERATIONS
(

PolyOne.

# MATERIAL SAFETY DATA SHEET **GEON MP65M BLACK 2999**

ersion Number 1.0 Revision Date 09/10/2007	Page 5 of 6 Print Date <i>11/28/2011</i>
Contaminated packaging	<ul> <li>possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal.</li> </ul>
	14. TRANSPORT INFORMATION
U.S. DOT Classification ICAO/IATA (air) IMO / IMDG (maritime)	<ul> <li>Not regulated for transportation.</li> <li>Not regulated for transportation.</li> <li>Not regulated for transportation.</li> </ul>
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	

PolyOne

## MATERIAL SAFETY DATA SHEET GEON MP65M BLACK 2999

Version Number 1.0 Revision Date 09/10/2007 Page 6 of 6 Print Date 11/28/2011

Chemical Name			CAS-No.	Weight %	NPRI ID#
2-Ethylhexanoic acid zinc salt		136-53-8	0.10 - 1.00		
Barium bis(nonylphenolate)			28987-17-9	0.10 - 1.00	
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
ational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.