PolyOne

## MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007 Page 1 of 7 Print Date 12/3/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	87256 BLUE
Product code :	VC10005304
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1
Calcium stearate	1592-23-0	1 - 5
Calcium carbonate	471-34-1	5 - 10

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007 Page 2 of 7 Print Date 12/3/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007		Page 3 of 7 Print Date 12/3/2011
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

## MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007 Page 4 of 7 Print Date 12/3/2011

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Calcium carbonate	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
  pellets, powder
  BLUE
  Very faint
  Not determined
  Not applicable
  Insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	: Stable.	
Hazardous Polymerization	: Will not occ	ır.
Conditions to avoid	1 2	rom oxidizing agents and open flame. To avoid thermal on, do not overheat.
Incompatible Materials	-	e with strong acids and oxidizing agents., Avoid contact omopolymers and acetal copolymers during processing.
Hazardous decomposition products	(NOx), other Prolonged he (200 °C) or s	ide (CO2), carbon monoxide (CO), oxides of nitrogen hazardous materials, and smoke are all possible. eating (approximately 30 minutes or more) above 392 °F short term heating at 482 °F (250 °C) may result in emposition and evolution of carbon monoxide and loride.
	I. TOXICOLO	GICAL INFORMATION

## MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007 Page 5 of 7 Print Date 12/3/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

	13.	DISPOSAL CONSIDERATIONS
Additional advice	: 1	Not applicable
Bioaccumulation Potential	: 1	No data available
Environmental Toxicity		Adverse ecological impact is not known or expected under normal use.
Persistence and degradability	: 1	Not readily biodegradable.

Product

: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste



# MATERIAL SAFETY DATA SHEET **87256 BLUE**

sion Number 1.0	Page 6 o
ision Date 12/13/2007	Print Date 12/3/20
	classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulati
Canadian Regulations:	

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **87256 BLUE**

Version Number 1.0 Revision Date 12/13/2007 Page 7 of 7 Print Date 12/3/2011

Chemical Name			CAS-No.	Weight %	NPRI ID#
Diphosphoric acid, ammonium manganese(3+)			10101-66-3	0.10 - 1.00	147
salt (1:1:1)					
Phthalocyanine blue			147-14-8	0.10 - 1.00	71
WHMIS Classification	:	D2A			
DSL	:	All components of this product are on the Canadian Domestic			
		Substances List (DSL) or are exempt.			
Jational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	1		
		<b>T T T</b>			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
**					
		16. OTHER I	NFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.