MATERIAL SAFETY DATA SHEET **GEON X15506902601 TRANS**

Version Number 1.2 Revision Date 05/31/2012 Page 1 of 6 Print Date 8/26/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	GEON X15506902601 TRANS
Product code	VC10005603
Chemical Name	Mixture
CAS-No.	Mixture
Product Use	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON X15506902601 TRANS**

Version Number 1.2 Revision Date 05/31/2012 Page 2 of 6 Print Date 8/26/2012

Medical Conditions : None known. Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne 	
Unusual Fire/Explosion Hazards	 contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	

PolyOne

MATERIAL SAFETY DATA SHEET GEON X15506902601 TRANS

Version Number 1.2 Revision Date 05/31/2012 Page 3 of 6 Print Date 8/26/2012

	7. HANDLING A	ND STORAGE	
Handling	only in areas with condensates may	prevent the build up of electrostatic charge. Heat appropriate exhaust ventilation. Processing fume contain combustible or toxic residue. Periodically s, and other surfaces to minimize accumulation of	
Storage	-	ry and tightly closed to avoid moisture absorption n. Keep in a dry, cool place.	
8. EXI	POSURE CONTROLS/	PERSONAL PROTECTION	
Respiratory protection		ratory protective equipment normally required. If occur wear appropriate respiratory protection.	
Eye/Face Protection	: Safety glasses with	h side-shields	
Hand protection	: Protective gloves		
Skin and body protection	: Long sleeved clot	hing	
Additional Protective Measures	: Safety shoes		
General Hygiene Considerations	practice. Wash h product may cont number 75-01-4) normal working c exposure limits w user should take t ventilation, local protection, etc.) to VCM or dusts tha	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 5 ppb (0.0000005%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.	
Engineering measures		with appropriate exhaust ventilation. Provide st ventilation at machinery.	
Exposure limit(s)			
9.	PHYSICAL AND CHE	MICAL PROPERTIES	
Form	: solid	Evaporation rate : Not applicable	
Appearance Colour	: pellets, powder : TRANSPARENT	Specific Gravity: Not determinedBulk density: Not established	

3/6

PolyOne

MATERIAL SAFETY DATA SHEET **GEON X15506902601 TRANS**

Version Number 1.2 Revision Date 05/31/2012

_

Page 4 of 6 Print Date 8/26/2012

Odour Melting point/range Boiling Point: Water solubility	 very faint Not determined not applicable insoluble 	Vapour pressure Vapour density pH	not applicablenot applicablenot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	oxidizing agents and open f o not overheat.	lame. To avoid thermal
Incompatible Materials		strong acids and oxidizing oolymers and acetal copoly	
Hazardous decomposition products	(NOx), other haza Prolonged heating (200 °C) or short t	CO2), carbon monoxide (CO rdous materials, and smoke (approximately 30 minute term heating at 482 °F (250 sition and evolution of carb	e are all possible. s or more) above 392 °F) °C) may result in

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-	Irritant	Eyes, Skin.
	stannatetradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-		
	oxo-, 2-ethylhexyl ester		

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: no data available
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON X15506902601 TRANS**

Version Number 1.2 Revision Date 05/31/2012	Page 5 of 6 Print Date <i>8/26/2012</i>			
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.			
IMO/IMDG (maritime)	: Not regulated for transportation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous S	ubstances (40 CFR 302)			
not applicable				
California Proposition 65	: Not applicable			
SARA Title III Section 302 Extra	SARA Title III Section 302 Extremely Hazardous Substance			
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
SARA Title III Section 313 Toxi	c Chemicals:			
Unless specific chemicals are ide	ntified under this section, this product is Not Applicable under this regulation			

PolyOne

MATERIAL SAFETY DATA SHEET **GEON X15506902601 TRANS**

Version Number 1.2 Revision Date 05/31/2012

_

Page 6 of 6 Print Date 8/26/2012

Canadian Regulations:				
National Pollutant Release Inventory (NPRI)				
not applicable	not applicable			
WHMIS Classification	:	D2B		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.