PolvOne

### MATERIAL SAFETY DATA SHEET BLKPWDMB (15% Black V-778)

Version Number 1.1 Revision Date 03/14/2013 Page 1 of 6 Print Date 3/14/2013

1.	PROD	UCT AND COMPANY IDENTIFICATION
POLYONE CORPORATI		
33587 Walker Road, Avoi	1 Lake,	OH 44012
Telephone		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone		CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number	•	or accident).
Product name	:	BLKPWDMB (15% Black V-778)
Product code	:	VC10006169
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use		Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Hematite, chromium green black	68909-79-5	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET **BLKPWDMB (15% Black V-778)**

Version Number 1.1 Revision Date 03/14/2013 Page 2 of 6 Print Date 3/14/2013

Medical Conditions Aggravated by Exposure:	: None known.				
	4. FIRST AID MEASURES				
Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.					
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIREFIGHTING MEASURES				
Flash point	: not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>				
	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.				
	7. HANDLING AND STORAGE				
Handling	: Take measures to prevent the build up of electrostatic charge. Heat				

PolyOne.

# MATERIAL SAFETY DATA SHEET BLKPWDMB (15% Black V-778)

ion Number 1.1 sion Date 03/14/2013			Print	Page 3 Date <i>3/14/</i> 2
	co cl	nly in areas with appropriat ondensates may contain con lean hoods, ducts, and other nese materials.	nbustible or toxic residue.	Periodically
Storage		eep containers dry and tigh nd contamination. Keep in		re absorption
8.]	EXPOSURE	CONTROLS/PERSONA	L PROTECTION	
Respiratory protection		o personal respiratory prote usty conditions occur wear		
Eye/Face Protection	: S	afety glasses with side-shie	lds	
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	pi pi ni ni e: u: vi pi V V	landle in accordance with geractice. Wash hands before roduct may contain residual umber 75-01-4) below 8.5 promal working conditions waxposure limits will be exceed ser should take the necessar entilation, local exhaust ver rotection, etc.) to ensure air CM or dusts that may be reelow regulated levels.	breaks and at the end of v vinyl chloride monomer ( opm (0.00085%). It is unlit vith adequate ventilation, t ded for residual VCM. Ho y precautions (e.g. mechan tilation, air-monitoring, re borne levels of any vapors	vorkday. This (VCM) (CAS kely, under hat the owever, the nical espiratory including
Engineering measures		leat only in areas with appropriate exhaust ventilation		. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Hematite, chromium green black	0.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL P	ROPERTIES	
Form	: solid			t applicable
Appearance Colour	: pelle : BLA			t determined t established

# MATERIAL SAFETY DATA SHEET BLKPWDMB (15% Black V-778)

Version Number 1.1 Revision Date 03/14/2013

\_\_\_\_

Page 4 of 6 Print Date 3/14/2013

Odour Melting point/range Boiling Point: Water solubility	<ul><li>very faint</li><li>Not determined</li><li>not applicable</li><li>insoluble</li></ul>	Vapour pressure Vapour density pH	
	10. STABILITY ANI	O REACTIVITY	
Stability	: The product is stabl	le if stored and handled as	s prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do	idizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials		strong acids and oxidizing lymers and acetal copoly	
Hazardous decomposition products	(NOx), other hazard Prolonged heating ( (200 °C) or short te	D2), carbon monoxide (C0 dous materials, and smoke (approximately 30 minute rm heating at 482 °F (250 tion and evolution of carb	e are all possible. s or more) above 392 °F ) °C) may result in

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68909-79-5	Hematite, chromium green black	Irritant	Eyes, Skin.

#### Additional Health Hazard Information:

Hematite, chromium green black 68909-79-5 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
<b>Bioaccumulation Potential</b>	:	no data available

PolyOne.

# MATERIAL SAFETY DATA SHEET **BLKPWDMB (15% Black V-778)**

Version Number 1.1 Revision Date 03/14/2013 Page 5 of 6 Print Date 3/14/2013

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
	: Not applicable
California Proposition 65	
65	xtremely Hazardous Substance

# MATERIAL SAFETY DATA SHEET **BLKPWDMB (15% Black V-778)**

Version Number 1.1 Revision Date 03/14/2013 Page 6 of 6 Print Date 3/14/2013

SARA Title III Section 313 Toxic Chemicals:

U	Inless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	s regulation
	Chemical Name	CAS-No.	Weight percent	
	CHROMIUM III COMPOUNDSCHROMIUM III	68909-79-5	10.00 - 30.00	
	COMPOUNDSCHROMIUM COMPOUNDS			

Canadian Regulations:

Chemical Name		•	CAS-No.	Weight percent	NPRI ID#
Hematite, chromium green b	lack		68909-79-5	10.00 - 30.00	
WHMIS Classification	:	D2B			
WHMIS Ingredient Disc	closu	ire List			
CAS-No. 68909-79-5					
DSL	:		ts of this product a t (DSL) or are exe	are on the Canadian mpt.	1 Domestic
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Not determined	l		
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	l		
Korea KECI	:	Listed			

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.