MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

Version Number 1.5 Revision Date 07/18/2012 Page 1 of 6 Print Date 8/28/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	14405-06 EXPA600S NATURAL
Product code	:	VC10006502
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne

MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

Version Number 1.5 Revision Date 07/18/2012 Page 2 of 6 Print Date 8/28/2012

Medical Conditions Aggravated by Exposure:	None known.		
4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

rsion Number 1.5 vision Date 07/18/2012	Page 3 of 0 Print Date 8/28/2012
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	
There are no known hazardo	ous components above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:

solid
pellets, powder
TRANSPARENT
very faint
Not determined
not applicable

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

PolyOne

MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

Version Number 1.5 Revision Date 07/18/2012 Page 4 of 6 Print Date 8/28/2012

	10. STABILITY AND REACTIVITY
Stability	: Stable
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °I (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.
	11. TOXICOLOGICAL INFORMATION
TC1 1 1 1	
There are no known hazardous	s components above regulatory thresholds in this product. 12. ECOLOGICAL INFORMATION
Persistence and degradability	12. ECOLOGICAL INFORMATION
Persistence and degradability Environmental Toxicity	12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal
Persistence and degradability Environmental Toxicity Bioaccumulation Potential	12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal use.
Persistence and degradability Environmental Toxicity Bioaccumulation Potential	12. ECOLOGICAL INFORMATION 12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal use. : no data available
Persistence and degradability Environmental Toxicity Bioaccumulation Potential Additional advice Product	12. ECOLOGICAL INFORMATION : Not readily biodegradable. : Adverse ecological impact is not known or expected under normal use. : no data available : not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

Version Number 1.5 Revision Date 07/18/2012

Page 5 of 6 Print Date 8/28/2012

U.S. DOT Classification	. Not reculated	fortrongration		
U.S. DOT Classification	: Not regulated	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		
IMO/IMDG (maritime)	: Not regulated	for transportation.		
	15. REGULATO	RY INFORMAT	ION	
US Regulations:				
OSHA Status	: There are no k thresholds in t	cnown hazardous co his product.	omponents above	regulatory
TSCA Status	: All component TSCA Invento	nts of this product a	are listed on or exe	empt from the
US. EPA CERCLA Hazardous Substances (40 CFR 302)				
not applicable				
California Proposition 65	: Not applicable	2		
SARA Title III Section 302 E	xtremely Hazardous S	Substance		
Unless specific chemicals are	identified under this	section, this produc	t is Not Applicabl	e under this regulatio
SARA Title III Section 313 T	ovia Chamicala			
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
Canadian Regulations:				
National Pollutant Rel	ease Inventory (NPRI			
Chemical Name		CAS-No.	Weight percent	NPRI ID#
Barium bis(nonylphenolate)	28987-17-9	0.10 - 1.00	
WHMIS Classification	n : Not controlled	l.		
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				

PolyOne

MATERIAL SAFETY DATA SHEET 14405-06 EXPA600S NATURAL

Version Number 1.5 Revision Date 07/18/2012 Page 6 of 6 Print Date 8/28/2012

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.