PolvOne

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

Version Number 1.2 Revision Date 03/29/2014 Page 1 of 6 Print Date 4/5/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
number	•	or accident).		
Product name	:	SFR 3 BLACK (PRICING ONLY)		
Product code	:	VC10007119		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

Version Number 1.2 Revision Date 03/29/2014 Page 2 of 6 Print Date 4/5/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

PolyOne.

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

sion Number 1.2 ision Date 03/29/2014			Prin	Page 3 (t Date 4/5/2)
	c c	nly in areas with appropriate e ondensates may contain combu lean hoods, ducts, and other su nese materials.	stible or toxic residue.	Periodically
Storage		Keep containers dry and tightly nd contamination. Keep in a d		e absorption
8.	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection		No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.		
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	Protective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	p p n e u v v v v	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.		
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20		}	MV OFI

9. PHYSICAL AND CHEMICAL PROPERTIES

(STEL):

MX OEL

20 mg/m3 Short Term Exposure Limit

PolyOne

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

Version Number 1.2 Revision Date 03/29/2014

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets, powder BLACK very faint Not determined not applicable insoluble 	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	
	10. STABILITY ANI	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	kidizing agents and open flands overheat.	ame. To avoid thermal
Incompatible Materials		strong acids and oxidizing olymers and acetal copolyn	
Hazardous decomposition products	(NOx), other hazar Prolonged heating (200 °C) or short te	O2), carbon monoxide (CO dous materials, and smoke (approximately 30 minutes erm heating at 482 °F (250 tion and evolution of carbo	are all possible. or more) above 392 °F °C) may result in

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available
Additional advice	:	not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

Version Number 1.2 Revision Date 03/29/2014 Page 5 of 6 Print Date 4/5/2014

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
SARA Title III Section 302 1	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313	Foxic Chemicals:

PolvOne

MATERIAL SAFETY DATA SHEET SFR 3 BLACK (PRICING ONLY)

Version Number 1.2 Revision Date 03/29/2014 Page 6 of 6 Print Date 4/5/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight	NPRI ID#
				percent	
Phthalocyanine green			1328-53-6	0.10 - 1.00	
2-Ethylhexanoic acid zinc salt			136-53-8	0.10 - 1.00	
Barium bis(nonylphenolate)			28987-17-9	0.10 - 1.00	
WHMIS Classification	:	Not controlled.			
DSL	:		s of this product a (DSL) or are exer		n Domestic
lational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
China IECS Europe EINECS	: :	Not determined Listed			
	:				
Europe EINECS	:	Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.