PolvOne

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

Version Number 1.2 Revision Date 03/29/2014 Page 1 of 6 Print Date 4/5/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION			
33587 Walker Road, Avon Lake, OH 44012			
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	15895-01 EXPBP70U0 BLACK 2999	
Product code	:	VC10007170	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use		Industrial Applications	

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent	
Calcium carbonate	1317-65-3	1 - 5	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
: Resin particles, like other inert materials, can be mechanically irritating.
: May be harmful if swallowed.
: Resin particles, like other inert materials, are mechanically irritating to eyes.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

Version Number 1.2 Revision Date 03/29/2014 Page 2 of 6 Print Date 4/5/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES
	0. ACCIDENTAL KELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

PolyOne.

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

sion Number 1.2 vision Date 03/29/2014			Print	Page 3 of Date 4/5/201
	c c	nly in areas with appropriate ex ondensates may contain combu lean hoods, ducts, and other su nese materials.	stible or toxic residue. I	Periodically
Storage		Leep containers dry and tightly nd contamination. Keep in a d		absorption
8.]	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION	
Respiratory protection		lo personal respiratory protecti usty conditions occur wear app		
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations : Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.				
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	9. PHYSIC	CAL AND CHEMICAL PRO	PERTIES	

PolyOne

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

Version Number 1.2 Revision Date 03/29/2014

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets, powder BLACK very faint Not determined not applicable insoluble 	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	: Not established : not applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open fla not overheat.	ame. To avoid thermal
Incompatible Materials		strong acids and oxidizing olymers and acetal copolyn	
Hazardous decomposition products	(NOx), other hazar Prolonged heating (200 °C) or short to	O2), carbon monoxide (CO dous materials, and smoke (approximately 30 minutes erm heating at 482 °F (250 ition and evolution of carbo	are all possible. or more) above 392 °F °C) may result in

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available
Additional advice	:	not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

Version Number 1.2 Revision Date 03/29/2014 Page 5 of 6 Print Date 4/5/2014

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
SARA Title III Section 302	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313	Foxic Chemicals:

PolyOne.

MATERIAL SAFETY DATA SHEET 15895-01 EXPBP70U0 BLACK 2999

Version Number 1.2 Revision Date 03/29/2014 Page 6 of 6 Print Date 4/5/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
not applicable					
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
16. OTHER INFORMATION					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.